

Procedure for Testing and Evaluating the Performance of Friction (Drag) Reducers in Aqueous-based Fluid Flowing in Straight, Smooth Circular Conduits

API TECHNICAL REPORT 13M-5
FIRST EDITION, OCTOBER 2018



AMERICAN PETROLEUM INSTITUTE

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API document is solely responsible for complying with all the applicable requirements of that document. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API publication.

Copyright © 2018 American Petroleum Institute. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

Copyright © 2018 American Petroleum Institute

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API technical report. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, standards@api.org.

Currently in preview, click buy full version

Contents

	Page
1 Scope	1
2 Terms and Definitions	1
3 Measurement and Precision	2
4 Instrument Calibration	2
5 Friction Loop Calibration	2
5.1 Introduction	2
5.2 Flow Loop Schematic	2
5.3 Calibration Procedure	3
5.4 Calibration Data Analysis	3
5.5 Determination of the Internal Tubing or Pipe Diameter (d_i)	4
5.6 Calibration Example—Determination of Internal Pipe Diameter	5
6 Fluid Preparation, Testing, and Analysis	7
6.1 Base Fluid	7
6.2 Test Fluid	7
6.3 Fluid Testing	8
6.4 Data Analysis	8
6.5 Example—Friction Reducer Fluid Analysis	8
Annex A (informative) List of Symbols and Conversion Factors	12
Bibliography	13
Figures	
1 Typical Flow Loop System (Schematic)	2
2 Plot of Wall Shear Stress vs Wall Shear Rate for Fresh Water Solvent	6
3 Plot of Fanning Friction Factor vs Solvent Reynolds Number for Fresh Water	7
4 Plot of Fanning Friction Factor vs Friction Reducer Fluid Reynolds Number	10
5 Plot of Drag Reduction vs Friction Reducer Fluid Reynolds Number	10
6 Plot of Drag Reduction vs Velocity for Friction Reducer Fluid	11
7 Plot of Drag Reduction vs Wall Shear Rate for Friction Reducer Fluid	11
Tables	
1 Calibration Test Data	5
2 Calibration Test Calculations	6
3 Friction Reducer Test Fluid Data	9
4 Friction Reducer Test Fluid Calculations	9
A.1 Symbols, Definitions, and Units	12

Introduction

The objective of this document is to provide a standard procedure for testing and evaluating the performance of friction (drag) reducers in straight, smooth circular conduits. This standard procedure was compiled on the basis of several years of comparative testing, debate, discussion, and continued research by the industry.

In this standard, where practical, US Customary units are included in brackets for information. The units do not necessarily represent a direct conversion of SI to US Customary units, or US Customary to SI. Consideration has been given to the precision of the instrument making the measurement. For example, thermometers are typically marked in one degree increments, thus temperature values have been rounded to the nearest degree.

This document uses a format for numbers which follows the examples given in API Document Format and Style Manual (Revision Date: November 2017). In this document, the decimal mark is a period and separates the whole part from the fractional part of a number. No spaces are used in the numbering format. The thousands separator is a comma and is only used for numbers greater than 10,000 (i.e. 5000 items, 12,500 bags).

Currently in preview, click buy full version

Procedure for Testing and Evaluating the Performance of Friction (Drag) Reducers in Aqueous-based Fluid Flowing in Straight, Smooth Circular Conduits

1 Scope

1.1 This document provides a consistent methodology to test and evaluate the performance of friction (drag) reducers in straight, smooth circular conduits. This standard includes only smooth-walled tubing and excludes any rough-walled tubing.

1.2 The International System of Units (SI) is used in this Technical Report. However, testing data acquisition can be conducted using US customary units (USC).

1.3 Factors included in Annex A Table A.1 permit conversions of USC units to SI units or SI units to USC units.

2 Terms and Definitions

For the purposes of this document, the following terms and definitions apply.

2.1

base fluid

Aqueous liquid media (solvent with or without additives) used to prepare test fluid (see 2.8).

2.2

friction reducer

Agent that dissolves in base fluid, thereby reducing frictional resistance to flow.

2.3

straight, smooth circular conduits

Metallic-based smooth-walled straight tubing or pipe having a constant diameter.

2.4

drag reduction

friction reduction

Relative reduction in the change in pressure due to frictional resistance by the addition of friction reducer to the base fluid.

2.5

Reynolds number (N_{Re})

The ratio of inertial forces to viscous forces within a fluid (a dimensionless number).

2.6

Fanning friction factor (f)

For a fluid, the ratio of pipe wall shear stress to the flow kinetic energy (a dimensionless number).

2.7

solvent

Aqueous liquid used to prepare the test fluid (water, brine, etc.) and the fluid used to determine the internal diameter of the tubing or pipe (see 5.3).

NOTE For the purpose of the document, for determination of internal diameter of the tubing or pipe, the solvent is fresh water.

2.8

test fluid

Fluid prepared with the base fluid and the friction reducer.