

# Pressure Effects on Subsea Hardware During Flowline Pressure Testing in Deep Water

API TECHNICAL REPORT 17TR11  
FIRST EDITION, SEPTEMBER 2015



AMERICAN PETROLEUM INSTITUTE

## Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Classified areas may vary depending on the location, conditions, equipment, and substances involved in any given situation. Users of this standard should consult with the appropriate authorities having jurisdiction.

Users of this publication should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

## Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the specification.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the specification.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, [standards@api.org](mailto:standards@api.org).

Currently in preview, click buy full version

## Contents

	Page
1 Scope .....	1
2 Normative References.....	1
3 Terms, Definitions, Acronyms, and Abbreviations .....	1
3.1 Terms and Definitions.....	1
3.2 Acronyms and Abbreviations .....	3
4 Limitations on Subsea Testing Pressures .....	3
4.1 General .....	3
4.2 Case 1: Subsea Test Pressures at or Below $1.0 \times RWP_a$ .....	4
4.3 Case 2: Subsea Test Pressures Greater than $1.0 \times RWP_a$ and Not Above $1.0 \times RWP_d$ .....	4
4.4 Case 3: Subsea Test Pressures Greater than $1.0 \times RWP_d$ (Greater than $1.0 \times RWP_a$ ), but Not Above $1.5 \times RWP_a$ .....	6
4.5 Case 4: Subsea Test Pressures Greater than $1.5 \times RWP_a$ , but Not Above $1.5 \times RWP_d$ (or $1.25 \times MAOP$ ) .....	7
4.6 Case 5: Subsea Test Pressure over $1.5 \times RWP_d$ —Not Recommended .....	9
5 Separate Testing of Subsea Flowline and Riser .....	9
6 Recording of Subsea Pressure Tests .....	10
7 Testing of New vs Old Equipment .....	10
Bibliography .....	11
<b>Figures</b>	
1 Commissioning Test of Subsea Flowline with Riser—Case 1 .....	4
2 Commissioning Test of Subsea Flowline with Riser—Case 2 .....	5
3 Commissioning Test of Subsea Flowline with Riser—Case 3 .....	6
4 Commissioning Test of Subsea Flowline with Riser—Case 4 .....	8

## Introduction

Subsea hydrotesting demonstrates the structural integrity of the flowline system to tolerate the maximum allowable operating pressure (MAOP), and it confirms the sealing integrity of the pipeline system and subsea hardware components to contain hydrocarbon production. These subsea hardware components may include, but are not limited to, integral and flanged valves; flanged connections and other-end connections (OECs); jumper and flowline connectors and hubs; pressure caps and their vent valves; pressure/temperature sensors; chemical injection valves and porting; electrical penetrators; tees; crosses; pipe bends; fittings; and any similar items that will be pressurized during the subsea flowline pressure testing operations.

For subsea systems where the pressure source is at the wellhead, the MAOP is typically assigned to be equal to the wellhead shut-in tubing pressure (WHSITP). Present regulations do not allow the owner/operator to consider the gradient of produced fluids to determine a variable design pressure along flowline and riser as a function of elevation if flowline and riser are not separated by physical barriers. For more details on this issue see:

- 30 *Code of Federal Regulations (CFR) 250 Subpart J, Paragraph 250.1002;*
- *Notice to Lessees (NTL) 2009-G28, Alternate Compliance and Departure Requests for Pipeline Applications;*
- *OTC Technical Paper 25087, Formulating Guidance on Hydrotesting Deepwater Oil and Gas Pipelines.*

Pre-commissioning leak testing demonstrates the sealing integrity of the barriers for a fully assembled subsea production system to contain hydrocarbon production fluids (or injection fluids). The leak test pressure is normally applied as internal pressure within the flowline itself, but leak testing of individual connections may be applied as a backside seal test using test pressure from a remotely operated vehicle (ROV) or other remote pressure source. The preferred use of a backside seal test is a preliminary or cursory test to verify the integrity of a connection joint before an internal pressure test of the system. The backside pressure test is typically performed with agreement between the operator and manufacturer. The backside seal test port can also be used to monitor an individual connection for leakage during an internal pressure test (during diagnostics or troubleshooting).

There is a need to distinguish between surface shut-in tubing pressure (SSITP) and WHSITP. Standard subsea flowline hydrotest pressure typically exposes the flowline system to a differential pressure between  $1.25 \times \text{MAOP}$  and  $1.5 \times \text{MAOP}$  of the flowline at all locations and elevations. In some cases, the surface test pressure can be based on a calculated SSITP taking into account the hydrostatic head within the riser. In other cases, the surface test pressure may have to be 1.25 (or 1.5) times the initial WHSITP at the seabed, with no reduction allowed for density of produced fluids in the riser. **Thus, it is important to confirm whether the surface test pressure must be based on WHSITP or if it can be reduced, based on SSITP, considering density of produced fluids in the riser.**

# Pressure Effects on Subsea Hardware During Flowline Pressure Testing in Deep Water

## 1 Scope

This document provides guidance to the industry on allowable pressure loading of subsea hardware components that can occur during hydrotesting of subsea flowlines and risers and during pre-commissioning leak testing of these systems. There are potential problems with confusion arising from high hydrostatic pressure in deep water, partially due to the variety of applicable test specifications and partly from the inconsistent use of a variety of acronyms for pressure terminology.

With guidance, owner/operators can avoid unexpected loading conditions and the resulting potential for equipment damage, failure, or leakage (either immediate or delayed leaks) or reduced service life.

This document and the examples provided give the user guidance for evaluating subsea hydrotesting scenarios where test pressures are often well above maximum allowable operating pressure (MAOP).

## 2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API Technical Report 17TR8, *High-pressure High-temperature Design Guidelines*

API Technical Report 17TR12, *Consideration of External Pressure in the Design and Pressure Rating of Subsea Equipment*

## 3 Terms, Definitions, Acronyms, and Abbreviations

### 3.1 Terms and Definitions

For the purposes of this document, the following definitions apply.

#### 3.1.1

##### **absolute pressure**

Absolute pressure inside the components being tested, measured in “psia.”

#### 3.1.2

##### **barrier**

Element forming part of a pressure-containing envelope that is designed to prevent unintentional flow of produced/injected fluids, particularly to the external environment.

#### 3.1.3

##### **differential pressure**

Difference between the absolute pressure inside a component and the absolute pressure outside of the component at that location, measured in “psid.”

NOTE For the purposes of discussions in this document, “psig” and “psid” are the same if at the same water depth.