

Short-term Evaporative Loss Estimation from Atmospheric Storage Tanks

API TECHNICAL REPORT 2576
FIRST EDITION, JULY 2016



AMERICAN PETROLEUM INSTITUTE

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Copyright © 2016 American Petroleum Institute. All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

Copyright © 2016 American Petroleum Institute

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, standards@api.org.

Currently in preview, click buy full version

Contents

	Page
1 Scope	1
2 Normative References	1
3 Estimating Reasonable Worst-case Short-term Emissions from an Individual Storage Tank	1
3.1 Liquid Storage Temperature	1
3.2 Product Storage	2
3.3 Fixed-roof Tanks (Vented to Atmosphere, No Floating Roof)	3
3.4 Floating-roof Tanks	3
4 Estimating Reasonable Worst-case Short-term Emissions from a Battery of Storage Tanks	5
4.1 Overview	5
4.2 Overlaying Equipment Limitations	5
Annex A (informative) Limitations on Applicability to Actual Short-term Emission Estimates	7

Introduction

This Technical Report provides guidance on how to determine reasonable worst-case short-term hourly emissions from individual tanks and from a battery of tanks.

Currently available estimation methodologies are based on factors that rely on averaging throughputs and meteorological conditions on a yearly or monthly frequency and may deviate significantly when compared to a reasonable worst-case short-term duration of hours to days. This guidance document presents a standardized approach for estimating reasonable worst-case short-term emissions, but it does not address estimation of actual short-term emissions (see Annex A for limitations on applying this methodology to actual scenarios). This short-term approach combined with the dispersion model will provide the user the ability to assess potential higher mass scenarios relative to yearly averages and can be used for process safety assessments, structure siting, area classifications, determining the need for additional controls, assessing risk of potentially elevated hazardous air pollutants (HAPs) from a confluence of conditions, and other possible concerns associated with short-term scenarios such as approach to lower explosive limit (LEL) or odor potential.

Hourly and annual emissions are used in air dispersion models that evaluate a facility's risk against the National Ambient Air Quality Standards for the purpose of issuing construction and operating air permits. Hourly emission rates are also used to evaluate whether or not there has been an emission increase to determine if a tank has been "modified" and has become subject to a New Source Performance Standard (NSPS) or a New Source Review (NSR). EPA's 2011 Refinery MACT Information Collection Request (ICR) Protocol required reporting "maximum hourly average emission rates" based on "the reasonable worst-case (high emission rate) situation," but did not provide a methodology.

Currently in preview, click buy full version

Short-term Evaporative Loss Estimation from Atmospheric Storage Tanks

1 Scope

This Technical Report provides methodology on how to estimate short-term individual tank and facility-wide emissions. The methodology is intended to generate reasonable worst-case short-term emission estimates, and not necessarily an estimate of actual short-term emissions (see Annex A for limitations on applying this methodology to actual scenarios). The methodology is applicable to routine tank operations and not applicable to emissions associated with maintenance activities or tank roof landings. The methodology is applicable for estimating short-term emissions from tanks with fittings and seals in good condition and not applicable for tanks with damaged seals or roof fittings. Also, this methodology is not intended for situations where a tank has a malfunction, the emission controls are not working as intended, or there is other structural damage.

The calculated mass emissions using this methodology can be used as input for short-term air dispersion modeling. The Technical Report does not provide guidance on applicability of any particular air dispersion models or modeling protocol.

2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API *Manual of Petroleum Measurement Standards (MPMS) Chapter 19.1, Evaporative Loss from Fixed-Roof Tanks*, 4th Edition, 2012.

API *MPMS Chapter 19.2, Evaporative Loss from Floating-Roof Tanks*, 3rd Edition, 2012.

API *MPMS Chapter 19.4, Evaporative Loss Reference Information and Speciation Methodology*, 3rd Edition, 2012.

3 Estimating Reasonable Worst-Case Short-term Emissions from an Individual Storage Tank

NOTE While units from these calculations are typically in pounds/year from the referenced API *MPMS* Ch. 19.1 and 19.2 standards, the short-term emissions durations are usually calculated on the order of hours to days. See Annex A for a more complete explanation of limitations.

3.1 Liquid Storage Temperature

Liquid surface temperature is correlated to tank short-term emissions. If the tank is not fully insulated, then the average daily liquid surface temperature for a given time period is determined as a weighted average of the ambient and liquid bulk temperatures.

$$T_{TLA} = 0.4T_{AA} + 0.6T_B + 0.005\alpha I^1$$

This expression for average daily liquid surface temperature may be converted to a reasonable worst-case maximum liquid surface temperature by using the average daily maximum ambient temperature, T_{MAX} , for the month in

¹ API *MPMS* Ch. 19.1, 4th Edition, 2012, Equation 8, and API *MPMS* Ch. 19.2, 3rd Edition, 2012, Equation 14; average daily liquid surface temperature (TLA).