

Liquid Hydrocarbon Measurement Uncertainty Calculations

API TECHNICAL REPORT 2579
FIRST EDITION, SEPTEMBER 2020



Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

Users of this technical report should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proper, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Copyright © 2020 American Petroleum Institute. All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue NW, Suite 1100, Washington, DC 20001.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue NW, Suite 1100, Washington, DC 20001, standards@api.org.

Currently in preview, click buy full version

Contents

	Page
1 Scope	1
2 Terms and Definitions	1
3 Performance Characteristics and Measurement by Meter Type	1
3.1 General	1
3.2 Uncertainty Requirements	2
4 Uncertainty Development	2
4.1 General	2
4.2 Basic Equations	2
Annex A (informative) Uncertainty Examples	10
Bibliography	31
Figures	
A.1 LACT Measurement System with PD Meter and Bi-directional Prover	10
A.2 LACT Measurement System with Coriolis and Compact Prover	20

Introduction

This document provides a methodology for calculating the uncertainty in the measurement of liquid hydrocarbons by flow measurement systems. Specifically, uncertainty performance expressions are developed for positive displacement and Coriolis meter types under API *Manual of Petroleum Measurement Standards (MPMS)* Chapter 5 for measuring hydrocarbons by volume. This includes ancillary devices, processes, and measurements used to calculate a net standard volume (NSV) such as pressure, temperature, density, and sediment and water (S&W). This document was written to determine if the performance of a given measurement device is in compliance with an acceptable level of uncertainty, either pre-installation or after the installation is in service. If this is not the case, the measurement device, its installation, or maintenance practices, etc. can be upgraded to meet the desired uncertainty performance criterion. Techniques are described to assess the uncertainty contribution of individual components of measurement systems and the overall measurement facility's measurement uncertainty. By following the guidance and calculation procedures of this document, cost-effective measurements of appropriate quality can be achieved. In most cases, the rigorous requirements of industry standards intended for allocation and custody transfer quality measurements can be reduced and still achieve the desired measurement uncertainty required. For this document, a measurement system is comprised of meters, provers, and the associated devices to calculate NSV.

This document addresses the most common liquid measurement devices in use at the time of its development and allows for updating for new devices in the future. This does not advocate the use of these devices or preclude the utilization of other types of devices, provided the targeted performance is achieved.

Liquid Hydrocarbon Measurement Uncertainty Calculations

1 Scope

This document provides guidelines for the calculation of uncertainty for field stored and transported hydrocarbon liquids. Special emphasis is placed on the measurement uncertainty of crude oils measured at tanks, by lease automatic custody transfer (LACT), and alternative measurement systems.

2 Terms and Definitions

For the purposes of this document, the following definitions apply.

2.1

accuracy

The closeness of agreement between a measured quantity value and a true quantity value of a measurand.

2.3

calibration

A set of operations that establish, under specified conditions, the relationship between the values indicated by a measuring device and the corresponding known values indicated when using a suitable measuring standard.

2.12

metering or measurement system

A combination of primary, secondary, and/or tertiary measurement components necessary to determine the flow rate.

2.14

performance

The response of a measurement device to influence parameters such as operating conditions, installation effects, and fluid properties.

2.16

uncertainty

The range or interval within which the true value is expected to lie with a stated degree of confidence. Describes the range of deviation between a measured value and the true value, expressed as a percentage. For example, a device with an accuracy of 2 % would have an uncertainty of ± 2 %.

3 Performance Characteristics and Measurement by Meter Type

3.1 General

The primary purpose of a liquid hydrocarbon meter for any application is to measure the flow. The uncertainty of measurement depends on the measurement equipment selected for the application, proper installation of the equipment, the ability to inspect, verify, or calibrate the various measurement system components, and the frequency of those maintenance activities. The performance of the meter may also depend on the piping configuration and compensation for variability of operating pressure, temperature, and fluid composition. It is important to recognize individual influence parameters and their effect on the measurement. Since the principle of operation and differing influence parameters have varying degrees of influence by meter type, it is important to identify and define the significant influence factors for the meter to determine the total or combined measurement uncertainty.