

# Defining Hydrogen-induced Cracking Test Criteria for Commodity-grade Line Pipe in Less Severe Sour Conditions

API TECHNICAL REPORT 5HIC  
FIRST EDITION, AUGUST 2024



American  
Petroleum  
Institute

## Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be used. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

## Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue NW, Suite 1100, Washington, DC 20001, [standards@api.org](mailto:standards@api.org).

Currently in preview, click buy full version

Currently in preview, click buy full version

## Contents

	Page
1	Scope..... 1
2	Normative References ..... 1
3	Terms, Definitions, Abbreviations, and Symbols..... 1
3.1	Terms and Definitions ..... 1
3.2	Abbreviations ..... 1
3.3	Symbols ..... 1
4	Background..... 2
5	Test Conditions ..... 2
6	Material ..... 4
7	Experimental..... 4
7.1	General ..... 4
7.2	Test Plan ..... 4
8	Test Sequence and Evaluation ..... 6
9	Results ..... 7
10	Commentary ..... 16
11	Conclusions ..... 17
	Annex A (informative) Individual Specimen Test Results for Pipe A and B..... 18
	Annex B (informative) Chemistry and Typical Microstructure for Pipe A and B ..... 26
	Bibliography..... 29

## Figures

1	Proposed HIC Severity Regions Suggested by EPRG ..... 3
2	Less Severe Sour Test Conditions to Define Test Criteria for Commodity-grade Line Pipe ..... 3
3	Oxygen Concentration Range during HIC Test Preparation in 30 L Test Vessel ..... 6
4	Hydrogen-induced Cracks, Unetched (Top) and Etched (Bottom), Specimens: A6-1 Section A (Left) and A6-2 Section B (Right) ..... 9
5	Hydrogen-induced Cracks, Unetched (Top) and Etched (Bottom), Specimens: B6-1 Section B (Left) and B6-1 Section C (Right)..... 10
6	Base Material Blistering, Unetched (Left) and Etched (Right), Specimen: B12-2 Section C ..... 10
7	UT Plot Indications of Hydrogen-induced Cracking, Specimens: A6-6 (Left) and A6-18 (Right) ..... 11
8	UT Plot Indications of Hydrogen-induced Cracking, Specimens: B3-9 (Left) and B6-25 (Right)..... 12
9	X65 Pipe A: Base Material Average CAR Dependent on Exposure Duration ..... 13
10	X65 Pipe A: Base Material Average CLR Dependent on Exposure Duration ..... 13
11	X70 Pipe B: Base Material Average CAR Dependent on Exposure Duration..... 14

## Contents

	Page
<b>12</b> X70 Pipe B: Base Material Average CLR Dependent on Exposure Duration .....	14
<b>13</b> X65 Pipe A: Overall Average CAR Dependent on Exposure Duration.....	15
<b>14</b> X65 Pipe A: Overall Average CLR Dependent on Exposure Duration .....	15
<b>15</b> X70 Pipe B: Overall Average CAR Dependent on Exposure Duration .....	16
<b>16</b> X70 Pipe B: Overall Average CLR Dependent on Exposure Duration.....	16
<b>B.1</b> Microstructure of Pipe Material A; 3 o'clock Position (Left) and 6 o'clock Position (Right) near Pipe Inside .....	27
<b>B.2</b> Microstructure of Pipe Material B; 3 o'clock Position (Left) and 6 o'clock Position (Right) near Pipe Inside .....	28

## Tables

<b>1</b> Pipe A+B: Overview of Individual HIC Test Batches and Exposure Conditions.....	6
<b>2</b> X65 Pipe A: Overview of Average HIC Test Results via CAR and CLR .....	7
<b>3</b> X70 Pipe B: Overview of Average HIC Test Results via CAR and CLR.....	8
<b>A.1</b> Individual Specimen Test Results for Pipe A and B .....	19
<b>B.1</b> Chemical Composition for Pipe Materials A and B .....	26

## Introduction

The API Subcommittee on Tubular Goods decided to have work performed to support the development of a moderate sour service commodity grade under API Specification 5L:2018 Annex H. The project aimed at defining HIC test conditions and exposure duration needed to assess the suitability of commodity-grade line pipe under less severe sour conditions compared with standard testing. The impact of varying test durations on the extent of hydrogen-induced cracking was assessed by using two sweet service submerged-arc longitudinally welded (SAWL) pipes of Grades X65 and X70 of different susceptibility to hydrogen-induced cracking. The test program consisted of 12 HIC test batches representing less severe sour test environments containing 1 %–10 % H<sub>2</sub>S with pH between 3.5–4.5. Specimen preparation, exposure, ultrasonic testing (UT) and metallographic evaluation was performed in accordance with NACE TM0284:2016.

For all sour test environments and exposure durations between 4–14 days, the X70 Pipe B showed significant hydrogen-induced cracking, whereas the X65 Pipe A gave less HIC indications in terms of crack area ratios (CAR) obtained by UT and crack length ratios (CLR) obtained by metallographic evaluation.

With the clear benefit of shorter test duration in mind, the project focused on the question of whether hydrogen-induced cracking can stabilize earlier in HIC tests shorter than the 14 days specified in NACE TM0284:2016 and to what extent choice of solution pH and H<sub>2</sub>S content could contribute to achieve this objective. Within the observed scatter, HIC tests conducted in solutions of higher acidity gave a tendency of higher levels of hydrogen-induced cracking at shorter exposure times than observed for exposure under lower acidity (higher pH) test conditions. Hydrogen-induced cracking did not, however, stabilize during exposure durations shorter than 14 days in those less severe sour test environments.

API Specification 5CT:2023 (NACE TM0177 Solution D) gave unexpectedly high cracking after four days exposure. Experience with this solution in HIC testing is limited. More work is needed before considering this solution, developed for SSC-DCB testing, as a standardized HIC test environment.

Considering the increase in hydrogen-induced cracking with longer test duration as an important result of this project, HIC test durations shorter than 14 days in the considered range of less severe sour test environments are not recommended.

Currently in preview, click buy full version

# Defining Hydrogen-induced Cracking Test Criteria for Commodity-grade Line Pipe in Less Severe Sour Conditions

## 1 Scope

The work described herein is to support the development of a moderate sour service commodity grade under API Specification 5L:2018 Annex H, while maintaining harmonization with ISO 15156-1 and NACE TM0284:2016 as regards resistance testing to hydrogen-induced cracking (HIC).

To define the HIC test conditions and exposure duration needed for that purpose, the impact of varying test durations on the extent of cracking in less severe sour test environments was specifically assessed in solutions containing 1 %–10 % H<sub>2</sub>S within pH values 3.5–4.5.

For the series of HIC tests conducted, sweet service test material from two different pipes was used, which showed different susceptibility to cracking in moderate sour conditions.

## 2 Normative References

There are no normative references in this document.

## 3 Terms, Definitions, Abbreviations, and Symbols

### 3.1 Terms and Definitions

There are no defined terms in this document.

### 3.2 Abbreviations

CAR	crack area ratio
CLR	crack length ratio
CSR	crack sensitivity ratio
CTR	crack thickness ratio
DCB	double cantilever beam
EPRG	European Pipeline Research Group
FSH	full screen height
HIC	hydrogen-induced cracking
OCTG	oil country tubular goods
SAWL	submerged-arc longitudinally welded
SOHIC	stress-oriented hydrogen-induced cracking
SSC	sulfide stress cracking
UT	ultrasonic testing

### 3.3 Symbols

Al <sub>2</sub> O <sub>3</sub>	alumina
CO <sub>2</sub>	carbon dioxide gas
H <sub>2</sub> S	hydrogen sulfide gas