

ASTM C704 Test Variability Reduced to Allow Further Optimization of Erosion-resistant Refractories for Critical Oil Refining Applications

API TECHNICAL REPORT 977
FIRST EDITION, FEBRUARY 2018



AMERICAN PETROLEUM INSTITUTE

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Classified areas may vary depending on the location, conditions, equipment, and substances involved in any given situation. Users of this Technical Report should consult with the appropriate authorities having jurisdiction.

Users of this Technical Report should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations to comply with authorities having jurisdiction.

Where applicable, authorities having jurisdiction should be consulted.

Work sites and equipment operations may differ. Users are solely responsible for assessing their specific equipment and premises in determining the appropriateness of applying the Technical Report. At all times users should employ sound business, scientific, engineering, and judgment safety when using this Technical Report.

Copyright reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patents.

Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, D.C. 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually and updated quarterly by API, 1220 L Street, NW, Washington, D.C. 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, D.C. 20005, standards@api.org.

Currently in preview, click buy full version

Contents

	Page
1 Scope	1
2 Referenced Documents	1
3 Terms and Definitions	1
4 Continuing Drive for More Erosion-resistant Cyclone Linings.....	7
5 Abrasion Testing-History	9
5.1 The Standard ASTM Test, ASTM C704	9
5.2 Consensus of Strengths and Weaknesses of the Test Procedure.....	10
5.3 Strengths and Weaknesses of the ASTM C704 Test Method	11
6 Evaluation of Potential Variables	12
7 Changes to Procedure Defined	12
8 Round Robin Design.....	13
8.1 Materials.....	13
8.2 Laboratories	14
8.3 Protocol for Testing	14
9 Results Compared Between the 2015 Round Robin and 1999 Round Robin	15
9.1 1999 Ruggedness Testing	15
9.2 2015 Ruggedness Testing	16
10 Conclusions.....	18
11 What is Next?	18
Bibliography.....	19
Figures	
1 ASTM C704 Testing Machine	2
2 Example of FCCU Cyclone Pair Showing Key Components	3
3 FCC Unit Showing Key Components	5
4 New Machined Stainless Steel Nozzle	6
5 Survey Events Determining FCCU Turnaround Timing Outside of Planned Maintenance.....	8
6 Samples of FCCU Cyclone Lining Failures	9
Tables	
1 Development Leading to the Introduction of ASTM C704	10
2 ASTM C704 Standard Actions and Modifications Since 1972	11
3 Precision Statistics for Abrasion Resistance: Research Report RR:C08-1019	16
4 Castable Abrasion Loss, cm ³	17
5 Gussite Abrasion Loss, cm ³	17

Currently in preview, click buy full version

ASTM C704 Test Variability Reduced to Allow Further Optimization of Erosion-resistant Refractories for Critical Oil Refining Applications

1 Scope

1.1 This technical report documents the results of a joint project conducted by the API CRE Subcommittee on Refractory Materials (SCRM) and the ASTM C08 Committee to improve the reproducibility of the ASTM C704/C704M, 2015 Edition, *Standard Test Method for Abrasion Resistance of Refractory Materials at Room Temperature*. Erosion-resistant refractories are used in many oil refining applications, such as fluid catalytic cracking units (FCCUs), to resist the wearing effects of solids particles (5 μm to 100 μm is typical) circulating at elevated velocities [30 ft/s to 200 ft/s (9 m/s to 61 m/s)] in a high-temperature process environment [900 °F to 1400 °F (482 °C to 760 °C)].

1.2 This technical report also reviews the drivers for continuing improvement in erosion-resistant refractories and the role of ASTM C704/C704M for the selection and installation quality control of refractories used in these installations. This report documents changes made to the setup and procedures to improve the reproducibility of the test. These changes are designed to achieve this end, while providing a rough equivalency consistent with historical data before the changes were made. These results are validated by extensive international round robin and ruggedness testing and are reported herein.

2 Referenced Documents

API 936, *Refractory Installation Quality Control—Inspection and Testing, Monolithic Refractory Linings and Materials* (2014)

API TR 978, *Monolithic Refractories: Manufacture, Properties, and Selection*

API TR 979, *Applications of Refractory Lining Materials*

API TR 980, *Monolithic Refractories: Installation and Dryout*

ASTM C704/C704M¹, *Standard Test Method for Abrasion Resistance of Refractory Materials at Room Temperature* (2015).

ASTM C1036, *Standard Specification for Flat Glass*

ASTM E691-09, *Standard Practice for Conducting an Interlaboratory Study to Determine the Precision of a Test Method*

3 Terms and Definitions

3.1

abrasion resistance

The ability to withstand the effects of eroding particles for an extended period without the significant loss of material or other damage. Often referred to as “erosion resistance” in fluid solids units, such as FCC units, which is technically incorrect, but commonly understood in refining jargon.

EXAMPLE Ability of a refractory lining in an FCCU transfer line to retain thickness when exposed to circulating catalyst in the process stream.

NOTE For refractory materials, abrasion resistance is measured in the form of eroded volume loss in accordance with ASTM C704/C704M.

¹ ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, Pennsylvania, 19428-2959.