

# Monolithic Refractories: Manufacture, Properties, and Selection

API TECHNICAL REPORT 978  
FIRST EDITION, MARCH 2019



AMERICAN PETROLEUM INSTITUTE

## Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

Classified areas may vary depending on location, conditions, equipment, and substances involved in any given situation. Users of this technical report should consult with the appropriate authorities having jurisdiction.

Users of this technical report should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

Where applicable, authorities having jurisdiction should be consulted.

Work sites and equipment operations may differ. Users are solely responsible for assessing their specific equipment and premises in determining the appropriateness of applying the technical report. At all times users should employ sound business, scientific, engineering, and judgment safety when using this technical report.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations to comply with authorities having jurisdiction.

Copyright reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

## Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this specification are as follows:

- the term “shall” denotes a minimum requirement in order to conform to the standard;
- the term “should” denotes a recommendation or that which is advised but not required in order to conform to the standard;
- the term “may” is used to express permission or a provision that is optional;
- the term “can” is used to express possibility or capability.

**Informative elements**—As used in a standard, “informative” denotes elements that identify the document, introduce its content, and explain its background, development, and its relationship with other documents or provide additional information intended to assist the understanding or use of the document.

**Normative elements**—As used in a standard, “normative” denotes elements that describe the scope of the document and that set out provisions that are required to implement the standard.

Questions concerning the interpretation of the content of this publication, or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, [standards@api.org](mailto:standards@api.org).

## Contents

	Page
1	Scope . . . . . 1
2	Referenced Documents . . . . . 1
3	Terms and Definitions. . . . . 2
4	Background . . . . . 9
4.1	Early Beginnings. . . . . 9
4.2	Formulation Differences. . . . . 9
4.3	Cement Bonded Refractories . . . . . 10
4.4	Comparison with Other Refractories . . . . . 11
4.5	Other Types of Refractories. . . . . 12
4.6	Non-refractory Applications of Calcium Aluminate Cement [1, 7, 8, 9, 10] . . . . . 13
5	Constituent Ingredients of Refractory Concretes . . . . . 14
5.1	Introduction . . . . . 14
5.2	Binders . . . . . 14
5.3	Aggregates. . . . . 15
5.4	Water. . . . . 19
6	Constituent Ingredients of Plastics . . . . . 21
6.1	Introduction . . . . . 21
6.2	Particle Size/Moisture Level. . . . . 21
6.3	Aggregates. . . . . 22
6.4	Fine Grained Additives . . . . . 23
6.5	Binder Ingredients . . . . . 23
6.6	Manufacturing Methods . . . . . 25
7	Selection Criteria for Refractory Concretes . . . . . 26
7.1	Introduction . . . . . 26
7.2	Castables and Field Mixes . . . . . 26
7.3	Service Temperature Range. . . . . 34
7.4	Thermal Cycling . . . . . 34
7.5	Load Bearing Considerations . . . . . 35
7.6	Manufacturing Methods . . . . . 35
7.7	Corrosion Influences . . . . . 35
7.8	Binder Types . . . . . 36
7.9	Aggregate Types . . . . . 37
7.10	Abrasion and Erosion Resistance . . . . . 37
7.11	Methods of Installation. . . . . 37
7.12	Application and Use . . . . . 38
7.13	Factor Dryout. . . . . 38
8	Selection Criteria for Plastic Refractories . . . . . 39
8.1	Introduction . . . . . 39
8.2	Defining the Service Requirements . . . . . 41
8.3	Choice Between Pre-fired Brick and Monolithic Refractories . . . . . 42
8.4	Choice Between Plastics and Refractory Concretes . . . . . 42
8.5	Performance and End-use Requirements . . . . . 46
8.6	Recommended Selection Procedure . . . . . 51
9	Composition and Proportioning . . . . . 52
9.1	Introduction . . . . . 52

## Contents

	Page
9.2	Basis for Proportioning . . . . . 52
9.3	Field Mixes . . . . . 52
9.4	Water Content . . . . . 57
10	Plastics Characteristics . . . . . 54
10.1	Introduction . . . . . 54
10.2	Selection of a Plastic Refractory . . . . . 55
10.3	Classification . . . . . 56
10.4	Chemical Analysis . . . . . 56
10.5	Sampling . . . . . 57
10.6	Product Characteristics . . . . . 57
11	Engineering Properties and Testing . . . . . 61
11.1	Permanent Linear Change (ASTM C179) . . . . . 62
11.2	Thermal Expansion . . . . . 62
11.3	Mechanical Strength and Structural Stability . . . . . 63
11.4	Cold Compressive Strength (Crushing) . . . . . 64
11.5	Cold Modulus of Rupture . . . . . 64
11.6	Hot Strength (ASTM C583) . . . . . 65
11.7	Hot Modulus of Rupture . . . . . 65
11.8	Thermal Structural Stability (ASTM C832 and ASTM C1419) . . . . . 65
11.9	Modulus of Elasticity and Stress-strain Properties (ASTM C885 and ASTM C1419) . . . . . 65
11.10	Permeability (ASTM C577) . . . . . 66
11.11	Thermal Properties . . . . . 66
11.12	Thermal Shock and Spall Resistance . . . . . 68
11.13	Electrical Resistivity . . . . . 68
11.14	Abrasion/Erosion Resistance (ASTM C704) . . . . . 68
11.15	Resistance to Carbon Monoxide (ASTM C288) . . . . . 69
11.16	Resistance to Slag Attack . . . . . 69
11.17	Status of Testing Procedures . . . . . 70
	Bibliography . . . . . 71
<b>Figures</b>	
1	Typical Taylor Screen Analysis of Plastics and Ramming Mixes . . . . . 21
2	Typical Production Flow Sheet for the Manufacturer of Plastic Refractories . . . . . 26
3	Temperature Drop Versus Thickness for Different Refractory Castables [Hot-face Temperature Contact at 2000 °F (1090 °C)] . . . . . 36
4	Refractories in a Petroleum Coke Calciner Showing the Use of Plastics, Castables and Ramming Mixes . . . . . 40
5	Determining the Consistency of Freshly Mixed Refractory Castable Using the ASTM C860 Ramming Hand Test . . . . . 54
6	Net Thermal Expansion of a Typical Super-duty Plastic Recovery . . . . . 63
7	Effect of Temperature on the Modulus of Rupture and Cold Crushing Strength of an 85 % Alumina Phos-bonded Plastic Refractory . . . . . 64
	Thermal Conductivity of Various Plastic Refractories . . . . . 67

## Contents

Page

### Tables

1	Characteristics of Calcium Aluminate Cement Binders	15
2	Maximum Service Temperatures of Selected Aggregates Mixed With Calcium Aluminate Cements under Optimum Conditions	15
3	Aggregate Grading	17
4	Types of Lightweight Aggregates Used in Refractory Insulating Concretes	18
5	Effect on Calcium Aluminate Cement of Various Additives and Admixtures	20
6	Acid-neutral Aggregates	22
7	Liquid Binder Ingredients for Plastics	24
8	Dry Binder Ingredients for Plastics	25
9	Characteristics of Normal Weight Refractory Concretes	28
10	Characteristics of Lightweight Refractory Concretes	33
11	Methods of Installing Monolithic Refractories	43
12	Properties of Chemically Similar Monolithic Refractories (All Based on Cellular Alumina Aggregates)	44
13	Product and Performance Factors Considered in the Selection of Calcined Clay-based Plastics for Refractory Applications	47
14	Strength, Volume, Stability, and Installed Density of Phosphate-bonded and Conventional High-alumina (50 % to 90 % Al <sub>2</sub> O <sub>3</sub> ) Plastics and Conventional Calcined Clay-based Plastics (40 % to 47 % Al <sub>2</sub> O <sub>3</sub> )	48
15	Product and Performance Factors Considered in the Selection of High-alumina Plastics and Ramming Mixes for Refractory Applications	48
16	Product and Performance Factors Considered in the Selection of Graphitic/Carbonaceous Plastics and Ramming Mixes	49
17	Product and Performance Factors Considered in the Selection of Magnesia-based Ramming Mixes and Refractory Applications	50
18	Product and Performance Factors Considered in the Selection of Zircon-Based Ramming Mixes for Refractory Applications	50
19	Product and Performance Factors Considered in the Selection of Chrome Ore-Based Plastics/ Ramming Mixes for Refractory Applications	51
20	Classification of Fireclay and High-alumina Plastic Refractories and Ramming Mixes (ASTM C673)	57
21	Properties of Plastics and Ramming Mixes	58

## Introduction

API TR 978 is the first in a series of three API technical reports updating the state-of-the-art use of refractory concrete (castables), plastics, and ramming mixes in applications for the Hydrocarbon Processing Industry (HPI). This technical report is complemented by two additional reports in this series:

- API TR 979, *Applications of Refractory Lining Materials*
- API TR 980, *Monolithic Refractories: Installation and Dryout*

These three API technical reports are based on two original reports written by the American Concrete Institute (ACI) Committee 547 and published by ACI in 1979 and 1989. The original ACI reports are ACI 547.R-79, State-of-the Art Report: *Refractory Concrete* and ACI 547.1R-89, State-of-the Art Report: *Refractory Plastics and Ramming Mixes*. ACI granted API a license to use all material from the two original ACI reports, in need of revision at the time, for the betterment of the oil and gas industry.

ACI Committee 547 was organized in 1969 to provide a reliable and comprehensive source of information on monolithic refractories technology. In subsequent years, ACI support from the refractory technical community waned and shifted in favor API. API has an Individual Certification Program (ICP) for refractory practitioners based on the API Standard 936, *Refractory Installation Quality Control-Inspection and Testing Monolithic Refractory Linings and Materials*. To facilitate development of updated content in API's certification program, ACI has allowed API to use the material from the two ACI reports, mentioned above, as the starting point for three new API technical reports, which add to and revise the content of the two ACI reports.

The American Petroleum Institute formed the Vessel Refractory Task Group in the late 1980s with the objective of providing a standard for inspection and application quality control of monolithic refractories used in refining applications. In response to demands for greater reliability and cycle life objectives, refiners had already developed their own company specifications for refractory installations for the most important applications where unit availability is critical. A cottage industry of supporting quality control experts and inspectors evolved to help owner-operators reduce the gap between ideal and actual cycle life. Prior to the Vessel Refractory Task Group (the predecessor of the SCRMI), manufacturers and installers largely had little say in these efforts and uniform industry standards were never developed or adopted.

To address this issue, the Vessel Refractory Task Group allowed for a broad representation of all the stake holders as part of the API's spring and fall Refining Equipment Standards Meetings. Addressing the standards gap and noting the many similarities in owner-operator and OEM developed specifications, the API Task Force undertook the task of identifying useful industry practices and/or negotiating to agreement best fits for standards applications. API's *Refractory Installation Quality Control Guidelines—Inspection and Testing Monolithic Linings and Material* was first issued in 1996 as a recommended practice. After a number of subsequent revisions, it was published as API Standard 936 in 2006, with a certification program beginning in 2004.

In addition to maintaining API Standard 936 and overseeing the certification program, in 2014 the Task Force reorganized under the Committee on Refinery Equipment (CRE) as the Refractory Project Group (RPG). As a project group, work extended to ceramic fiber and brick quality control standards; unit specific applications, such as SRU and hydrogen furnaces; and technical reports, including this report. In response to this broadening recognition of the need to advance this technology for HPI applications, the CRE reclassified the group as a full subcommittee in 2016 and now works under the title of the Subcommittee on Refractory Materials.

# Monolithic Refractories: Manufacture, Properties, and Selection

## 1 Scope

This technical report covers the installation and dryout of monolithic refractory lining materials for Hydrocarbon Processing Industry (HPI) applications. It discusses the best practice procedures and techniques used in the installation of refractory concrete, as well as those for air and heat setting plastics and ramming mixes. In addition, it addresses the need for curing and dryout procedures to achieve successful results. This instruction is consistent with API Standard 936, which is the HPI industry standard for the installation quality control of monolithic refractories. API 936 also serves as a body of knowledge document for the API certification program for refractory practitioners.

NOTE API TR 979 and API TR 980 are additional reports listed in Section 2, designed to provide a complete discussion of the monolithic refractory subject.

## 2 Referenced Documents

API 936, *Refractory Installation Quality Control—Inspection and Testing Monolithic Refractory Linings and Materials*

API TR 977, *ASTM C704 Test Variability Reduced to Allow Further Optimization of Erosion Resistant Refractories for Critical Oil Refining Applications*<sup>1</sup>

API TR 979, *Applications of Refractory Lining Materials*<sup>1</sup>

ASTM C16, *Standard Test Method for Load Testing Refractory Shapes at High Temperatures*

ASTM C20, *Standard Test Methods for Apparent Porosity, Water Absorption, Apparent Specific Gravity, and Bulk Density of Burned Refractory Brick and Shapes by Boiling Water*

ASTM C24, *Standard Test Method for Pyrometric Cone Equivalent (PCE) of Fireclay and High-Alumina Refractory Materials*

ASTM C92, *Standard Test Methods for Sieve Analysis and Water Content of Refractory Materials*

ASTM C115, *Standard Test Method for Fineness of Portland Cement by the Turbidimeter*

ASTM C129, *Standard Specification for Nonloadbearing Concrete Masonry Units*

ASTM C133, *Standard Test Methods for Cold Crushing Strength and Modulus of Rupture of Refractories*

ASTM C134, *Standard Test Methods for Size, Dimensional Measurements, and Bulk Density of Refractory Brick and Insulating Firebrick*

ASTM C150, *Standard Specification for Portland Cement*

ASTM C179, *Standard Test Method for Drying and Firing Linear Change of Refractory Plastic and Ramming Mix Specimens*

ASTM C181, *Standard Test Method for Workability Index of Fireclay and High-Alumina Refractory Plastics*

ASTM C191, *Standard Test Methods for Time of Setting of Hydraulic Cement by Vicat Needle*

ASTM C201, *Standard Test Method for Thermal Conductivity of Refractories*