

Australian Standard[®]

Partial discharge measurements

This Australian standard was prepared by Committee EL/7, Power Switchgear. It was approved on behalf of the Council of the Standards Association of Australia on 20 November 1984 and published on 4 April 1985.

The following interests are represented on Committee EL/7

Australian British Chamber of Commerce
Australian Electrical and Electronic Manufacturers Association
Confederation of Australian Industry
Electricity Supply Association of Australia
Institution of Engineers, Australia
Railways of Australian Committee
Testing Authority

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standard users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay so that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 83217.

Australian Standard[®]

Partial discharge measurements

First published	1970
Second edition	1985

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 3651 9

PREFACE

This edition of this standard was prepared by the Association's Committee on Power Switchgear to supersede AS 1018—1970, Recommendations for Partial Discharge Measurements.

This standard is identical with and has been reproduced from IEC 270(1981), Partial Discharge Measurements. Thus it does not have the same format as AS 1018—1970.

This standard applies to the methods of measurement of partial discharges in the insulating media of electrical equipment during tests principally with alternating voltage, however, it also covers special requirements for partial discharge test measurements during tests with direct voltage.

This standard is intended principally as a guide to the drafting of specifications for specific equipment.

For the purpose of this standard, the text of the IEC Publication should be modified as follows:

- (a) *Clauses 4.3.6 and 6.4.1.* Both Clauses 4.3.6 and 6.4.1 have been slightly amended and for the convenience of users the amendments have been inserted directly into the text of the standard and this is indicated by a rule in the margin.
- (b) *Technical Committee.* Where reference is made to 'the relevant Technical Committee' this should also be taken as a reference to the relevant equipment standard.
- (c) *Decimal comma.* The decimal point should replace the decimal comma wherever it appears.
- (d) *Cross-reference.* The reference to IEC Publication should be replaced by reference to Australian Standards, as follows:

<i>Reference to IEC Publication</i>	<i>Appropriate Australian Standard</i>
IEC 60: High voltage test techniques	AS 1952 High Voltage Testing Techniques
IRC 60-2, Part 2: Test Procedures	Part 1— General Definitions, Test procedures and Measuring Devices

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

	<i>Page</i>
1 SCOPE	5
2 OBJECT	6
3 DEFINITIONS	
3.1 Partial discharge	6
3.2 Quantities related to partial discharges	6
3.3 Specified partial discharge magnitude	7
3.4 Voltages related to partial discharges	7
4 TEST CIRCUITS AND MEASURING INSTRUMENTS	
4.1 General requirements	8
4.2 Test circuits	8
4.3 Measuring instruments	10
4.4 Non-electrical methods of detection	12
5 CALIBRATION	
5.1 General	12
5.2 Determination of instrument characteristics	13
5.3 Calibration of the instrument in the complete test arrangement	14
6 TESTS	
6.1 General requirements	15
6.2 Conditioning of the test object	15
6.3 Requirements for the test voltages	15
6.4 Choice of test procedure	15
6.5 Measurements on cables and on test objects with windings	16
7 MEASURING ACCURACY AND SENSITIVITY	16
8 DISTURBANCES	
8.1 Sources of disturbances	17
8.2 Detecting disturbances	17
8.3 Reduction of disturbances	18
8.4 Disturbance levels	19
9 SPECIAL REQUIREMENTS FOR PARTIAL DISCHARGE MEASUREMENTS DURING TESTS WITH DIRECT VOLTAGE	
9.1 General	19
9.2 Quantities related to partial discharges	20
9.3 Voltages related to partial discharges	20
9.4 Test circuits and measuring instruments	20
9.5 Tests	20
9.6 Disturbances	21
APPENDICES	
A Test circuits	22
B Integrated quantities	24
C Measurements on cables and on test objects with windings	25
D The use of radio interference metres for the measurement of partial discharges	26

PARTIAL DISCHARGE MEASUREMENTS

1. Scope

This standard applies to the measurement of partial discharges during tests with alternating voltage, but general terms, definitions and requirements are usually also applicable for measurement of partial discharges during tests with direct voltage. Some special characteristics of partial discharge measurements under direct voltage are given in a separate clause and necessary references are made throughout the text. This standard is intended principally as a general guide to the drafting of specifications for specific apparatus.

Measurements of partial discharges are made for the following main purposes:

- to verify that the test object does not exhibit partial discharges greater than a specified magnitude, at a specified voltage;
- to determine the voltage amplitude at which partial discharges of a specified low magnitude commence with increasing voltage and cease with decreasing voltage;
- to determine the magnitude of the specified discharge quantity at a specified voltage.

The partial discharges which are considered in this standard are localized electrical discharges in insulating media, restricted to only a part of the dielectric under test and only partially bridging the insulation between conductors. Discharges mostly occur in the form of individual pulses, which can be detected as electrical pulses in the external circuit connected to the test object. However, a more continuous form may also occur, the so-called pulseless discharge. This form will normally not be detected by the measurement methods described in this standard.

Partial discharges may occur in cavities in solid insulation, in gas bubbles in liquid insulation or between layers of insulation with different dielectric characteristics. They may also occur at sharp edges or points of metallic surfaces.

Even though they involve only small amounts of energy, partial discharges may lead to progressive deterioration of the dielectric properties of insulating materials; the definition and variation of such deterioration, however, is beyond the scope of this standard.

Partial discharge measurements on cables and on apparatus having windings, such as transformers, generators and motors, are complicated by attenuation, resonance and travelling wave phenomena. Special requirements for tests on these objects are only briefly dealt with.

This standard deals mainly with electrical measurements of partial discharges, but some reference is also made to non-electrical methods.