

AS 1081.1—1990

ISO 1680/1: 1986

Australian Standard[®]

**Acoustics—Measurement of
airborne noise emitted by rotating
electrical machinery**

**Part 1: Engineering method for
free field conditions over a
reflective plane**

This Australian Standard was prepared by Committee AV/6, Acoustics — Machinery Noise. It was approved on behalf of the Council of Standards Australia on 2 February 1990 and published on 7 May 1990.

The following interests are represented on Committee AV/6:

Australian Coal Association
Australian Compressed Air and Mining Equipment Institute
Australian Federation of Construction Contractors
Australian and New Zealand Environmental Council
Confederation of Australian Industry
Construction Equipment Importers and Manufacturers of Australia
Council of the City of Sydney
Department of Industrial Relations and Employment, N.S.W.
Department of Labour, S.A.
Master Builders Construction and Housing Association Australia
Metal Trades Industry Association of Australia
Monash University
National Association of Australian State Road Authorities
National Farmers Federation
Outdoor Power Equipment Association
Royal Institute of Naval Architects
Tractor and Machinery Association of Australia
University of Melbourne

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

Australian Standard[®]

**Acoustics—Measurement of
airborne noise emitted by rotating
electrical machinery**

**Part 1: Engineering method for
free-field conditions over a
reflective plane**

First published in part as AS 1081—1975.
Revised and redesignated AS 1081.1—1990.

PREFACE

This Standard was prepared by the Standards Australia Committee on Acoustics—Machinery Noise to supersede, in part, AS 1081—1975, *Measurement of airborne noise emitted by rotating electrical machinery*. It is identical with and has been reproduced from ISO 1680/1—1986, *Acoustics—Test code for the measurement of airborne noise emitted by rotating electrical machinery—Part 1: Engineering method for free-field conditions over a reflective plane*.

This Standard is one of the series which deals with rotating electrical machinery noise, the series being arranged as follows:

Part 1: Engineering method for free-field conditions over a reflective plane (this Standard).

Part 2: Survey method.

For the purpose of this Australian Standard, the ISO text should be modified as follows:

(a) *Clause 3*: The terms which have their equivalents in AS 1633, *Acoustics—Glossary of terms and related symbols* should follow the definitions of the Australian Standard. The terms which do not have equivalents in the AS 1633 should be as in this Standard.

(b) *References*: The reference to other publications should be modified as follows:

ISO		AS	
266	Acoustics—Preferred frequencies for measurements	2533	Acoustics—Preferred frequencies for measurements
354	Acoustics—Measurement of sound absorption in a reverberation room	1045	Acoustics—Measurement of sound absorption in a reverberation room
1680/2	Acoustics—Test code for the measurement of airborne noise emitted by rotating electrical machinery—Part 2: Survey method	1081.2	Acoustics—Measurement of airborne noise emitted by rotating electrical machinery Part 2: Survey method
3740	Acoustics—Determination of sound power levels of noise sources—Guidelines for the use of basic standards and for the preparation of noise test codes	127.1	Determination of sound power levels of noise sources, Part 1: Guidelines for the use of basic standards for the preparation of noise test codes
3741	Acoustics—Determination of sound power levels of noise sources—Precision methods for broad-band sources in reverberation rooms	1217.2	Acoustics—Determination of sound power levels of noise sources, Part 2: Precision methods for broad-band sources in reverberation rooms
3742	Acoustics—Determination of sound power levels of noise sources—Precision methods for discrete-frequency and narrow-band sources in reverberation room	1217.3	Acoustics—Determination of sound power levels of noise sources, Part 3: Precision methods for discrete-frequency and narrow-band sources in reverberation room
3744	Acoustics—Determination of sound power levels of noise sources—Engineering methods for free-field conditions over a reflecting plane	1217.5	Acoustics—Determination of sound power levels of noise sources, Part 5: Engineering methods for free-field conditions over a reflecting plane
3745	Acoustics—Determination of sound power levels of noise sources—Precision methods for anechoic and semi-anechoic rooms	1217.6	Acoustics—Determination of sound power levels of noise sources, Part 6: Precision methods for anechoic and semi-anechoic rooms
IEC			
34/1	Rotating electrical machines Part 1: Rating and performance	1359	Rotating electrical machines — General requirements
225	Octave, half-octave and third-octave band filters intended for the analysis of sounds and vibrations	Z41	Octave, half-octave and one-third octave band pass filters intended for analysis of sound and vibrations
651	Sound level meters	1259	Sound level meters

CONTENTS

	<i>Page</i>
0 INTRODUCTION	4
1 SCOPE	4
2 REFERENCES	4
3 DEFINITIONS	5
4 ACOUSTIC ENVIRONMENT	6
5 INSTRUMENTATION	6
6 INSTALLATION AND OPERATION OF THE MACHINE	7
7 SOUND PRESSURE LEVELS ON THE MEASUREMENT SURFACE	7
8 CALCULATION OF SURFACE SOUND PRESSURE LEVEL AND SOUND POWER LEVEL	11
9 INFORMATION TO BE RECORDED	11
10 INFORMATION TO BE REPORTED	12
ANNEXES	
A QUALIFICATION PROCEDURES FOR THE ACOUSTIC ENVIRONMENT	13
B COMPUTATIONAL PROCEDURES FOR CALCULATING A-WEIGHTED SOUND POWER LEVEL FROM ONE-THIRD OCTAVE BAND POWER LEVELS	16
C METHOD FOR ESTIMATING THE DIFFERENCE IN NOISE LEVEL BETWEEN NO-LOAD AND ON-LOAD OPERATIONS	17

© Copyright — STANDARDS AUSTRALIA

Purchasers of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

Acoustics—Measurement of airborne noise emitted by rotating electrical machinery— Part 1: Engineering method for free-field conditions over a reflecting plane

0 Introduction

This part of ISO 1680 is based on ISO 3744 and has been drafted in accordance with ISO 3740.

The main purpose of this part of ISO 1680 is to specify a clearly defined measurement method for rotating electrical machines operating under steady-state conditions, the results of which can be expressed in sound power levels so that all machines tested using this code can be directly compared. Other methods, such as the precision methods of ISO 3741, 3742 and 3745, may also be used for determining sound power levels if the installation and operating conditions of this part of ISO 1680 are used.

1 Scope and field of application

1.1 General

This part of ISO 1680 specifies, in accordance with ISO 2204, an engineering method (grade 2) for measuring the sound pressure levels on a rectangular parallelepiped surface enveloping the machine and for calculating the sound power level produced by the machine. It outlines the procedures which may be used to evaluate the test environment and specifies the characteristics of suitable measuring instruments. A method is given for determining the A-weighted sound power level and, if required, octave or one-third octave band sound power levels of the machine from the mean of the sound pressure level measured on the rectangular parallelepiped surface.

This part of ISO 1680 applies to the measurement of airborne noise from rotating electrical machines, such as motors and generators (d.c. and a.c. machines) without any limitation on the output or voltage, when fitted with their normal auxiliaries. It applies to rotating electrical machines with any linear dimension (length, width or height) not exceeding 15 m.

This part of ISO 1680 applies to measurements carried out in environmental conditions that meet the criteria given in clause 4 and annex A (environmental correction $K \leq 2$ dB, correction for background noise ≤ 1 dB). If these criteria are not met, standard deviations of the test results may be greater than those given in table 1, i.e. the engineering grade of accuracy may not be achieved. The method given in ISO 1680/2 shall then be used, which will result in A-weighted sound power levels of

lower accuracy. In this case, no reference shall be made to this part of ISO 1680.

1.2 Measurement uncertainty

Measurements carried out in conformity with this part of ISO 1680 usually result in standard deviations which are equal to or less than those given in table 1. The standard deviations given in table 1 reflect the cumulative effects of all causes of measurement uncertainty, excluding variations in the sound power level of the machine from test to test. For a machine which emits noise with a relatively "flat" spectrum in the 100 to 10 000 Hz frequency range, the A-weighted sound power level is determined with a standard deviation of approximately 2 dB. For outdoor measurements, the standard deviation in the octave band centred on 63 Hz will be approximately 5 dB.

NOTE—The standard deviations in table 1 include the effects of allowable variations in the positioning of the measurement positions and in the selection of the stipulated measurement surface.

Table 1—Uncertainty in determining sound power levels for engineering measurements indoors or outdoors

Octave band centre frequencies Hz	One-third octave band centre frequencies Hz	Standard deviation of mean value dB
125	100 to 160	3,0
250 to 500	200 to 630	2,0
1 000 to 4 000	800 to 5 000	1,5
8 000	6 300 to 10 000	2,5

2 References

ISO 266, *Acoustics — Preferred frequencies for measurements.*

ISO 354, *Acoustics — Measurement of sound absorption in a reverberation room.*

ISO 1680/2, *Acoustics— Test code for the measurement of airborne noise emitted by rotating electrical machinery— Part 2: Survey method.*