

Australian Standard™

Railway permanent way material

Part 17: Steel sleepers



Standards Australia

This Australian Standard was prepared by Committee CE/2, Railway Permanent Way Materials. It was approved on behalf of the Council of Standards Australia on 24 January 2000 and published on 7 March 2000.

The following interests are represented on Committee CE/2:

Australasian Railway Association
Australian Chamber of Commerce and Industry
Australian Industry Group
Bureau of Steel Manufacturers of Australia
Rail Track Association Australia

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Australia web site at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Australian Standard*, has a full listing of revisions and amendments published each month.

We also welcome suggestions for the improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.com.au, or write to the Chief Executive, Standards Australia International Ltd, PO Box 1055, Strathfield, NSW 2135.

Australian Standard™

Railway permanent way material

Part 17: Steel sleepers

First published as AS 1085.17—2000.

COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd
PO Box 1055, Strathfield, NSW 2135, Australia

ISBN 0 7337 3212 7

PREFACE

This Standard was prepared by the Standards Australia Committee CE/2, Railway Permanent Way Materials.

The objective of this Standard is to provide purchasers and suppliers including owners, operators, designers and manufacturers of railway sleepers with requirements for the specification, manufacture and testing of trough-shaped steel sleepers for use in railway track.

This Standard is intended for use by persons experienced in track design and performance and who have a good knowledge of the duty and environment of the track in which the sleepers are to be used (see also Foreword).

Loads and calculation methods given in this Standard are in permissible stress format and are not based on limit states principles.

Statements expressed in mandatory terms in notes to tables are deemed to be requirements of this Standard.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the appendix to which they apply. A 'normative' appendix is an integral part of a Standard, whereas an 'informative' appendix is only for information and guidance.

CONTENTS

	<i>Page</i>
FOREWORD	4
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE	5
1.2 PURPOSE AND CONTEXT OF USE	5
1.3 TESTING	5
1.4 REFERENCED DOCUMENTS	6
1.5 DEFINITIONS	6
1.6 NOTATION	6
SECTION 2 PERFORMANCE REQUIREMENTS	
2.1 TRACK SYSTEM COMPATIBILITY	11
2.2 SERVICE LIFE	11
2.3 RAIL RESTRAINT AND SUPPORT	12
2.4 INSTALLATION AND MAINTENANCE	13
2.5 MARKING	13
2.6 HANDLING	14
SECTION 3 RESILIENT RAIL FASTENING ASSEMBLIES	
3.1 TESTING	15
3.2 FASTENING PERFORMANCE	15
SECTION 4 LOADS FOR DESIGN AND TESTING	
4.1 GENERAL	16
4.2 TRACK CONDITIONS	16
4.3 QUASI-STATIC VERTICAL WHEEL LOAD	16
4.4 IMPACT FACTOR	16
4.5 QUASI-STATIC VERTICAL RAIL SEAT LOAD	17
4.6 QUASI-STATIC LATERAL WHEEL LOAD	18
4.7 QUASI-STATIC LATERAL RAIL SEAT LOAD	19
SECTION 5 STRUCTURAL ANALYSIS	
5.1 GENERAL	20
5.2 CORROSION AND WEAR	20
5.3 DESIGN BENDING STRESS	20
5.4 EMPIRICAL METHOD	20
5.5 BEAM ON ELASTIC FOUNDATION (BOEF) METHOD	23
APPENDICES	
A INFORMATION TO BE PROVIDED	26
B MEANS OF DEMONSTRATING COMPLIANCE WITH THIS STANDARD	30
C SPECIAL SLEEPERS AND FASTENINGS	32
D SLEEPER SHAPE	37
E TRACK PANEL ASSEMBLY TEST	40
F ELECTRICAL IMPEDANCE TEST	41
G RAIL SEAT ASSEMBLY REPEATED LOAD TEST	42
H LATERAL LOAD RESTRAINT TEST	45
I FASTENING LONGITUDINAL RESTRAINT TEST	47
J FASTENING UPLIFT TEST	49
K LATERAL STABILITY TEST	51
L SLEEPER SPACING	53

FOREWORD

The performance of steel sleepers in track depends on the condition of the rail, the condition and type of rail joints, the ballast support and the rail fastening system. Accordingly, when considering their performance, the sleeper and its fastening together with the rail must be regarded as interdependent components of a system.

The limits given in this Standard are based on the current state of knowledge of steel sleeper behaviour in service; however, service conditions are difficult to define and test criteria, which are seen as the most appropriate for the current state of knowledge, have been adopted.

A critical design aspect of steel sleepers is the interaction of the fastening and the portion of sleeper around the hole in which the fastening is secured. The rail seat assembly rejected load test can not be used to predict the expected in-track fatigue life. It does, however, provide a means of acceptance of a design by comparison with existing proven designs on the basis of experience.

The loads used in testing and design should reflect the use of the sleeper. For example, if sleepers are used in an interspersed pattern, a disproportionate amount of the load may be taken by a particular sleeper and early in-service failure may result.

This Standard does not cover sleepers for use in curves with radii less than 200 m.

Track constructed using sleepers and fastener components meeting the requirements of this Standard is expected to give satisfactory performance when properly installed and under an appropriate maintenance program.

STANDARDS AUSTRALIA

Australian Standard
Railway permanent way material

Part 17: Steel sleepers

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE

This Standard specifies the performance requirements and gives design and testing methods for trough-shaped steel sleepers and their associated components for use in railway track. It also sets out requirements for the performance of rail-insulating components.

NOTES:

- 1 Sleepers are generally designed to suit a specific rail profile and gauge with a given fastening.
- 2 Guidance to purchasers on information needing to be supplied at the time of calling for tenders or quotations and testing of new products is given in Appendix A.
- 3 Information on the means for determining compliance with this Standard is given in Appendix B.
- 4 Guidelines on the design and manufacture of special sleepers and fastenings are given in Appendix C.

1.2 PURPOSE AND CONTEXT OF USE

1.2.1 Function

Sleepers are support members that are part of the structure of railway permanent way. They are embedded into the ballast and support the rails above. They tie the rails together maintaining gauge and rail position and resisting lateral and longitudinal movement of the rail system. Fastenings, as part of the sleeper assembly, secure the rails to the sleeper.

1.2.2 Action

Sleepers are subjected to—

- (a) loads imposed by the passage of rolling stock on the rails and during maintenance;
- (b) loads generated by thermal effects on the rail and by ballast movement; and
- (c) fatigue, wear, damage and corrosion.

2 TESTING

Testing shall be conducted by a laboratory appropriately qualified to carry out the tests. Testing shall be carried out on sleeper assemblies or elements that have been produced using the processes and the plant, and with the materials that the manufacturer uses or intends to use in mass production. The tests given in this Standard are for the design and acceptance of steel sleepers.

Testing shall be carried out using the rail profile (or part of the rail profile, as appropriate) and the sleeper assembly, including rail fastening, that is intended to be used. This includes the use of spacers or other variation in configuration (e.g. multiple sets of holes).