

Under Revision see DR 94247

AS 1111—1980
UDC 621.882.211

Australian Standard 1111—1980

ISO METRIC HEXAGON COMMERCIAL BOLTS AND SCREWS

[Title Allocated by Department of Cataloguing Authority:

BOLT, MACHINE, SCREW, MACHINE (ISO Metric,	NSC 5306
Steel, Hexagon Head, Commercial Products)	NSC 5305]



STANDARDS ASSOCIATION OF AUSTRALIA

Incorporated by Royal Charter



THE FOLLOWING SCIENTIFIC, INDUSTRIAL AND GOVERNMENTAL ORGANIZATIONS and departments were officially represented on the committee entrusted with the preparation of this standard:

Australian Institute of Steel Construction Ltd
Bureau of Steel Manufacturers of Australia
Confederation of Australian Industry
Department of Defence
Electricity Supply Association of Australia
Fasteners Institute of Australia
Federal Chamber of Automotive Industries
Institution of Production Engineers
Metal Trades Industry Association of Australia
Petroleum Refinery Engineers Advisory Committee
Railways of Australia Committee
Telecom Australia
University of Sydney

This standard, prepared by Committee ME 79, Fasteners, was approved on behalf of the Council of the Standards Association of Australia, on 21 September 1980, and was published on 31 December 1980

To keep abreast of progress in industry, Australian standards are subject to continuous review and are kept up-to-date by the issue of amendments or new editions as necessary. It is important therefore that standard users ensure that their standards are up-to-date. Full details of all SAA publications can be found in the Annual List of Australian Standards; these details are supplemented by monthly listings in the SAA journal 'The Australian Standard'. Information on the Annual List and 'The Australian Standard' may be obtained from any sales office of the Association, where details are also available of the current status of individual standards. Suggestions for improvements to published standards, addressed to the head office of the Association, are welcomed.

This standard was issued in draft form for public review as DR 79190.

AUSTRALIAN STANDARD

**ISO METRIC HEXAGON
COMMERCIAL BOLTS AND SCREWS**

AS 1111-1980

First published	1972
Second edition	1980

**PUBLISHED BY THE STANDARDS ASSOCIATION OF AUSTRALIA
STANDARDS HOUSE, 80 ARTHUR ST, NORTH SYDNEY, N.S.W.**

ISBN 0 7262 2045 0



PREFACE

This standard was prepared by the Association's Committee on Fasteners to supersede the 1972 edition. The latter was intended to cover the anticipated needs of Australian industry under the metric system for metric hexagon bolts and screws. In the interests of international trade and international standardization, the standard at the time was fully aligned with the recommendations of the International Organization for Standardization (ISO), which had emanated from its technical committee TC2.

Since 1972 there have been several important changes introduced in the international standards, also the needs of Australian industry have become more crystallized, and hence a complete revision was necessary to take all factors into account. The changes in the ISO standards have been introduced after a great deal of technical study and research within ISO/TC 2, and were to a large degree initiated by the U.S.A. which, when the metric system was first seriously proposed for adoption in that country, developed a new metric fastener system (The Optimum Metric Fastener System). This system was forwarded to ISO as a U.S.A. proposal for a revision of the relevant standards. In the original submission, a very significant number of changes were proposed for both metric fasteners and metric screw threads. The ensuing discussion within ISO/TC 2 which took place over several years were aimed at reducing the technical changes to existing ISO standards to a minimum consistent with achieving improved performance without significantly increasing product costs.

The most significant changes in ISO standards and in this standard from the user's point of view are in the across-flat hexagon sizes, and attention is drawn to Appendix F where this is fully detailed.

This standard has been based on and in alignment with the following ISO standards, with the exception that the tolerance on overall length of js16 has been retained:

- ISO 272 Fasteners — Hexagon Products — Widths Across Flats
- ISO/R733 Hexagon Bolts and Nuts — Metric Series — Tolerances on Widths Across Flats, Widths Across Corners

- ISO 885 General Purpose Bolts and Screws — Metric Series — Radii Under the Head
- ISO 888 Bolts, Screws and Studs — Nominal Lengths and Thread Lengths for General Purpose Bolts
- ISO 898 Mechanical Properties of Fasteners
Part 1 — Bolts, Screws and Studs
Part 3 — Marking of Bolts, Screws, Studs and Nuts
- ISO 4016 Hexagon Head Bolts — Product Grade C
- ISO 4018 Hexagon Head Screws — Product Grade C
- ISO 4759 Tolerances for Fasteners
Part 1 — Bolts, Screws and Nuts with Thread Diameters between 1.6 (inclusive) and 150 mm (inclusive) and Product Grades B and C.

This standard may require reference to the following Australian standards:

- AS 1110 ISO Metric Hexagon Precision Bolts and Screws
- AS 1112 ISO Metric Hexagon Nuts including Thin Nuts, Slotted Nuts and Castle Nuts
- AS 1114 Hot-dip Galvanized Coatings on Threaded Fasteners (ISO Metric Coarse Thread Series)
- AS 1236 Split Cotter Pins (Metric Series)
- AS 1275 Metric Screw Threads for Fasteners
- AS 1391 Methods for Tensile Testing of Metals
- AS 1544 Methods for Impact Tests on Metals
Part 3 — Charpy U-notch and Keyhole Notch
- AS 1654 Limits and Fits for Engineering
- AS 1721 General Purpose Metric Screw Threads
- AS 1815 Method for Rockwell Hardness Test
- AS 1816 Method for Brinell Hardness Test
- AS 1817 Method for Vickers Hardness Test
- AS 1897 Electroplated Coatings on Threaded Components (Metric Coarse Series)

© Copyright — STANDARDS ASSOCIATION OF AUSTRALIA 1980

Users of standards are reminded that copyright subsists in all SAA publications. No part of this publication may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing of the Standards Association of Australia.

CONTENTS

	<i>Page</i>
SPECIFICATION	
1 Scope	4
2 Definitions	4
3 Method of Manufacture	4
4 Shape, Dimensions and Finish	4
5 Materials and Mechanical Properties	10
6 Testing of Mechanical Properties of Hexagon Steel Bolts and Screws	12
7 Marking	15
APPENDICES	
A Basis for Derivation of Tolerances	17
B Shank and Head Dimensions for Hexagon Bolts and Screws over M64	18
C Drilled Bolts and Screws for Split-pins	19
D Notes on Hexagon Sizes of Metric Bolts and Screws	20
E A Suggested Sampling Plan for Mechanical Properties	21
F Complete Designation for the Purpose of an Enquiry or Order	22
FIGURES	
1 Concentricity, Symmetry and Squareness of Hexagon Bolts and Screws	5
2 ISO Metric Hexagon Commercial Bolts and Screws	6
3 Proof Loading Test	13
4 Application of Proof Load	13
5 Wedge Loading Test	14
6 Wedge Loading of Full-size Bolt or Screw	14
7 Machined Test Piece	15
8 Location of a Standard 50 mm Gauge Length for Test Piece Turned from Large-size Bolt or Screw	15
9 Example of Marking of Machined Product	15
10 Example of Marking of Part Turned Product	15
TABLES	
1 Nominal Thread Lengths for Bolts	5
2 General Dimensions of ISO Metric Commercial Bolts and Screws	7
3 Lengths of Commercial Hexagon Bolts	8
4 Lengths of Commercial Hexagon Screws	9
5 Mechanical Properties of Steel Bolts and Screws	11
6 Chemical Composition of Steel Bolts and Screws	11
7 Acceptance Tests for Full-size Bolts and Screws	12
8 Acceptance Tests for Machined Proportional Test Pieces	12
9 Tensile and Proof Loads for Steel Bolts and Screws	12
10 Dimensions for Wedge Loading Test	14

STANDARDS ASSOCIATION OF AUSTRALIA

Australian Standard
for
ISO METRIC HEXAGON COMMERCIAL BOLTS AND SCREWS

1 SCOPE. This standard specifies requirements for commercial hexagon bolts and commercial hexagon screws, with ISO metric coarse pitch series threads in diameters from 5 mm to 64 mm inclusive.

Bolts up to 200 mm length are specified with shanks of approximately the nominal diameter (full size shanks). Over 200 mm length, bolts may be supplied with a reduced shank (scant shank bolt) of diameter approximately equal to the thread pitch diameter unless otherwise specified by the purchaser.

This standard is intended primarily to apply to steel bolts and screws used within the temperature range of -50°C to $+300^{\circ}\text{C}$, and does not make provision for products requiring special properties, such as weldability, or for corrosion-resistant materials.

NOTES:

1. The range of nominal sizes included in this standard is considered adequate for most of the applications for which this series is likely to be employed, but for the convenience of users requiring larger sizes, further information in relation to the derivation of tolerances and head dimensions is provided in Appendix A and Appendix B respectively.

The recommended classes of nuts suitable for assembly with ISO metric hexagon commercial bolts and screws are property class 5 for normal, slotted and cap nuts, and property class 04 for thin nuts. These classes are in accordance with AS 1112.

2. Bolts and screws manufactured of free cutting steel should not be used at a temperature in excess of $+250^{\circ}\text{C}$.
3. Precision bolts or screws of property classes 4.6 and 5.8 (see AS 1110) may be supplied in lieu of commercial products at the option of the supplier.
4. Hexagon bolts and screws given in this standard are in complete agreement with those given in international standards for product Grade 8 except for the tolerance on bolt length which is unchanged from the previous edition of this standard.

The hexagon sizes for M10 and M12 have also been changed from those given in the previous edition, reflecting changes introduced in ISO 272. Further information on this aspect is given in Appendix D.

2 DEFINITIONS. For the purpose of this standard, the following definitions apply:

2.1 Commercial bolts and screws — products made to relatively wide tolerances and having some or all surfaces, except screw threads, in the as-forged (hot or cold) condition.

2.2 Transition diameter (D_s) — the diameter of a circle formed at the transition between the fillet radius r and the bearing surface of the head.

2.3 Concentricity tolerance — of a bolt, is the allowable deviation of the shank with respect to the screw thread (see Fig. 1).

2.4 Symmetry tolerance — of a bolt or screw is the allowable deviation of the across-flats dimension with respect to the shank of a bolt or the major diameter of a screw (see Fig. 1).

2.5 Nominal length (l) — of a bolt or screw, is the distance from the bearing surface of the head to the extreme end of the shank including any chamfer or radius (see Fig. 2).

2.6 Thread length (b) — of a bolt, is the difference between the nominal length of the bolt and the distance between the bearing surface of the head and the nearest face of a nut with no internal chamfer, screwed as far as practicable on to the bolt by hand.

2.7 Length of unthreaded shank (l_u) — of a bolt, is the distance from the bearing surface of the bolt head to the last scratch of thread, or top of the extrusion angle, whichever is closer to the head.

2.8 Grip length (l_g) — of a bolt, is the minimum thickness of materials which can be clamped, but excluding the washer thickness.

2.9 Thread runout.

2.9.1 Bolts and screws with rolled threads — the distance from the top of the extrusion cone to the nearest face of a nut with no internal chamfer screwed on to the bolt as far as practicable by hand.

2.9.2 Bolts and screws with cut threads — the distance from the last witness of thread to the nearest face of a nut with no internal chamfer, screwed on to the bolt as far as practicable by hand.

3 METHOD OF MANUFACTURE. Hexagon bolts and screws may be produced by hot or cold forging with or without secondary machining. Alternatively they may be machined from bar stock.

4 SHAPE, DIMENSIONS AND FINISH.

4.1 Length of Hexagon Bolts and Screws. Nominal lengths, maximum lengths and minimum lengths of hexagon bolts and screws are given in Tables 3 and 4 respectively.

4.2 Ends of Hexagon Bolts and Screws. The ends of hexagon bolts and screws may, at the option of the manufacturer, be finished with either a 45-degree (nominal) chamfer, to a depth slightly exceeding the depth of thread, or a radius approximately equal to 1.25 times the nominal diameter of the shank. Alternatively, when bolts are made with rolled threads, the lead formed at the end of the bolt by the rolling operation may be regarded as providing the necessary chamfer to the end, no other machining operation being necessary. The end shall be reasonably square with the shank (see Fig. 2).