



Tolerances for fasteners

Part 2: Washers for bolts, screws and nuts—Product grades A, C and F

STANDARDS
Australia

Currently in preview, click buy full version

This Australian Standard® was prepared by Committee ME-029, Fasteners. It was approved on behalf of the Council of Standards Australia on 22 August 2016.
This Standard was published on 7 September 2016.

The following are represented on Committee ME-029:

- Association of Accredited Certification Bodies
 - Association of Wall and Ceiling Industries of Australia and New Zealand
 - Australasian Corrosion Association
 - Australian Chamber of Commerce and Industry
 - Australian Engineered Fasteners and Anchors Council
 - Australian Industry Group
 - Australian Steel Institute
 - Austroads
 - Bureau of Steel Manufacturers of Australia
 - CSIRO
 - Galvanizers Association of Australia
 - Materials Australia
 - National Association of Steel-Framed Housing
 - National Association of Testing Authorities, Australia
 - Society of Automotive Engineers—Australasia
 - Swinburne University of Technology
-

This Standard was issued in draft form for comment as DR AS 1237.2:2016.

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Standard through their representation on the Committee and through the public comment period.

Keeping Standards up-to-date

Australian Standards® are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting www.standards.org.au

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

Australian Standard[®]

Tolerances for fasteners

**Part 2: Washers for bolts, screws and
nuts—Product grades A, C and F**

Originally as part of AS 1237—1973.
Revised and redesignated in part as AS 1237.2—2002.
Second edition 2016.

COPYRIGHT

© Standards Australia Limited

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968.

Published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001, Australia

ISBN 978 1 76035 561 6

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee ME-029, Fasteners, to supersede AS 1237.2—2002. After consultation with stakeholders in both countries, Standards Australia and Standards New Zealand decided to develop this Standard as an Australian rather than an Australian/New Zealand Standard.

The objective of this Standard is to establish a selection of tolerances for use in the preparation of ISO product standards for punched plain washers of product grades A and C, for use with bolts, screws and nuts of nominal thread diameters of from 1 mm to 150 mm inclusive.

This Standard is identical with, and has been reproduced from ISO 4759-3:2016, *Tolerance for fasteners, Part 3: Washers for bolts, screws and nuts—Product grades A, C and F*.

As this Standard is reproduced from an International Standard, the following applies:

- (a) In the source text ‘this part of ISO 4759’ should read ‘this Australian Standard’.
- (b) A full point substitutes for a comma when referring to a decimal marker.

The term ‘informative’ has been used in this Standard to define the application of the annex to which it applies. An ‘informative’ annex is only for information and guidance.

None of the normative references in the source document have been adopted as Australian or Australian/New Zealand Standards.

CONTENTS

1	Scope	1
2	Normative references	1
3	Symbols	1
4	Tolerances	2
	Annex A (informative) Tolerances	8
	Bibliography	11

Currently in preview, click buy full version

AUSTRALIAN STANDARD

Tolerances for fasteners

Part 2:

Washers for bolts, screws and nuts—Product grades A, C and F

1 Scope

This part of ISO 4759 specifies tolerances for flat washers of product grades A, C and F with nominal diameters of 1 mm to 150 mm inclusive, designed to be used in bolted joints in combination with bolts, screws, studs and nuts.

This part of ISO 4759 may be applied to non-flat washers however it does not include all the tolerances related to these washers.

It applies to non-captive and captive washers, and to standard and non-standard washers.

It does not apply to dynamic disc springs.

Washers of product grades F and A are intended to be used with bolts, screws, studs and nuts of product grades A and B; washers of product grade C are intended to be used with bolts, screws, studs and nuts of product grade C.

NOTE The product grade refers to a specific tolerance range related to dimensional and geometrical characteristics (product grade F for fine tolerances, product grade A for precise tolerances, product grade C for large tolerances).

[Annex A](#) presents tolerances taken from ISO 286-1 and ISO 286-2.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1101, *Geometrical product specifications (GPS) — Geometrical tolerancing — Tolerances of form, orientation, location and run-out*

ISO 2692, *Geometrical product specifications (GPS) — Geometrical tolerancing — Maximum material requirement (MMR), least material requirement (LMR) and reciprocity requirement (RPR)*

3 Symbols

c_1	height of the internal chamfer, mm
c_2	height of the external chamfer, mm
d_1	clearance hole, mm
d_2	outside diameter, mm