

Australian Standard®

Acoustics—Hearing conservation

This Australian Standard was prepared by Committee AV/3, Acoustics—Human Effects. It was approved on behalf of the Council of Standards Australia on 12 March 1989 and published on 19 May 1989.

The following interests are represented on Committee AV/3:

Association of Consulting Engineers, Australia
Australian and New Zealand Pulp and Paper Industry Technical Association
(Appita)
Australian Environment Council
Confederation of Australian Industry
Department of Industrial Relations and Employment, N.S.W.
Department of Occupational Health, Safety and Welfare, W.A.
Institute of Marine Engineers
Metal Trades Industry Association of Australia
National Acoustic Laboratories
National Occupational Health and Safety Commission
Otolaryngological Society of Australia
Royal Australian Institute of Architects
Royal Institution of Naval Architects
South Australian Health Commission
Safety Institute of Australia
University of Queensland

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up-to-date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 87240.

Australian Standard®

Acoustics—Hearing conservation

First published as AS 1269—1976.
Second edition 1979.
Third edition 1983.
Fourth edition 1989.

STANDARDS AUSTRALIA

Amendment No 1
to
AS 1269—1989
Acoustics—Hearing conservation

CORRECTIONS

The 1989 edition of AS 1269 is amended as follows; the amendments should be inserted in the appropriate place.

SUMMARY: This Amendment applies to Clauses 3.2.2, 3.2.3, 3.2.4.2, 3.2.4.3, Table 3.1, and Appendix A.

Published on 13 October 1989.

AMDT
No 1
OCT.
1989

Page 10. Clause 3.2.2.
Delete ' $L_{Aeq,T,i}$ ' and *substitute* ' $L_{Aeq,Ti}$ '.

AMDT
No 1
OCT.
1989

Page 10. Clause 3.2.3.
Delete ' $L_{Aeq,T,i}$ ' and *substitute* ' $L_{Aeq,Ti}$ '.

AMDT
No 1
OCT.
1989

Page 10. Table 3.1.
Delete ' $L_{AeqT,i}$ ' and *substitute* ' $L_{Aeq,Ti}$ '.
Delete ' $L_{Aeq,T}$ ' and *substitute* ' $L_{Aeq,8h}$ '.

AMDT
No 1
OCT.
1989

Page 11. Clause 3.2.4.2. Note 2.
Delete
 $L_{Aeq,8h} = 90 + 10 \log_{10}(8.5/6.5) \times 10 \log_{10}0.86 = 91 \text{ dB(A)}$.
and *substitute*
 $L_{Aeq,8h} = 90 + 10 \log_{10}(8.5/6.5) + 10 \log_{10}0.86 = 91 \text{ dB(A)}$.

AMDT
No 1
OCT.
1989

Page 11. Clause 3.2.4.3.
Delete
 $L_{Aeq,8h} = 90 = 10 \log_{10} \left[D_M + \sum_i^n (PND)_i \right]$
and *substitute*
 $L_{Aeq,8h} = 90 + 10 \log_{10} \left[D_M + \sum_i^n (PND)_i \right]$

AMDT
No 1
OCT.
1989

Page 20. Paragraph A2. Lines 9, 12, and 14.
Delete 'Table A2' and *substitute* 'Table A1'.

AMDT
No 1
OCT.
1989

Page 21. Figure A1.
Delete ' $L_{Aeq,T,i}$ ' and *substitute* ' $L_{Aeq,Ti}$ '.

AMDT
No 1
OCT.
1989

Page 22. Paragraph A3.
Line 4, *delete* ' L_A ' and *substitute* ' $L_{Aeq,T}$ '.
Line 12, *delete* ' $L_{A1}, L_{A2}, L_{A3}, L_{A4}$ ' and *substitute* ' $L_{Aeq,T1}, L_{Aeq,T2}, L_{Aeq,T3}, L_{Aeq,T4}$ '.
Line 13, *delete* 'Table A1' and *substitute* 'Table A2'.
Line 13, *delete* ' L_A ' and *substitute* ' $L_{Aeq,T}$ '.
Line 16, after 'hour' *insert* 'is'.
Line 16, *delete* 'Table A1' and *substitute* 'Table A2'.

PREFACE

This Standard was prepared by Standards Australia's Committee on Acoustics—Human Effects, to supersede AS 1269—1983, *Hearing Conservation*.

AS 1269 has been widely used since its introduction in 1976 and its revisions in 1979 and 1983. The 1979 edition was called up in statutory regulations relating to protection of hearing of persons exposed to occupational noise and the 1983 edition continued to be part of those regulations.

This edition incorporates changes to Table 5.1 which now includes additional data for various types of earphone/cushion or earphone/enclosure combination fitted to audiometers. Appendix D has been revised to reflect the estimated incidence of hearing impairment, which is defined in the body of the Standard, in noise-exposed populations, instead of the hearing loss incidence presented in the 1983 edition.

The utilization of a criterion based on an $L_{Aeq,8h}$ of 90 dB(A) may not necessarily provide adequate protection for all persons in the working population. Appendix A in this Standard provides calculation of daily noise dose (*DND*) from equivalent continuous sound pressure level (L_{Aeq}) or cumulative exposure to different levels of sound exposure. Some persons have been shown to be more susceptible than others to noise-induced impairment, and Appendix D has been revised to provide data on estimated incidence of hearing impairment. As a general rule, it appears essential that personal hearing protection be provided at lower levels than those specified in statutory regulations, in the interest of protecting the more susceptible members of the working community.

The detection of the early stage of noise-induced hearing impairment is of crucial importance. Persons highly susceptible to noise-induced hearing loss will suffer loss of hearing sensitivity early in their exposure history. Experience has shown that such impairment can be detected by audiometric monitoring only if the standard of testing and the reliability of the tests are very high. Accordingly, this edition introduces a recommendation that all audiograms be obtained by averaging the results of at least two separate tests.

Part of Table 5.1, showing maximum permissible background noise levels for audiometric testing using noise-excluding audiometric headsets, has been revised and extended on the basis of data supplied by the National Acoustic Laboratories.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the Head Office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

	<i>Page</i>
SECTION 1. SCOPE AND GENERAL	
1.1 SCOPE	4
1.2 OBJECTIVES	4
1.3 REFERENCED DOCUMENTS	4
1.4 DEFINITIONS	4
1.5 RESPONSIBILITY FOR IMPLEMENTATION	5
SECTION 2. NOISE MEASUREMENT AND ASSESSMENT	
2.0 INTRODUCTION	6
2.1 SCOPE OF SECTION	6
2.2 TYPES OF NOISE ASSESSMENT	6
2.3 DESCRIPTION OF NOISE	7
2.4 SELECTION AND USE OF EQUIPMENT	7
2.5 NOISE MEASUREMENT PROCEDURES	8
2.6 FURTHER MEASUREMENT PROCEDURES FOR DETAILED ASSESSMENT FOR NOISE REDUCTION	9
2.7 MEASUREMENT PROCEDURES FOR SELECTION OF HEARING PROTECTION DEVICES	9
SECTION 3. EVALUATION OF NOISE	
3.1 SCOPE OF SECTION	10
3.2 CALCULATION OF 8-HOUR EQUIVALENT CONTINUOUS A-WEIGHTED SOUND PRESSURE LEVEL ($L_{Aeq,8h}$)	10
3.3 ACTION TO BE TAKEN WHEN THE NOISE EXPOSURE LEVEL LIMIT IS EXCEEDED	11
SECTION 4. ENGINEERING NOISE REDUCTION	
4.1 SCOPE OF SECTION	13
4.2 NOISE REDUCTION	13
SECTION 5. HEARING PROTECTION PROGRAM	
5.1 SCOPE OF SECTION	14
5.2 ADMINISTRATIVE RESPONSIBILITIES NECESSITATED BY A HEARING PROTECTION PROGRAM	14
5.3 HEARING PROTECTION DEVICES	15
5.4 SELECTION OF HEARING PROTECTION DEVICES	15
5.5 FITTING, USE, MAINTENANCE, AND SUPERVISION OF HEARING PROTECTION DEVICES	17
5.6 AUDIOMETRY AND ASSESSMENT OF RESULTS	18
APPENDICES	
A ALTERNATIVE METHODS FOR CALCULATION OF DAILY NOISE DOSE	20
B GUIDANCE IN INSTRUMENTATION AND THE USE OF INS- TRUMENTS IN THE MEASUREMENT OF NOISE EXPOSURE IN HEARING CONSERVATION	23
C METHODS OF CALCULATING THE NOISE REDUCTION PROVIDED BY HEARING PROTECTION DEVICES	26
D ESTIMATED PREVALENCE OF NOISE-INDUCED HEARING IMPAIRMENT IN NOISE-EXPOSED POPULATIONS	30
E AUDIOMETRIC TEST PROCEDURE	32

STANDARDS AUSTRALIA

Australian Standard
Acoustics—Hearing conservation

SECTION 1. SCOPE AND GENERAL

1.1 SCOPE. This Standard describes the establishment of a hearing conservation program to protect persons who are occupationally exposed to noise.

For the purpose of this Standard, a hearing conservation program is a planned procedure to evaluate and control noise and to prevent impairment of hearing in persons exposed to excessive noise. The components of the program are as follows:

- (a) Motivation and education of all concerned to accept responsibility for their part in the hearing conservation program.
- (b) Measurement of the noise.
- (c) Evaluation of any noise problem.
- (d) Reduction of noise exposure.
- (e) Provision of personal hearing protection and regular hearing testing if noise exposure remains excessive.

This Standard does not specify limits for exposure to occupational noise. Attention is invited to the appropriate limits for exposure to occupational noise specified in the relevant Statutory Regulations.

NOTE: Aspects of the implementation of the programs regarded as mandatory, if the programs are to be effective, are indicated by the use of words 'shall', or 'is necessary'. Aspects to be regarded as highly advisable are indicated by the use of the word 'should'. Clauses of both types, together with informative material for further guidance, are collated into a continuous text for easier comprehension.

1.2 OBJECTIVES.

1.2.1 Noise reduction program. As a primary aim, the Standard seeks to reduce exposure to noise by reducing noise levels. The Standard describes methods of measurement (see Section 2) which can be used to determine whether statutory noise exposure limits are exceeded (see Section 3), and provides advice on methods of reducing noise levels by engineering means (see Section 4). Where such methods of hearing conservation are not readily feasible, it becomes necessary to introduce other methods, such as the wearing of hearing protection devices (see Section 5).

1.2.2 Hearing protection program. The Standard also describes methods for personal hearing protection and regular hearing testing (see Section 5) to be adopted where technical or economic problems delay the reduction of noise exposure by engineering means or by administrative procedures.

1.3 REFERENCED DOCUMENTS. The following documents are referred to in this Standard.

AS	
1259	Sound level meters
1270	Acoustics—Hearing protectors
1319	Safety signs for the occupational environment
2399	Personal noise dosimeters

2586	Audiometers
2659	Guide to the use of sound measuring equipment
2659.1	Part 1: Portable sound level meters
2659.2	Part 2: Portable equipment for integration of sound signals
2680	Acoustics—Performance requirements for tape recording equipment for use in acoustical measurement systems
Z41	Octave, half octave and one-third octave band pass filters intended for the analysis of sound and vibrations
IEC	
804	Integrating-averaging sound level meters
ISO	
1999	Acoustics—Assessments of occupational noise exposure for hearing conservation purposes

1.4 DEFINITIONS. For the purpose of this Standard, the definitions below apply.

1.4.1 Daily noise dose (DND)—the sum of partial noise doses to which an employee is exposed throughout a representative working day. It is the ratio of the noise exposure experienced by a person in a representative working day to a reference value of noise exposure.

NOTES:

- The reference value of noise exposure is defined in AS 2399 as being $3.2 \text{ Pa}^2 \cdot \text{h}$, where the pressure quantity is A-weighted. This reference value corresponds to a *DND* of 1.0, or an $L_{\text{Aeq},8\text{h}}$ value of 90 dB(A) re 20 μPa . The reference value has been set arbitrarily.
- For the basis of *DND* calculations, see Clause 3.2 and Appendix A.

1.4.2 Partial noise dose—a parameter determined by a sound pressure level and its duration during a representative working day.

1.4.3 Equivalent continuous A-weighted sound pressure level ($L_{\text{Aeq},T}$)—that steady sound pressure level which would in the course of time period T cause the same A-weighted sound energy as that due to the actual noise over the same time period.

Symbol: $L_{\text{Aeq},T}$ Unit symbol: dB(A)

1.4.4 Eight-hour equivalent continuous A-weighted sound pressure level ($L_{\text{Aeq},8\text{h}}$)—that steady sound pressure level which would in the course of an 8-hour period cause the same A-weighted sound energy as that due to the actual noise over a representative working day.

Symbol: $L_{\text{Aeq},8\text{h}}$ Unit symbol: dB(A)

NOTES:

- For the basis of $L_{\text{Aeq},8\text{h}}$ calculations, see Clause 3.2.
- $L_{\text{Ceq},8\text{h}}$ is a similar quantity, but refers to the C-weighted sound energy. (See Clause 2.2.4 and Appendix A).