



**Glass in buildings—Selection and
installation**

STANDARDS
Australia

Currently in preview, click buy full version

This Australian Standard® was prepared by Committee BD-007, Glazing and Fixing of Glass. It was approved on behalf of the Council of Standards Australia on 28 November 2005. This Standard was published on 16 January 2006.

The following are represented on Committee BD-007:

- Australian Building Codes Board
- Australian Chamber of Commerce and Industry
- Australian Glass and Glazing Association
- Australian Industry Group
- Australian Institute of Building Surveyors
- Australian Shop and Office Fitting Industry Association
- Australian Window Association
- Building Research Association of New Zealand
- CSIRO Manufacturing and Infrastructure Technology
- Certification Interests (Australia)
- Engineers Australia
- Housing Industry Association
- Master Builders Australia
- Monash University
- New Zealand Safety Glass Association
- University of New South Wales
- University of Sydney
- Window Association of New Zealand
- Window Film Association of Australia & New Zealand
- Window and Door Industry Council

Additional Interests:

- Leadlight, Decorative and Stained Glass Association

This Standard was issued in draft form for comment as DR 02145.

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Standard through their representation on the Committee and through the public comment period.

Keeping Standards up-to-date

Australian standards® are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting www.standards.org.au

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

Australian Standard[®]

Glass in buildings—Selection and installation

First published as AS CA26—1957.
AS CA26—1957 revised and redesignated AS 1288—1973.
AS 1288—1973 revised and redesignated AS 1288.1—1979, AS 1288.2—1979
and AS 1288.3—1979.
AS 1288.1—1979, AS 1288.2—1979 and AS 1288.3—1979 revised, amalgamated
and redesignated AS 1288—1989.
Fourth edition 2006.
Reissued incorporating Amendment No. 1 (January 2008).
Reissued incorporating Amendment No. 2 (November 2011).
Reissued incorporating Amendment No. 3 (February 2016).

COPYRIGHT

© Standards Australia Limited

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968.

ISBN 0 7337 7096 7

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee BD-007, Glazing and Fixing of Glass, to supersede AS 1288—1994.

This Standard incorporates Amendment No. 1 (January 2008), Amendment No. 2 (November 2011) and Amendment No 3 (February 2016). The changes required by the Amendment are indicated in the text by a marginal bar and amendment number against the clause, note, table, figure or part thereof affected.

The objective of this Standard is to provide uniform direction for the use and installation of glazing throughout Australia to allow its use in legislation, and to clarify technical definitions.

This Standard will be referenced in the Building Code of Australia 2006, thereby superseding AS 1288—1994, which will be withdrawn in 12 months from the date of publication of this Standard.

When revising this Standard, consideration was given to the existing human impact safety requirements of AS 1288—1994 and NZS 4223.3:1999 *Code of practice for glazing in buildings Part 3: Human impact safety requirements*, as well as AS 6202-4, *Glazing for buildings, Part 4: Safety related to human impact*.

There was also a need to recognize that accidents involving glass continued at a high rate and at a considerable cost to the community. With these factors in mind, changes were made that have resulted in the introduction of increased areas of safety glass and the reduction of areas of ordinary glass in locations where accidents are known to occur at greater frequency. The Standard has also been closely aligned with international practice by the adoption of selected criteria from international Standards.

The change to ultimate limit state design in the new wind code has necessitated the corresponding upgrading of the wind loading charts. The new charts are based on the increased ultimate limit state wind speed. The committee has taken this opportunity to improve the design charts to include basic criteria such as the influence of aspect ratio and slenderness factor. The charts are more comprehensive as they incorporate all relevant aspects that influence the performance of glass in the one chart for each glass type and thickness.

The most significant changes of this revision include the following:

- (a) Change from permissible design stresses for wind loading to Ultimate Limit State design.
- (b) New design charts for wind loading based on ULS and taking into consideration panel aspect ratio.
- (c) Introduction of new and increased areas of safety glass in locations subject to high risk of human impact.
- (d) New section on installation requirements for glass.
- (e) New sections and detailed specifications for overhead glazing, balustrades, faceted glazing and fin-supported glazing.

This Standard makes recommendations for design and installation practice based on proven techniques. Where materials or methods are used that are not covered in this Standard, or if alternative solutions are used, they must satisfy the relevant performance requirements of the NCC, determined and assessed in accordance with the NCC.

Notes to the text contain information and guidance. They are not an integral part of the Standard.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the appendix to which they apply. A 'normative' appendix is an integral part of a Standard, whereas an 'informative' appendix is only for information and guidance.

Currently in preview, click buy full vers.

CONTENTS

	<i>Page</i>
FOREWORD.....	7
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE.....	8
1.2 APPLICATION	8
1.3 NORMATIVE REFERENCES	9
1.4 DEFINITIONS.....	10
1.5 NOTATION.....	11
SECTION 2 MATERIALS	
2.1 GLASS	17
2.2 OTHER GLAZING MATERIALS	18
SECTION 3 GENERAL DESIGN CRITERIA	
3.1 GENERAL.....	19
3.2 LOADS AND OTHER ACTIONS.....	19
3.3 LIMIT STATES.....	19
3.4 LAMINATED GLASS AND INSULATING GLASS UNITS.....	22
3.5 FRAMES	23
3.6 DESIGN THICKNESS OF GLASS.....	23
3.7 STRUCTURAL SILICONE.....	24
3.8 SELECTION OF GLASS FOR MINIMIZING THE RISK DUE TO GLASS SPONTANEOUS FRACTURE	24
SECTION 4 DESIGN FOR WIND LOADING	
4.1 GENERAL.....	26
4.2 DESIGN WIND PRESSURE	26
4.3 INSULATING GLASS UNITS.....	26
4.4 MAXIMUM SPAN FOR GLASS PANELS SUBJECTED TO WIND LOADING....	26
4.5 ORGANIC SAFETY FILMS AND OTHER GLASS COATINGS.....	28
SECTION 5 CRITERIA FOR HUMAN IMPACT SAFETY	
5.1 SCOPE.....	64
5.2 DOORS.....	66
5.3 SIDE PANELS	66
5.4 GLAZING CAPABLE OF BEING MISTAKEN FOR A DOORWAY OR OPENING	67
5.5 LOW-LEVEL GLAZING IN RESIDENTIAL BUILDINGS	68
5.6 EXTERNAL SHOPFRONTS	68
5.7 INTERNAL SHOPFRONTS AND INTERNAL PARTITIONS	68
5.8 BATHROOM, ENSUITE AND SPA ROOM GLAZING	69
5.9 BALUSTRADES.....	69
5.10 SCHOOLS, EARLY CHILDHOOD CENTRES, AGED CARE BUILDINGS AND NURSING HOMES	69
5.11 MIRRORS AND OTHER TYPES OF GLASS SUBJECT TO RISK OF HUMAN IMPACT	70
5.12 LOUVRE BLADES SUBJECT TO RISK OF HUMAN IMPACT	70
5.13 WINDOW SEAT GLAZING.....	70
5.14 OPERABLE WINDOWS.....	70

	<i>Page</i>
5.15 TWO-EDGE UNFRAMED GLAZING	71
5.16 STAIRWAY GLAZING	71
5.17 LEADLIGHTS.....	72
5.18 CURVED GLASS.....	72
5.19 MAKING GLASS VISIBLE (MANIFESTATION).....	72
5.20 UNFRAMED EDGES	73
5.21 USE OF SAFETY GLASS OF NON-STANDARD THICKNESSES	73
5.22 INSULATING GLASS UNITS.....	73
5.23 IDENTIFICATION OF SAFETY GLASS.....	73
5.24 AREAS SUBJECT TO HIGH RISK OF BREAKAGE	74
5.25 FIRE DOORS	75
SECTION 6 SLOPED OVERHEAD GLAZING	
6.1 GENERAL.....	78
6.2 LOADS AND ACTIONS.....	78
6.3 LOAD COMBINATIONS	78
6.4 DESIGN CRITERIA.....	79
6.5 SELECTION OF OVERHEAD GLASS	79
SECTION 7 BALUSTRADES	
7.1 GENERAL.....	84
7.2 LOADS AND OTHER ACTIONS.....	84
7.3 SELECTION OF BALUSTRADE GLASS.....	84
7.4 SWIMMING POOL BARRIERS/FENCES	90
SECTION 8 INSTALLATION	
8.1 SCOPE.....	91
8.2 SITE WORKING AND DAMAGE OF GLASS	91
8.3 DIMENSIONAL REQUIREMENTS	91
8.4 GLAZING MATERIALS	93
8.5 SETTING BLOCKS	94
8.6 LOCATION BLOCKS	95
8.7 DISTANCE PIECES.....	97
8.8 PREPARATION OF REBATES AND GROOVES	97
8.9 GLAZING BEAD	97
8.10 STRUCTURAL SEALANTS.....	97
SECTION 9 FRAMED, UNFRAMED, AND PARTLY FRAMED GLASS ASSEMBLIES	
9.1 GENERAL.....	98
9.2 STRUCTURAL SILICONE.....	98
9.3 FACETED GLAZING	98
9.4 FIN-SUPPORTED GLAZING.....	101
9.5 UNFRAMED TOUGHENED AND TOUGHENED LAMINATED GLASS ASSEMBLIES	104
APPENDICES	
A SIMPLIFIED METHOD FOR DETERMINING ULTIMATE AND SERVICEABILITY LIMIT STATE DESIGN WIND PRESSURES	108
B WORKED EXAMPLES TO SECTION 4 WIND LOADING REQUIREMENTS ...	119
C BASIS FOR DETERMINATION OF FIN DESIGN TO PREVENT BUCKLING ..	126
D RECOMMENDATIONS FOR SHOWER SCREEN INSTALLATION	132
E SLOPED OVERHEAD GLAZING FRACTURE CHARACTERISTICS	133
F STRUCTURAL SILICONE GLAZING	135

		<i>Page</i>
G	FLOW CHARTS	138
H	BIBLIOGRAPHY	144

Currently in preview, click buy full version

FOREWORD

Due to the revision of AS 1170.2—1989, *Minimum design loads on structures—Wind loads* to include limit states design, it became necessary for AS 1288 to be revised. The rationale used in the revision of AS 1288 to include the ultimate design strength of glass is given below.

A3

The National Construction Code (NCC) sets the importance levels and annual probability of exceedance for wind, snow and earthquake actions applicable to buildings and structures.

Design wind speeds depend on the importance levels of the buildings as well as the wind region for the building, resulting in increased risk of glass breakage for glazing in lower importance levels.

The previous edition of AS 1288 gave permissible design stresses for wind load as 16.7 MPa for glass ≤ 6 mm thickness and 15.2 MPa for glass > 6 mm thickness. However, since the publication of the previous edition in 1994, further research was carried out and it was found that the stresses varied considerably with panel aspect ratio and glass thickness.

The charts in this edition are based on ULS stresses of 27.0 MPa, for the thickest glass (25 mm) and 41.0 MPa for the thinnest glass (3 mm). It was also agreed that glass edge design stresses are to be 80% of the mid-span (i.e. away from edge) stresses. The limiting design stresses for each glass thickness used in developing the design charts are given in Appendix B.

STANDARDS AUSTRALIA
Australian Standard
Glass in buildings—Selection and installation

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE

This Standard sets out procedures for the selection and installation of glass in buildings, subject to wind loading, human impact, and special applications such as overhead glazing, balustrades and glass assemblies.

Glass strength requirements are given for glazing, based on the tensile stresses developed on the surface of the glass.

This Standard does not cover the following:

- (a) Glazing in lift cars and lift wells (see Note 1).
- (b) Furniture glass, cabinet glass, vanities, glass basins, refrigeration units, internal glass fittings and internal wall mirrors not specifically covered by Section 5 (see Note 2).
- (c) Buildings and structures with no public access intended for horticultural or agricultural use.
- (d) Windows and doors in heritage buildings as defined by the relevant State or Territorial authority (see Note 3).
- (e) Restoration and or repairs to existing leadlights.
- (f) Special glazing applications which might fail due to the stresses other than tensile stresses, such as shear stresses.

- A1 | (g) Glass blocks, bricks or pavers.

NOTES:

- 1 For glazing in lift cars and lift wells, see AS 1735.2 (Appendix H)
- 2 For further guidance see HB 125.
- 3 The traditional use of these buildings suggests their current construction and glazing practices are acceptable. However, consideration should always be given to the brittle nature of glass and the consequences of its breakage.
- 4 In Australia, legislation requires products to be 'fit for purpose'. Where glazing is replaced because of breakage or any other reason, it is recommended that the replacement glass comply with the requirements of the relevant sections of this Standard, unless otherwise permitted by the relevant legislation.

1.2 APPLICATION

The thickness and type of glass required shall be determined on the basis of all the following criteria:

- (a) For installations subject to wind loading, glass to be selected using either first principles as set out in Section 3, or using the simplified design as set out in Section 4.

NOTE: Section 4 may give a more conservative design solution.

- (b) For human impact considerations, glass to be selected according to Section 5.
- (c) For overhead glazing, glass to be selected according to Section 6.