

Australian Standard[®]

Methods of testing soils for engineering purposes

Method 7.1.3: Soil reactivity tests— Determination of the shrinkage index of a soil—Core shrinkage index

1 SCOPE This Standard sets out a method for determining the shrinkage index of a soil (see AS 2870) by core shrinkage testing.

2 REFERENCED DOCUMENTS The following documents are referred to in this Standard:

AS

- 1289 Methods of testing soils for engineering purposes
1289.0 Part 0: General requirements and list of methods
1289.2.1.1 Method 2.1.1: Soil moisture content tests—Determination of the moisture content of a soil—Oven drying method (standard method)
1289.2.2.1 Method 2.2.1: Soil moisture content tests—Determination of the total suction of a soil—Standard method
2870 Residential slabs and footings—Construction

3 APPARATUS The following apparatus is required:

- (a) Thin-walled sampler consisting of a tube with a bevelled cutting edge machined directly on the sample tube. The bevelled cutting edge shall make an angle not exceeding 15° to the axis of the tube with a permitted land width at the cutting edge not exceeding 0.5 mm. The ratio of net projected area of sampler to projected area of sample core shall not exceed 10%, and any internal clearance shall not exceed 1% of the diameter at the cutting edge.
- (b) Drying oven complying with AS 1289.0.
- (c) Balance of 500 g capacity having a limit of performance not exceeding ± 0.05 g.
- (d) Spatula or palette knife of convenient size.
- (e) Vacuum desiccator.
- (f) Metal drawing pins.
- (g) Vernier callipers with a precision of 0.05 mm, capable of measuring lengths 50 to 120 mm.
- (h) Apparatus to measure total soil suction in accordance with that described in AS 1289.2.2.1.
- (i) Drying room with temperature controlled at $23 \pm 2^\circ\text{C}$.
- (j) Supersaturated solution of ammonium chloride (see Note 1).