

Australian Standard<sup>®</sup>

---

**Bursting discs and bursting disc  
devices—Guide to application,  
selection, and installation**

---

[Title allocated by Defence Cataloguing Authority: DISK,  
RUPTURABLE (Guide to application, selection and installation)]

This Australian Standard was prepared by Committee ME/1, Boilers and Unfired Pressure Vessels. It was approved on behalf of the Council of Standards Australia on 12 May 1989 and published on 18 August 1989.

---

The following interests are represented on Committee ME/1:

Aluminium Development Council  
Australian Compressed Air Institute  
Australian Institute for Non-destructive Testing  
Australian Institute of Energy  
Australian Institute of Petroleum  
Australian Liquefied Petroleum Gas Association  
Australian Valve Manufacturers Association  
Australian Welding Institute  
Australian Welding Research Association  
Boiler and Pressure Vessel Manufacturers Association of Australia  
Bureau of Steel Manufacturers of Australia  
Confederation of Australian Industry  
Department of the Arts, Sport, the Environment, Tourism, and Territories  
Department of Defence  
Department of Industrial Affairs, Qld  
Department of Industrial Relations and Employment, N.S.W.  
Department of Labour, S.A.  
Department of Labour, Vic.  
Department of Labour and Industry, Tas.  
Department of Occupational Health, Safety and Welfare, W.A.  
Electricity Supply Association of Australia  
Institute of Metals and Materials, Australia  
Institution of Engineers, Australia  
Insurance Council of Australia  
Metal Trades Industry Association of Australia  
National Association of Trading Authorities, Australia  
Railways of Australia Committee  
Society of Mechanical Engineers of Australasia  
Sugar Research Institute  
Work Health Authority, N.T.

---

**Review of Australian Standards.** To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

---

*This Standard was issued in draft form for comment as DR 88118.*

Australian Standard<sup>®</sup>

---

**Bursting discs and bursting disc  
devices—Guide to application,  
selection, and installation**

---

First published as AS 1358—1972.  
Second edition 1989.

Incorporating:  
Amdt 1—1991

PUBLISHED BY STANDARDS AUSTRALIA  
(STANDARDS ASSOCIATION OF AUSTRALIA)  
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 5788 5

## PREFACE

This Standard was prepared by Standards Australia's Committee on Boilers and Unfired Pressure Vessels, to supersede AS 1358-1972, *Bursting discs*.

In the preparation of this Standard, the committee considered ISO 6718, *Bursting discs and bursting disc devices*, and the assistance gained therefrom is acknowledged.

## © Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

## CONTENTS

	<i>Page</i>
<b>SECTION 1. SCOPE AND GENERAL</b>	
1.1 SCOPE .....	4
1.2 DEFINITIONS .....	4
<b>SECTION 2. GENERAL DESCRIPTIONS OF BURSTING DISCS AND BURSTING DISC DEVICES</b>	
2.1 BURSTING DISCS .....	6
2.2 BURSTING DISC HOLDERS .....	6
2.3 BACKPRESSURE SUPPORTS .....	10
2.4 TEMPERATURE SHIELDS .....	10
2.5 STIFFENING RINGS .....	10
2.6 GASKETS .....	10
2.7 PROTECTION FROM CORROSION .....	10
<b>SECTION 3. APPLICATION AND SELECTION OF BURSTING DISCS AND BURSTING DISC DEVICES</b>	
3.1 APPLICATION .....	11
3.2 SELECTION .....	11
3.3 DISCHARGE CAPACITY .....	11
3.4 IDENTIFICATION AND MARKING .....	11
<b>SECTION 4. INSTALLATION OF BURSTING DISC DEVICES</b>	
4.1 GENERAL .....	12
4.2 BURSTING DISC ALONE .....	12
4.3 IN COMBINATION WITH SAFETY VALVES OR IN PARALLEL .....	12
4.4 BACKPRESSURE SUPPORTS .....	13
4.5 MODIFICATIONS .....	13
4.6 GASKETS .....	13
<b>APPENDICES</b>	
A INFORMATION TO ASSIST DESIGN OR SELECTION OF BURSTING DISCS AND BURSTING DISC DEVICES .....	14
B IDENTIFICATION AND MARKING OF BURSTING DISCS AND BURSTING DISC DEVICES .....	15
C DISCHARGE CAPACITY .....	16
D DEVIATION OF COMPRESSIBILITY FACTOR .....	22

## STANDARDS AUSTRALIA

## Australian Standard

**Bursting discs and bursting disc devices—Guide to application, selection, and installation**

## SECTION 1. SCOPE AND GENERAL

**1.1 SCOPE.** This Standard provides guidance on the application, selection, and installation of bursting discs and bursting disc devices.

Information which the purchaser may provide to assist in the design or the selection of bursting discs and bursting disc devices is shown in Appendix A.

The information which may be used for identification and the information which may be marked on bursting discs and bursting disc devices is shown in Appendix B.

Equations for the calculation of the discharge capacity for single phase flow are shown in Appendix C.

**1.2 DEFINITIONS.** For the purpose of this Standard, the definitions below apply.

**1.2.1 Bursting pressure**—the value of the pressure differential across the disc at which a bursting disc device functions. (See Note to Clause 1.2.2.)

**1.2.2 Specified bursting pressure**—the pressure, quoted with a coincident temperature, specified by the user or his agent when defining the disc requirement.

NOTE: The words maximum and minimum may be used with the terms bursting pressure and specified bursting pressure.

**1.2.3 Average bursting pressure**—the arithmetic average value, at the coincident temperature, of the test bursts carried out on a batch of discs.

**1.2.4 Coincident temperature (bursting pressure)**—the temperature used in conjunction with bursting pressure.

**1.2.5 Operating temperature**—the average temperature of the disc and the surrounding parts during normal operation.

**1.2.6 Bursting tolerance**—the maximum variation of test results in equal positive and negative quantities or percentages related to the average bursting pressure. Where a zero manufacturing range is stated, the tolerance is applied directly to the specified bursting pressure.

**1.2.7 Manufacturing range**—a range of pressure within which the average bursting pressure of a batch of bursting discs falls in order to be acceptable for a particular application.

**1.2.8 Performance tolerance**—a range of pressure in positive and negative quantities or percentages which includes both manufacturing range and bursting tolerance at a coincident temperature, which is applied directly to the specified bursting pressure.

**1.2.9 Foil**—the sheet or strip used for the manufacture of metallic bursting discs.

**1.2.10 Batch**—a group of bursting discs of the same type, size, average bursting pressure, and coincident temperature, manufactured from material of the same identity and properties made as a single group.

**1.2.11 Bursting disc device**—a non-reclosing pressure-relief device actuated by differential pressure and designed to function by the bursting or venting of the bursting disc.

**1.2.12 Bursting disc assembly**—the complete assembly of components which are installed in the bursting disc holder to perform the desired function.

**1.2.13 Bursting disc**—the pressure-containing and pressure-sensitive element of a bursting disc device.

**1.2.14 Bursting disc holder**—that part of a bursting disc device which retains the bursting disc assembly in position.

**1.2.15 Backpressure**—the static pressure existing at the outlet of a bursting disc device at the time the device is required to operate. It is the result of pressure in the discharge system from other sources or as a result of vacuum on the upstream side.

**1.2.16 Backpressure support**—that component of a bursting disc assembly which prevents the failure of the disc due to backpressure differential.

NOTE: Backpressure support which is intended to prevent the failure of the disc when the system pressure falls below atmospheric pressure is sometimes referred to as a vacuum support.

**1.2.17 Baffle plate**—a plate attached to vent side of a bursting disc device or system to redirect discharge or reduce recoil.

**1.2.18 Muffled outlet**—a component of a bursting disc device which disperses the discharge.

**1.2.19 Stiffening ring**—an integral component of the bursting disc assembly used primarily for the stiffening of fragile discs.

**1.2.20 Coating**—a layer of metallic or non-metallic material applied by brush, spray, dipping, fluidized bed, or other similar method to components of a bursting disc device.

**1.2.21 Lining**—an additional sheet or sheets of material forming part of the bursting disc assembly or holder. The lining can be metallic or non-metallic.

**1.2.22 Plating**—a metal layer applied to a disc or holder by a plating process.

**1.2.23 Excess flow valve**—a device which permits limited flow. When this flow is exceeded the valve closes.

**1.2.24 Conventional domed bursting disc**—a bursting disc which is domed in the direction of the bursting pressure and designed to fail in tension. (See Figures 2.2 and 2.3.)

**1.2.25 Slotted lined bursting disc**—a conventional domed bursting disc made up of two or more layers, one of which is slit or slotted so as to reduce its strength and to control the bursting pressure of the bursting disc. (See Figure 2.4.)