

Australian Standard™

Design of rotating steel shafts

Currently in preview, click buy full version



**STANDARDS
AUSTRALIA**

This Australian Standard was prepared by Committee ME-005, Cranes. It was approved on behalf of the Council of Standards Australia on 9 March 2004 and published on 21 May 2004.

The following are represented on Committee ME-005:

Australian Chamber of Commerce and Industry
Australian Elevator Association
Australian Industry Group
Australian Institute for Non-Destructive Testing
Bureau of Steel Manufacturers of Australia
Construction and Mining Equipment Association of Australia
Crane Industry Council of Australia
Department of Administrative and Information Services (South Australia)
Department of Employment Training and Industrial Relations (Qld)
Department of Infrastructure, Energy and Resources (Tasmania)
Department of Labour New Zealand
Institution of Engineers Australia
State Chamber of Commerce
The Association of Consulting Engineers Australia
The University of New South Wales
Victorian WorkCover Authority
WorkCover NSW
WorkSafe Western Australia

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Web Shop at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Global Standard*, has a full listing of revisions and amendments published each month.

Australian Standards™ and other products and services developed by Standards Australia are published and distributed under contract by SAI Global, which operates the Standards Web Shop.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001..

STANDARDS AUSTRALIA

RECONFIRMATION

OF

AS 1403—2004

Design of rotating steel shafts

RECONFIRMATION NOTICE

Technical Committee ME-005 has reviewed the content of this publication and in accordance with Standards Australia procedures for reconfirmation, it has been determined that the publication is still valid and does not require change.

Certain documents referenced in the publication may have been amended since the original date of publication. Users are advised to ensure that they are using the latest versions of such documents as appropriate, unless advised otherwise in this Reconfirmation Notice.

Approved for reconfirmation in accordance with Standards Australia procedures for reconfirmation on 1 November 2016.

The following are represented on Technical Committee ME-005:

Australian Chamber of Commerce and Industry
Australian Industry Group
Australian Institute for Non-Destructive Testing
Bureau of Steel Manufacturers of Australia
Concrete Pumping Association of Australia
Crane Association of New Zealand
Crane Industry Council of Australia
Department of Industry, Skills and Regional Development (NSW)
Department of Justice and Attorney General (QLD)
Electricity Engineers Association (New Zealand)
Engineers Australia
Institution of Professional Engineers New Zealand
SafeWork NSW
Transport for NSW
Worksafe Division, Department of Commerce, Western Australia
Worksafe New Zealand
WorkSafe Victoria

NOTES

Currently in preview, click buy full vers.

Australian Standard™

Design of rotating steel shafts

Originated as AS B249—1969.
Previous edition AS 1403—1985.
Fourth edition 2004.

COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd
GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 5893 2

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee ME-005, Cranes, to supersede AS 1403—1985.

The 1985 edition was reviewed by the Committee, and it was found to be technically valid. Hence, this edition does not include technical alterations to the 1985 edition; however, the referenced documents have been updated, and editorial changes have been made to align with current Standards Australia policy.

The term 'informative' has been used in this Standard to define the application of the appendix to which it applies. An informative appendix is only for information and guidance.

CONTENTS

	<i>Page</i>
FOREWORD.....	4
1 SCOPE.....	5
2 REFERENCED DOCUMENTS.....	5
3 DEFINITIONS.....	6
4 NOTATION.....	6
5 APPLIED LOADING.....	8
6 MINIMUM CALCULATED DIAMETER OF SHAFT.....	8
7 SHAFT DESIGN AND MANUFACTURE.....	9
8 SHAFT DESIGN FACTORS.....	10
APPENDICES	
A 'TRIAL' SHAFT DIAMETER.....	21
B ITERATIVE METHOD FOR CALCULATING MINIMUM DIAMETER OF SHAFT.....	22
C CHARACTERISTICS OF MOTOR CONTROLLERS AND TORQUE-LIMITING DEVICES.....	23
D TYPICAL WORKED EXAMPLE—CRANE DRIVING MECHANISM.....	26
E TYPICAL WORKED EXAMPLE—CRANE FOOT DRIVE.....	36
F TYPICAL WORKED EXAMPLE—CONVEYOR DRIVE.....	45

FOREWORD

The method of design in this Standard is the same as that contained in the 1984 issue and is based on calculations for infinite life of the shaft.

It is noted that, as the result of extensive laboratory and/or field tests, shafts of diameters smaller than those resulting from calculations in this Standard may be used.

Although the method is not theoretically precise, it gives results that are of sufficient accuracy for practical purposes. The method makes no allowance for corrosive or other abnormal conditions, such as the presence of buckling, 'whipping', cyclic vibrations and similar effects (see Clause 7.2).

In some cases, deflection may be the factor that determines the minimum value of the shaft diameter (see Clause 7.6).

Typical worked examples employing this method of shaft design are given in Appendices D, E and F.

A 'trial' diameter may be necessary in the application of the design method. The value may be assumed on the basis of the designer's previous experience, or a simplified version of the method may be used to determine the order of magnitude of the shaft diameter, and the full method then applied to check the assumed trial diameter. A convenient quick method of estimating the 'trial' diameter is given in Appendix A, and an iterative method using programmable calculators is provided in Appendix B.

The process of carrying out an accurate and complete analysis of loadings applied to a shaft (see Clause 5) may involve much time and effort, and is warranted where it is desired to keep shaft diameters as small as possible. Where larger diameter shafts can be tolerated, it may be more appropriate to use approximations or to ignore inertia or other effects, but it is important to ensure that, where such inaccuracies are introduced, they result in increased rather than decreased margin of safety and stress-raising characteristics are avoided.

The effect of electric motors with high breakdown torque (also known as pull-out torque) or high locked-rotor torque (also known as starting torque) and the characteristics of motor controllers and torque-limiting devices are outlined in Appendix C.

STANDARDS AUSTRALIA

Australian Standard Design of rotating steel shafts

1 SCOPE

This Standard provides formulae for the design of rotating steel shafts that are subjected to torsional, bending and axial-tensile loads either singly or in combination, on the basis of infinite life.

The Standard does not cover specially developed shafts, for example, those involving extensive laboratory and field testing, heat treatment and like developments, or shafts for specific applications such as automotive and construction equipment transmissions.

NOTES:

- 1 Particular consideration has to be given to deflections of long shafts where the effects of out-of-balance forces tend to induce 'whipping', and to long shafts that are subject to buckling due to compressive loading (see Foreword).
- 2 The use of this method of shaft design enables justification of the use of shafts of minimal diameter. Where the designer conservatively sizes a shaft then only those calculations necessary to ensure that the shaft complies with this Standard (see Clause 5) are required.
- 3 A 'trial' shaft diameter is given in Appendix A.
- 4 An interactive method for calculating minimum diameter of shaft is given in Appendix B.
- 5 Characteristics of motor controllers and torque-limiting devices are provided in Appendix C.
- 6 A typical worked example for crane driving mechanism is provided in Appendix D.
- 7 A typical worked example for crane hoist drive is provided in Appendix E.
- 8 A typical worked example for conveyor drive is provided in Appendix F.

2 REFERENCED DOCUMENTS

The following documents are referred to in this standard:

AS

- | | |
|--------|---|
| 1391 | Methods for tensile testing of metals |
| 1654 | ISO system for limits and fits |
| 1654.1 | Part 1: Bases of tolerances, deviations and fits |
| 1654.2 | Part 2: Tables of standard tolerance grades and limit deviations for holes and shafts |

ISO

- | | |
|-----|--|
| 14 | Straight-sided splines for cylindrical shafts with internal centering; Dimensions, tolerances and verification |
| 415 | Straight cylindrical involute splines; Metric module, side fit; Generalities, dimensions and inspection |

BS

- | | |
|------|---|
| 2059 | Specification for straight-sided splines and serrations |
|------|---|