

Australian Standard 1544, Part 4—1980

METHODS FOR IMPACT TESTS ON METALS

Part 4—CALIBRATION OF THE TESTING MACHINE



STANDARDS ASSOCIATION OF AUSTRALIA

Incorporated by Royal Charter



THE FOLLOWING INDUSTRIAL, SCIENTIFIC AND GOVERNMENTAL organizations and departments were officially represented on the committee entrusted with the preparation of this standard:

Aluminium Development Council
Australian Institute of Metals
Bureau of Steel Manufacturers of Australia
Confederation of Australian Industry
Department of Defence (Standardization Committee)
Department of Industry and Commerce
Federal Chamber of Automotive Industries
Metal Trades Industry Association of Australia
National Association of Testing Authorities
National Measurement Laboratory
Railways of Australia Committee
Society of Automotive Engineers - Australia
Universities

This standard, prepared by Committee MT/6, Mechanical Testing of Metals, was approved by the Metals Standards Board on behalf of the Council of the Standards Association of Australia on 3 March 1980, and was published on 1 June 1980.

To keep abreast of progress in industry, Australian Standards are subject to continuous review and are kept up-to-date by the issue of amendments or new editions as necessary. It is important therefore that standards users ensure that their standards are up-to-date. Full details of all SAA publications will be found in the Annual List of Australian Standards; these details are supplemented by listings in the SAA monthly journal 'The Australian Standard'. Information on the Annual List and 'The Australian Standard' may be obtained from any sales office of the Association, where details are also available of the current status of individual standards. Suggestions for improvements to published standards, addressed to the head office of the Association, are welcomed.

This standard was issued in draft form for public review as DR 79002.

AUSTRALIAN STANDARD

**METHODS FOR IMPACT TESTS
ON METALS**

**Part 4
CALIBRATION OF THE
TESTING MACHINE**

AS 1544, Part 4 — 1980

First published (as AS B188, Part 4)...1966
AS 1544, Part 4 first published1980

PUBLISHED BY THE STANDARDS ASSOCIATION OF AUSTRALIA
STANDARDS HOUSE, 80 ARTHUR ST, NORTH SYDNEY, N.S.W.

ISBN 0 7262 1913 4



PREFACE

This standard was prepared by the Association's Committee on Mechanical Testing of Metals to supersede AS B188, Part 4—1966.

During preparation of this standard, the committee reviewed ASTM E23 which uses standard test pieces for proof testing of Charpy testing machines. The committee considered the introduction of a similar scheme into the Australian standard but resolved that as such a scheme requires considerable experimentation which has not been undertaken at this stage, it was not possible to include such a scheme; however, when the results are available this standard will be revised accordingly.

This standard requires reference to the following Australian standards

- AS 1544 Methods for Impact Tests on Metals
 - Part 1—Izod
 - Part 2—Charpy V-notch
 - Part 3—Charpy U-notch and Keyhole Notch

©Copyright — STANDARDS ASSOCIATION OF AUSTRALIA · 1980

Users of standards are reminded that copyright subsists in all SAA publications. No part of this publication may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing of the Standards Association of Australia.

CONTENTS

	<i>Page</i>
FORWORD	4
SECTION 1. SCOPE, APPLICATION AND DEFINITIONS	
1.1 Scope	5
1.2 Application	5
1.3 Definitions	5
1.4 Symbols and Designations	5
SECTION 2. COMPLETE CALIBRATION	
2.1 Scope of Section	11
2.2 Preliminary Inspection	11
2.3 Level	11
2.4 Bearings	11
2.5 Indicating Equipment	11
2.6 Friction Losses	12
2.7 Location of Pendulum	13
2.8 Test Piece Supports	14
2.9 Striker	15
2.10 Test Piece Clearance (Charpy Machines)	16
2.11 Centre of Percussion	16
2.12 Initial Potential Energy	17
2.13 Calibration of Scales	17
2.14 Striking Velocity	18
2.15 Time Interval Between Complete Calibrations	19
2.16 Record of Results	19
2.17 Report of Complete Calibration	19
SECTION 3. PARTIAL CALIBRATION	
3.1 Scope of Section	20
3.2 Procedure for Partial Calibration	20
3.3 Time Interval Between Partial Calibrations	20
3.4 Record of Results	20
3.5 Report of Partial Calibration	20
APPENDIX A. DIMENSIONS OF GAUGES	22

STANDARDS ASSOCIATION OF AUSTRALIA

Australian Standard METHODS FOR IMPACT TESTS ON METALS

PART 4—CALIBRATION OF THE TESTING MACHINE

FOREWORD

The methods for the calibration of pendulum impact testing machines described in this standard relate to the following elements of the machine, which are illustrated in Figs 1 to 4:

- (a) Machine framework, i.e. the structure supporting the pendulum, excluding only the foundation.
- (b) Pendulum and striker.
- (c) Test piece supports.
- (d) Indicating equipment, e.g. scale and friction pointer.

The clauses describing these methods have been drafted with particular application to the normal arrangement depicted in Figs 1, 3 and 5 (a), with the struck face of the test piece vertically below the axis of rotation. However, in some machines the test piece supports have been advanced so that impact occurs before the pendulum is at the bottom of its swing and the support surfaces are tilted by the amount of the angular advance. In other machines the long axis of the test piece, and not the struck face, is vertically below the axis of rotation. There is no evidence that either variation affects the results obtained on the machine. Clauses 2.7.2, 2.8, 2.12 and 2.14 should be interpreted to take account of these variations.

In the application of the methods, all the absorbed energy indicated by the machine is attributed to the fracturing of the test piece.

NOTE: It is known that energy is absorbed other than by the fracturing of the test piece. It is assumed that this energy is absorbed by items such as the test piece supports, the machine foundation and framework, the pendulum and striker, ejection of the broken part of the test piece, and drag of a partially broken test piece. This energy is not determined, as suitable methods and apparatus have not yet been developed for measuring either its total or constituent parts.

SECTION 1. SCOPE, APPLICATION AND DEFINITIONS

1.1 SCOPE. This standard sets out methods for the static calibration of the energy measuring system of machines used for impact tests on metals in accordance with AS 1544, Parts 1, 2 and 3.

The standard deals with complete calibration and with partial calibration.

1.2 APPLICATION. This standard primarily applies to testing machines which indicate in terms of the SI unit of energy, the joule (J).

1.3 DEFINITIONS. For the purpose of this standard, the definitions given in AS 1544, Parts 1, 2 and 3 and the following definitions apply:

1.3.1 Initial potential energy—the energy theoretically available in a pendulum-type impact testing machine when the pendulum is released from its striking position to its initial release position.

1.3.2 Striking energy—the kinetic energy of the pendulum of the testing machine at the instant of impact.

1.3.3 Point of impact—the midpoint of the line of contact between the striking edge and the test piece.

1.3.4 Length of pendulum—the distance from the axis of rotation to the point of impact on a standard test piece.

1.3.5 Striking velocity—the linear velocity of the striking edge at the point of impact at the instant of impact.

1.3.6 Centre of percussion—that point in a pendulum at which a blow, delivered in a tangential direction, will cause no reaction at the centre of rotation.

1.3.7 Calibration—all the operations for the purpose of determining the compliance of the machine with the requirements of this standard.

1.3.8 Calibrating authority—any approved person or organization qualified and equipped to perform the tests set out in Section 2 or Section 3, or both.

NOTE: There are organizations registered with the National Association of Testing Authorities, Australia, for performing calibrations in accordance with this standard.

1.4 SYMBOLS AND DESIGNATIONS. For the purpose of this standard, the following symbols and designations apply:

- E = nominal initial potential energy
- L = length of pendulum
- M = moment of pendulum
- P = distance of centre of percussion from axis of rotation
- g = acceleration due to gravity
- t = time of one complete oscillation
- v = striking velocity