

Australian Standard™

**Elastomeric seals for waterworks
purposes**

**Part 2: Material requirements for
pipe joint seals used in water and
wastewater applications—Specified
by prescriptive formulation**



Standards Australia

This Australian Standard was prepared by Committee WS/10, Flexible Jointing Gaskets. It was approved on behalf of the Council of Standards Australia on 31 March 2000 and published on 28 April 2000.

The following interests are represented on Committee WS/10:

Australasian Plastics and Rubber Institute
Australian Association of Certification Bodies
Australian Chamber of Commerce and Industry
Australian Industry Group
Concrete Pipe Association of Australasia
Master Plumbers Association of Queensland
New Zealand Contractors Federation
Plastics and Chemicals Industries Association
Rubber Manufacturers Association of Australasia
Water Services Association of Australia

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Australia web site at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Australian Standard*, has a full listing of revisions and amendments published each month.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.com.au, or write to the Chief Executive, Standards Australia International Ltd, PO Box 1055, Strathfield, NSW 2135.

Australian Standard™

**Elastomeric seals for waterworks
purposes**

**Part 2: Material requirements for
pipe joint seals used in water and
wastewater applications—Specified
by prescriptive formulation**

Originated as AS A139—1964.
Previous edition AS 1646—1992.
Revised and redesignated in part as AS 1646.2—2000.

COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd
PO Box 1055, Strathfield, NSW 2135, Australia

ISBN 0 7337 3355 7

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee WS/10, Flexible Jointing Gaskets, to supersede, in part, AS 1646—1992, *Elastomeric seals for waterworks purposes*.

This Standard is the result of a consensus among Australia and New Zealand representatives on the Joint Committee to produce it as an Australian Standard.

The objective of this Standard is to set out requirements for a wide range of seals used in the water and wastewater industries including the material requirements for specific applications.

AS 1646 is a suite of Standards that covers elastomeric seals. To date the suite is comprised of the following:

AS

- 1646 Elastomeric seals for waterworks
- 1646.1 Part 1: General requirements
- 1646.2 Part 2: Material requirements for pipe joint seals used in water and wastewater applications—Specified by prescriptive formulation (this Standard)
- 1646.3 Part 3: Material requirements for pipe joint seals used in water and wastewater applications with the exception of natural rubber and polyisoprene compounds

The previous edition of AS 1646 has been retained and amended, and incorporated into Parts 1 and 2, significantly, for its valuable information on natural rubber.

This Standard necessarily deals with existing conditions, but is not intended to discourage innovation or to exclude materials, equipment and methods which may be developed in future. Revisions will be made from time to time in view of such developments and amendments to this edition will be made only when absolutely necessary.

Where possible the suite of Standards (Parts 1 to 3) makes reference to ISO Standards, which have been taken into consideration at the time of preparation of this Standard.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the appendix to which they apply. A 'normative' appendix is an integral mandatory part of a Standard, whereas an 'informative' appendix is only for information and guidance.

CONTENTS

	<i>Page</i>
FOREWORD	4
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE	5
1.2 REFERENCED DOCUMENTS	5
1.3 DEFINITIONS	6
1.4 MARKING	7
SECTION 2 MATERIALS AND COMPOSITION	
2.1 GENERAL	8
2.2 ELASTOMERS	8
2.3 ELASTOMERIC COMPOUNDS	8
2.4 COPPER AND MANGANESE	8
SECTION 3 DETERMINATION OF PROPERTIES OF ELASTOMERIC COMPOUNDS	
3.1 GENERAL	9
3.2 ELASTOMER HARDNESS	9
3.3 TENSILE STRENGTH AND PERCENTAGE ELONGATION AT BREAK	9
3.4 COMPRESSION SET	9
3.5 LOW TEMPERATURE COMPRESSION SET	9
3.6 ACCELERATED AGEING	9
3.7 WATER IMMERSION	9
3.8 OIL RESISTANCE	9
3.9 STRESS RELAXATION IN COMPRESSION	9
3.10 OZONE RESISTANCE	10
SECTION 4 PROPERTIES OF SEALS	
4.1 CONSTRUCTION	11
4.2 SEAL HARDNESS	11
4.3 PURCHASING	11
APPENDICES	
A MEANS FOR DEMONSTRATING COMPLIANCE WITH THIS STANDARD	12
B SEAL HARDNESS TEST	15

FOREWORD

A designer of an installation should, among other duties, evaluate the possible conditions to which the seals will be exposed.

The type of elastomer and its properties should be selected with consideration of several factors including the following:

- (a) The requirements of the regulatory authority within whose jurisdiction the seals are to be used.
- (b) Where appropriate, the effects of the seal on the water conveyed.
- (c) Selection for particular environments, which include the following:
 - (i) Internal—having due regard to liquid conveyed, e.g. sewage at variable depths.
 - (ii) External—
 - (A) below ground, having due regard to—
 - (1) root intrusion;
 - (2) microorganism attack; and
 - (3) temperature after jointing and before covering with fill; and
 - (B) above ground, having due regard to—
 - (1) ultraviolet light;
 - (2) ozone; and
 - (3) temperature.

STANDARDS AUSTRALIA

Australian Standard

Elastomeric seals for waterworks purposes

Part 2: Material requirements for pipe joint seals used in water and wastewater applications—Specified by prescriptive formulation

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE

This Standard specifies requirements for elastomeric seals to be used in pipe line systems that convey water and wastewater at temperatures of less than 50°C. It also specifies composition and formulation requirements for seals.

Means for demonstrating compliance with this Standard are given in Appendix A.

1.2 REFERENCED DOCUMENTS

The following documents are referred to in this Standard

AS

1199	Sampling procedures and tables for inspection by attributes
1646	Elastomeric seals for waterworks purposes
1646.1	Part 1: General requirements
1646.3	Part 3: Material requirements for pipe joint seals used in water and wastewater applications with the exception of natural rubber and polyisoprene compounds
1683	Methods of test for elastomers
1683.11	Method 11: Tension testing of vulcanized rubber
1683.13	Method 13: Compression set of vulcanized rubber under constant deflection
1683.15	Method 15: International rubber hardness (ISO 48)
1683.15.1	Method 15.1: International rubber hardness
1683.15.2	Method 15.2: Durometer hardness
1683.23	Method 23: Rubber—Vulcanized—Determination of resistance to liquids
1683.24	Method 24: Rubber—Vulcanized—Determination of resistance to ozone cracking—Static strain test
1195	Methods for calibration and grading of force-measuring systems of testing machines
2490	Sampling procedures and charts for inspection by variables for percent non-conforming

SAA

HB 18.28 (SANZ 18.28)	Guide 28: General rules for a model third-party certification system for products
--------------------------	---

ASTM

D1278	Standard test methods for rubber from natural sources—Chemical analysis
-------	---