

Australian Standard[®] 1735.3—1986

SAA LIFT CODE

Part 3—PASSENGER AND
GOODS LIFTS—
ELECTROHYDRAULIC



STANDARDS ASSOCIATION OF AUSTRALIA
Incorporated by Royal Charter



This Australian standard was prepared by Committee ME/4, Lift Installations. It was approved on behalf of the Council of the Standards Association of Australia on 12 February 1986 and published on 7 April 1986.

The following interests are represented on Committee ME/4:

Association of Consulting Engineers Australia
Association of Independent Lift Companies
Australian Chamber of Commerce
Australian Uniform Building Regulations Co-ordinating Council
Board of Fire Commissioners of New South Wales
Building Owners and Managers Association of Australia Limited
Confederation of Australian Industry
Department of Employment and Industrial Affairs, Qld
Department of Employment and Industrial Affairs, Vic.
Department of Housing and Construction
Department of Industrial Relations, N.S.W.
Department of Labour, S.A.
Department of Labour and Industry, Tas.
Department of Mines and Energy, N.T.
Department of Occupational Health, Safety and Welfare, W.A.
Department of Public Works, N.S.W.
Department of Territories
Institution of Engineers, Australia
Insurance Council of Australia
Lift Manufacturers Association of Australia Limited
Metal Trades Industry Association of Australia
Royal Australian Institute of Architects

Review of Australian Standards. To keep abreast of progress in industry, Australian standards are subject to periodic review and are kept up-to-date by the issue of amendments or new editions as necessary. It is important therefore that standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all SAA publications will be found in the Catalogue of SAA Publications; this information is supplemented each month by SAA's journal 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn standards.

Suggestions for improvements to Australian standards, addressed to the head office of the Association, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This standard was issued in draft form for comment as DR 84251.

Dup

STANDARDS AUSTRALIA

Amendment No 1

to

AS 1735.3—1986

Lifts, escalators, and moving walks

Part 3: Passenger and goods lifts—Electrohydraulic

REVISED TEXT

The 1986 edition of AS 1735.3 is amended as follows; the amendments should be inserted in the appropriate place.

SUMMARY: This Amendment applies to Contents, Clause 7.4.3.3, Section 26, Clauses 30.1.1 and 30.5, and Appendix A (w).

Published on 14 July 1989.

AMDT
No 1
JULY
1989

Page 4. Contents.

Add the following entry:

APPENDIX A. PERIODIC INSPECTION AND TESTING	26
---	------	------	------	------	----

AMDT
No 1
JULY
1989

Page 13. Clause 7.4.3.3.

Delete existing Clause and substitute:

7.4.3.3 Location. The location and the method of installation of hoses shall not prevent visual inspections.

NOTE: It is acceptable for a hose to require removal, to permit visual inspections.

The locations of hoses and connections shall permit replacement of the hoses and the connections.

Flexible connections shall not be installed between the cylinder and the flow-restriction valve required by Clause 7.5.5.

AMDT
No 1
JULY
1989

Page 23. Section 26.

Delete existing Section and substitute:

SECTION 26. ELECTRICAL INSTALLATION

The electrical installation shall comply with the requirements of Section 26 of AS 1735.2.

The circuit-breaker required by Clause 26.2 of AS 1735.2 shall be provided with a notice on or adjacent to it, bearing the following words:

<p>EXCEPT FOR EMERGENCIES OR SERVICING, DO NOT OPEN THIS SWITCH UNLESS HYDRAULIC LIFT IS AT BOTTOM LANDING</p>

In the ninth line of the fifth paragraph of Clause 26.9 of AS 1735.2, 'main control contactor or contactors' may include the coils of solenoid valves on electrohydraulic lifts.

AMDT
No 1
JULY
1989

Page 30. Clause 30.1.1.

Delete existing Clause and substitute:

30.1.1 Compliance with AS 1735.2. Electrical protective devices shall comply with the following Clauses of AS 1735.2, except where exempted by Clause 30.1.2 herein:

- 30.1 to 30.7
- 30.10
- 30.11
- 30.14 to 30.17.

NOTE: The phase-reversal protection required by Clause 30.20 of AS 1735.2 is not required for electrohydraulic lifts.

AMDT
No 1
JULY
1989

Page 24. Clause 30.5.

Delete existing Clause and substitute:

30.5 DOOR LOCK VALVE TEST SWITCH. A test switch shall be provided which shall enable compliance with the requirements of Clause 7.5.4 for the door lock valve to be tested.

AMDT
No 1
JULY
1989

Page 26. New Appendix A.

Add the following Appendix:

APPENDIX A

PERIODIC INSPECTION AND TESTING

Periodic inspection and testing of every installation should be carried out at intervals of not more than one year.

Regular maintenance of the installation should be performed at more frequent intervals.

Currently in preview, click buy full ver

AUSTRALIAN STANDARD

LIFTS, ESCALATORS, AND MOVING WALKS

Known as the
SAA LIFT CODE

Part 3 PASSENGER AND GOODS LIFTS— ELECTROHYDRAULIC

AS 1735.3—1986

First published (included in AS CA3)	1935
Revised	1947
AS CA3, Part III separately published	1968
AS 1735, Part 3 first published	1975
Second edition	1982
Third edition	1986

PUBLISHED BY THE STANDARDS ASSOCIATION OF AUSTRALIA
STANDARDS HOUSE, 80 ARTHUR ST, NORTH SYDNEY, N.S.W.

ISBN 0 7262 4117 2



PREFACE

This edition of this standard was prepared by the Association's Committee on Lift Installations, to supersede AS 1735, Part 3—1982, Electrohydraulic Lifts: Passenger and Goods.

This edition includes the following technical changes:

- (a) Clause 5.2 has been amended to allow for a reduction of the variations to the SAA Lift Code in the Lift Regulations of Victoria.
- (b) Clause 7.4.1.4 permits the use of flared screwed hydraulic connections on hydraulic lifts.
- (c) Clause 7.4.3.5 and Figs 7.4.3.5(A) and 7.4.3.5(B) have been amended to remove misleading information.
- (d) Clauses 8.1.4 and 8.1.5 allow for the specific clearances needed above cars which are supported by crossheads located at the side of hydraulic lift cars.

Other changes of an editorial nature have been made to bring the standard into line with current SAA policy.

© Copyright — STANDARDS ASSOCIATION OF AUSTRALIA 1986

Users of standards are reminded that copyright subsists in all SAA publications. No part of this publication may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing of the Standards Association of Australia.

CONTENTS

	<i>Page</i>
SECTION 1. SCOPE AND GENERAL	
1.1 Scope	5
1.2 Referenced Documents	5
SECTION 2. SPEED	5
SECTION 3. PRESSURE TEST AFTER ERECTION	6
SECTION 4. BEAMS, SUPPORTS, AND FOUNDATIONS FOR CYLINDERS, MACHINES, AND OVERHEAD SHEAVES	6
SECTION 5. MACHINE ROOMS AND MACHINERY SPACES	
5.1 General	6
5.2 Location Relative to Liftwell	6
SECTION 6. ACCESS TO OVERHEAD SHEAVES	6
SECTION 7. HYDRAULIC DRIVING MACHINES	
7.1 Application	7
7.2 Rams	7
7.3 Cylinders	12
7.4 Hydraulic Lines	12
7.5 Valves	15
7.6 Tanks	15
SECTION 8. CLEARANCES FOR CARS AND COUNTERWEIGHTS	
8.1 Direct-acting Electrohydraulic Lifts	16
8.2 Suspended Electrohydraulic Lifts	17
SECTION 9. BUFFERS AND HOLDING DEVICES	
9.1 Car Buffers	18
9.2 Devices to Hold Car Above Lowest Floor	18
9.3 Counterweight Buffers	18
9.4 Flying Counterweight Buffers	18
SECTION 10. PITS	
10.1 General	19
10.2 Pits Not Extending to Lowest Floor of Building	19
SECTION 11. LIFTWELL ENCLOSURES	19
SECTION 12. LANDING DOORS	
12.1 Provision	20
12.2 General	20
12.3 Closing of Landing Doors	20
SECTION 13. LOCKING OF LANDING DOORS	
13.1 General	20
13.2 Parking of Attendant-controlled Cars	20
SECTION 14. DOOR LOCKS	20
SECTION 15. CLEARANCES IN LIFTWELLS AND ENCLOSURES	
15.1 General	21
15.2 Flushness of Liftwell	21
SECTION 16. PIPING, ETC, IN LIFTWELLS OR MACHINE ROOMS	21

	<i>Page</i>
SECTION 17. SUSPENSION ROPES	21
SECTION 18. ROPE ATTACHMENTS AND FITTINGS	21
SECTION 19. SHEAVES AND PULLEYS	21
SECTION 20. COUNTERWEIGHTS AND FLYING COUNTERWEIGHTS	
20.1 General	22
20.2 Pit Guards	22
20.3 Flying Counterweight Overtravel Limit Switch	22
20.4 Mass of Flying Counterweight	22
SECTION 21. GUIDES FOR LIFT CARS AND COUNTERWEIGHTS	
21.1 General	22
21.2 Stresses and Deflections in Steel Car Guide Rails	22
SECTION 22. RATED CAR CAPACITY AND CLASSES OF LOADING	22
SECTION 23. CAR CONSTRUCTION	
23.1 General	23
23.2 Car Frames for Direct-acting Lifts	23
SECTION 24. CAR DOORS	23
SECTION 25. POWER OPERATION OF CAR AND LANDING DOORS	23
SECTION 26. ELECTRICAL INSTALLATION	23
SECTION 27. EARTHING	
27.1 General	23
27.2 Electrical Apparatus Installed on Cars	23
SECTION 28. PRECAUTIONS IN WIRING	24
SECTION 29. OPERATING DEVICES AND CONTROL EQUIPMENT	24
SECTION 30. ELECTRICAL PROTECTIVE DEVICES	
30.1 General	24
30.2 Top Overtravel Limit Switch	24
30.3 Anti-creep Levelling Device	24
30.4 Normal Limit Switches	24
30.5 Door Lock Valve	24
30.6 Flying Counterweight Overtravel Limit Switch	24
SECTION 31. TERMINAL STOPPING DEVICES	
31.1 General	25
31.2 Normal Limit Switches (Slowing Down and Stopping)	25
31.3 Top Overtravel Limit Switches	25
31.4 Anti-creep Levelling Device	25
31.5 Flying Counterweight Bottom Overtravel Limit Switch	25
SECTION 32. INDICATORS, ANNUNCIATORS, ALARMS, TELEPHONES, ETC.	26
SECTION 33. CAR AND COUNTERWEIGHT SAFETY GEAR	26
SECTION 34. SPEED GOVERNORS	26
Appendix A > SEE AMENDMENT (1)	
INDEX	27

STANDARDS ASSOCIATION OF AUSTRALIA

Australian Standard

for

LIFTS, ESCALATORS, AND MOVING WALKS

PART 3—PASSENGER AND GOODS LIFTS—ELECTROHYDRAULIC

SECTION 1. SCOPE AND GENERAL

1.1 SCOPE. This standard sets out requirements for electrohydraulic lifts for carrying passengers and goods.

This standard is complementary to AS 1735.1 and AS 1735.2, but the requirements of this standard take precedence over corresponding requirements of those standards.

1.2 REFERENCED DOCUMENTS. The following standards are referred to in this standard:

AS 1074	Steel Tubes and Tubulars Threaded or Suitable for Threading with Pipe Threads of Whitworth Form	AS 1735.10	SAA Lift Code, Part 10—Testing
AS 1250	SAA Steel Structures Code	AS 1835	Tubes for Pressure Purposes—Seamless Steel
AS 1392	Precast Concrete Pressure Pipes	AS 1836	Tubes for Pressure Purposes—Welded Steel
AS 1711	Asbestos Cement Pressure Pipes	AS 2129	Flanges for Pipes, Valves and Fittings
AS 1722	Pipe Threads of Whitworth Form Part 1—Sealing Pipe Threads	AS 2544	Grey Iron Pressure Pipes and Fittings
AS 1735.1	SAA Lift Code, Part 1—General Requirements	AS B226	Hydraulic Hose
AS 1735.2	SAA Lift Code, Part 2—Passenger and Goods Lifts—Electric	AS CB15	SAA Fusion Welding Code
		BS 1600	Dimensions of Steel Pipe for the Petroleum Industry
		BS 1640	Wrought and Cast Austenitic Chromium-nickel Steel Fittings
		BS 1740	Wrought Steel Pipe Fittings (Screwed BSP Thread) Part 1—Metric Units
		ANSI/ASME B1.20.1	Pipe Threads, General Purpose (Inch)
		ANSI/ASME B36.10	Welded and Seamless Wrought Steel Pipe
		SAE J516 JUN 84	Hydraulic Hose Fittings.

SECTION 2. SPEED

The rated speed of an electrohydraulic lift (see Clause 2.120 of AS 1735.1) shall be not more than 1 m/s.

The speed in the down direction, under full load conditions, shall not exceed the relevant maximum value given in Table 2.1, subject to a maximum of 1.4 m/s.

TABLE 2.1
MAXIMUM SPEED IN DOWN DIRECTION

Type of lift	percent of rated speed	
	Maximum speed in down direction	
	Where rated speed ≤ 0.5 m/s	Where rated speed > 0.5 m/s ≤ 1 m/s
Passenger	150	140
Passenger and goods	150	140
Goods	160	150*

* Subject to a maximum of 1.4 m/s.