

**AUSTRALIAN STANDARD**

**ROAD SIGNS  
SPECIFICATIONS**

**STANDARDS AUSTRALIA**



currently in preview, click buy full version

incomplete copy

Currently in preview, click buy full version

AS 1743-1989

**ROAD SIGNS  
SPECIFICATIONS**

Currently in preview, click buy full version

## STANDARDS AUSTRALIA

---

 AMENDMENT No 1  
 to  
 AS 1743—1989  
 ROAD SIGNS—SPECIFICATIONS
 

---

## CORRECTION

The 1989 edition of AS 1743 is amended as follows; the amendment(s) should be inserted in the appropriate place.

*SUMMARY:* This Amendment applies to Sign W5-22.

Published on 1 March 1989.

---

AMDT  
No 1  
MAR.  
1989

**Page 98. Sign W5-22.**

Delete the table of dimensions and *substitute:*

	a	b	c	d	e	f	g	h <sub>1</sub>	r
W5-22A	600	8	16	226	118	254	266	40	40
W5-22B	750	10	20	283	148	318	333	50	50
W5-22C	900	12	24	339	177	381	399	60	60

---

*Amdt 1. 1989-03-01*

Australian Standard®

---

**Road signs—Specifications**

---



**STANDARDS AUSTRALIA** 

This Australian Standard was prepared by Committee MS/12, Road Signs and Traffic Signals. It was approved on behalf of the Council of Standards Australia on 17 October 1988 and published on 23 January 1989.

---

The following interests are represented on Committee MS/12:

Australian Automobile Association  
Australian Council of Local Government Associations  
Australian Road Research Board  
Confederation of Australian Industry  
Department of Transport and Communications  
Department of Arts, Sport, the Environment, Tourism and Territories  
Local Government Engineers Association of Victoria  
Main Roads Department, Queensland  
National Association of Australian State Road Authorities  
Railways of Australia Committee  
Road Traffic Authority, Victoria  
Road Traffic Board, South Australia  
Transport Commission, Tasmania

---

**Review of Australian Standards.** To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up-to-date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

Australian Standard®

---

**Road signs—Specifications**

---

First published as AS E36—1960.  
Revised and redesignated AS 1743—1975.  
Second edition 1989.

PUBLISHED BY STANDARDS AUSTRALIA  
(STANDARDS ASSOCIATION OF AUSTRALIA)  
STANDARDS HOUSE, 80 ARTHUR ST, NORTH SYDNEY, NSW

ISBN 0 7262 5291 3

## PREFACE

This Standard was prepared by the Standards Australia Committee on Road Signs and Traffic Signals to supersede AS 1743—1975 which was prepared by the Australian Committee on Road Devices (ACORD), endorsed by the Australian Transport Advisory Council and approved by the Council of Standards Australia for publication as an Australian Standard.

This Standard is complementary to and should be read in conjunction with AS 1742 *Manual of uniform traffic control devices*. The purpose of this Standard is to establish uniformity in the layout and standards of manufacture of road signs provided for in AS 1742.

The introduction of CAD/CAM and photographic methods into the design and manufacture of road signs in recent years has resulted in certain new practices which are now recognized in this Standard. Oversize versions of many standard signs (other than T series signs, see below) are now most commonly manufactured by photographic enlargement of the basic size sign. Tabulations of sign dimensions in this Standard, therefore, now show all oversize versions for such signs as having all dimensions in exact proportion to the basic sign. The use of these methods can also result in letter and numeral heights which do not conform with the standard sizes given in AS 1744 *Forms of letters and numerals for road signs*. These intermediate sizes are now also permitted in this Standard.

Provision is also made in this Standard for the use of computer generated letter series intermediate to the standard series. This facility will be of particular use in the manufacture of certain direction signs, especially street name signs.

Other changes to the Standard include amplification of materials and manufacturing standards, such as the introduction of numerical values for manufacturing tolerances, together with a number of new requirements for sign layout design.

Changes have also been made to specific signs or specific categories of sign. These have largely been caused by the revision of AS 1742 and include the following:

- (a) Some text signs in the regulatory and warning signs have been replaced with symbol signs. The use of symbols has increased the effectiveness of these signs as the symbols are legible and understood at a greater distance from the hazard or decision-making point than the text they replace. All new symbols included in this Standard have been successfully tested in accordance with AS 2342.3 *The design and use of graphic symbols and public information symbol signs, Part 3, Test procedures for evaluating graphic symbols and symbol signs* by the Australian Road Research Board.
- (b) Many T series signs have been altered, added or deleted as a result of the new roadworks signing philosophy adopted in developing AS 1742.3 *Traffic control devices for work on roads*, i.e. more emphasis given to roadworks delineation and less to worded messages which merely labelled activities. All of the yellow T series signs now have a black border which increases conspicuity when the signs are mounted against light backgrounds. Redesign of letter sizes and font series to better accommodate the legends within the black borders has also been necessary.
- (c) Fluorescent red or fluorescent orange has been specified for use on T series signs where higher conspicuity is required in daylight, e.g. to warn of works near road. These colours were formerly referred to as fluorescent red/orange and fluorescent yellow/orange. Red has been retained for specific hazard warning, e.g. blasting.

It has not been possible to adopt exact proportioning for most oversize versions of T series signs. This is because, for economic reasons, it was decided to standardize on a limited range of signboard sizes.

It should also be noted that contrary to the advice given in Amendment No 4 to AS 1743—1975, issued December 1985, artwork in bromide form for legends for T series signs is not available from Standards Australia any longer.

Road Authorities will adopt their own timetables for introduction of new designs but the committee believes that all signs should be constructed to the new designs by the 31st December, 1990.

The committee recognized that manufacturers would require a transition period to enable them to clear stock and to make signs to the new designs. However, where symbol signs replace text signs, it is recommended that these be introduced as soon as possible.

## CONTENTS

	<i>Page</i>
1 SCOPE .....	4
2 REFERENCED DOCUMENTS .....	4
3 NUMBERING SYSTEMS .....	4
4 DIMENSIONS .....	4
5 LEGEND .....	5
6 LAYOUT .....	5
7 BORDERS, EDGE STRIPS AND CORNERS .....	5
8 COLOURS .....	6
9 SIGNBOARD CONSTRUCTION .....	6
10 APPLICATION OF SIGN FACES .....	7
 APPENDICES	
A LAYOUT OF ADVANCE DIRECTION SIGNS .....	8
B DESIGN AND LAYOUT OF SYMBOLIC SERVICE SIGNS .....	10
C RETROREFLECTIVE COLOURS .....	13
D FLUORESCENT COLOURS .....	15
 DRAWINGS OF STANDARD ROAD SIGNS	
REGULATORY SIGNS (R) .....	17
WARNING SIGNS (W) .....	65
GUIDE SIGNS (G AND GE) .....	129
TEMPORARY SIGNS (T) .....	205
HAZARD MARKERS (D) .....	239

## © Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the copyright law allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the Head Office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

## STANDARDS AUSTRALIA

**Australian Standard**  
**ROAD SIGNS—SPECIFICATIONS**

**1 SCOPE.** This Standard specifies the design and construction requirements for standard road signs provided for in AS 1742.1.

NOTE: Authorities responsible for the erection of signs are not encouraged to develop signs for their own use. However, there will be instances where no suitable standard sign exists. In such cases, the relevant State Road Authority should be contacted to determine whether such a sign is already in use. If a new sign is to be developed, it should comply with the design requirements specified in this Standard for the particular sign classification. If it is considered that the sign could also be required by other authorities, Standards Australia should be advised so that, during the course of its regular review of road signs, it can take all new developments into account with a view to their possible inclusion in the relevant Standards in due course. It is most important that the proliferation of signs with differing designs of legend, symbol, etc, essentially for the same purpose, is minimized.

**2 REFERENCED DOCUMENTS.** The documents below are referred to in this Standard.

AS	
1397	Steel sheet and strip—Hot-dipped zinc-coated or aluminium/zinc-coated
1562	Design and installation of metal roofing
1580	Methods of test for paints and related materials
1734	Aluminium and aluminium alloys—Flat sheet, coiled sheet and plate
1742	Manual of uniform traffic control devices
1742.1	Part 1: General introduction and index
1742.2	Part 2: Traffic control devices for general use
1742.3	Part 3: Traffic control devices for works on roads
1744	Forms of letters and numerals for road signs (known as standard alphabets for road signs)
1906	Retroreflective materials and devices for road traffic control purposes
1906.1	Part 1: Retroreflective materials
2342	The design and use of graphic symbols and public information signs
2342.3	Part 3: Test procedures for evaluating graphic symbols and symbol signs
2300	Colour standards for general purposes

### 3 NUMBERING SYSTEMS.

**3.1 General.** Two numbering systems are used in this Standard; one for identifying individual signs and the other for identifying individual symbols and route marker emblems which are used as components within a sign.

These systems are set out in Clauses 3.2 and 3.3.

**3.2 Signs.** The numbering system for signs is as follows:

(a) A letter prefix, as shown below, denoting class of sign—

- R —Regulatory Signs
- W —Warning Signs
- G —Guide Signs
- GE —Freeway Guide Signs
- T —Temporary Signs
- D —Hazard Markers

(b) A number denoting the series or group of signs.

(c) Number(s) identifying the sign in the series, or group.

NOTE: Where variations of some types of sign occur, they are identified by an additional number.

(d) A letter denoting the size of the sign, e.g. A, B, C, D, etc, where A is the smallest sign.

(e) The letter (L) or (R), when the sign has directional significance.

EXAMPLE: R2-6A(L) or (R) denotes a regulatory sign in the Direction Series—R2. The sign in the series, is the smallest available, and has directional significance.

**3.3 Route marker emblems and symbols.** The numbering system for route marker emblems and symbols is given below.

**3.3.1 Route marker emblems.** Route marker emblems are numbered as follows:

(a) A letter prefix, as shown below, used to identify an individual type of route marker—

- NH —National Highway Marker Emblems
- NR —National Route Marker Emblems
- NR(A)—Alternative National Route Marker Emblems
- SR —State Route Marker Emblems
- TR —Tourist Route Marker Emblems

(b) A number in brackets immediately following the prefix e.g. (2) or (3), indicating the number of numerals in the route number.

(c) A number, following a dash, indicating the size of an emblem e.g. - 1 - 2 - 3, where 1 is the smallest emblem.

**3.3.2 Symbols.** Symbols are identified by the letter prefix S followed immediately by a number which indicates the particular symbol.

### 4 DIMENSIONS.

**4.1 General.** The following signs shall conform to the relevant drawing given in this Standard:

- (a) Those which have a unique legend and standardized layout and size range, e.g. R1-1 and W1-1.
- (b) Those which comply with (a) above but have a variable element, e.g. a variable numerical value or arrow, which does not affect the size or layout (see R2-14).