

Australian Standard[®]

**HELICAL LOCK-SEAM
CORRUGATED STEEL PIPES —
DESIGN AND INSTALLATION**

This Australian standard was prepared by Committee WS/11, Corrugated Metal Drainage Pipes and Arches. It was approved on behalf of the Council of the Standards Association of Australia on 7 September 1984 and published on 7 December 1984.

The following interests are represented on Committee WS/11:

Confederation of Australian Industry
Department of Public Works, New South Wales
Metal Trades Industry Association of Australia
National Association of Australian State Road Authorities
Public Works Department, Victoria
Railways of Australia Committee
University of Adelaide
University of New South Wales

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcome. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

Australian Standard[®]

**HELICAL LOCK-SEAM
CORRUGATED STEEL PIPES —
DESIGN AND INSTALLATION**

First published	1979
Second edition	1984

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 3541 5

PREFACE

This edition of this standard was prepared by the Association's Committee on Corrugated Metal Drainage Pipes and Arches to supersede AS 1762—1979, Code for Design and Installation of Helical Lock-seam Corrugated Steel Pipes.

The principal purpose of the standard is to lay down the essential requirements for the installation of helical lock-seam corrugated steel pipes manufactured in accordance with AS 1761, Helical Lock-seam Corrugated Steel Pipes, as distinct from riveted, nestable and bolted corrugated steel structures manufactured in accordance with AS 2041, Corrugated Steel Pipes, Pipe-arches and Arches.

This edition differs from the previous edition as follows:

- (a) The ultimate ring compression strength (F_c) in Fig. 2.3 is increased to 250 MPa.
- (b) The equations for stresses in Clause 2.5 are amended.
- (c) For handling stiffness (F_F), in Clause 2.7, the pipe diameter is increased to 3600 mm.
- (d) The values of the section properties of corrugated steel sheet (Table 2.4) and corrugations for helical lock-seam pipe are changed.
- (e) Consequential changes as a result of (a) above are made in Appendix A.
- (f) Appendices B and C are amended.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

	<i>Page</i>
SECTION 1. SCOPE AND GENERAL	
1.1 Scope	4
1.2 Referenced Documents	4
1.3 Definitions	4
1.4 Notation	4
1.5 Materials	4
SECTION 2. INSTALLATION DESIGN	
2.1 General	5
2.2 Design Soil Compaction	5
2.3 Design Pressure	5
2.4 Ring Compression	5
2.5 Stresses	6
2.6 Thickness	6
2.7 Handling Stiffness	6
2.8 Minimum Cover	6
2.9 End Treatment	6
SECTION 3. INSTALLATION	
3.1 Application	10
3.2 Assembly	10
3.3 Multiple Installations — Minimum Permissible Spacing	10
3.4 Installation of Pipes	10
3.5 Corrosion of Corrugated Steel Structures	12
APPENDICES	
A Reference Tables Based on Railway Loading (M250) and Highway Loading (T44-A14)	13
B Roadway M250 Load — Live Load Plus Impact Pressure on the Structure	16
C Highway T44-A14 Load — Live Load Plus Impact Pressure on the Structure	17
D Corrosion of Corrugated Steel Structures	18

STANDARDS ASSOCIATION OF AUSTRALIA

Australian Standard
for
HELICAL LOCK-SEAM CORRUGATED STEEL PIPES — DESIGN AND INSTALLATION

SECTION 1. SCOPE AND GENERAL

1.1 SCOPE. This standard sets out requirements for the design and installation of structures of helical lock-seam corrugated steel pipes.

1.2 REFERENCED DOCUMENTS. The following standards are referred to in this standard:

AS 1289 Methods of Testing Soils for Engineering Purposes

1289.E1.1 — Part E — Soil Compaction and Density Tests — Determination of the Dry Density/Moisture Content Relation of a Soil Using Standard Compaction — Standard Method

1289.E1.2 — Part E — Soil Compaction and Density Tests — Determination of the Dry Density/Moisture Content Relation of a Soil Using Standard Compaction — Subsidiary Method

AS 1761 Helical Lock-seam Corrugated Steel Pipes.

1.3 DEFINITIONS. For the purpose of this standard the following definition applies:

Cover — the vertical distance between the top of the structure and —

- (a) pavement surface of road;
- (b) top of rails;
- (c) top of fill where (a) and (b) are not applicable.

1.4 NOTATION. The notation used in this standard shall have the following meaning with respect to the structure or member or component to which a clause is applied:

A = area of corrugated steel section per unit length, in square millimetres per millimetre

C = ring compression, in kilonewtons per metre

E = modulus of elasticity for steel, taken as 205×10^3 MPa

F_a = allowable compressive strength, in megapascals

F_c = ultimate compressive wall strength, in megapascals

F_Y = minimum yield strength, in megapascals

F_F = flexibility value, in millimetres per newton

H = height of cover, in metres

I_c = second moment of area of the corrugated section per unit length, in millimetres to the fourth power per millimetre

K_f = load factor (see Clause 2.3)

P_{DL} = dead load pressure, in kilopascals

P_{LL} = live load pressure, in kilopascals

P_V = design pressure, in kilopascals

r = radius of gyration of corrugated steel section, in millimetres

S_s = internal diameter of pipe, in millimetres

t = thickness, in millimetres

w = unit load of fill, in kilonewtons per cubic metre

Z = section modulus of corrugated steel section, in millimetres cubed per millimetre

1.5 MATERIALS. Helical lock-seam corrugated steel pipes shall comply with AS 1761.