

Australian Standard[®]

**SEMICONDUCTOR
CONVERTORS**

**Part 3 — SEMICONDUCTOR
DIRECT D.C.
CONVERTORS
(D.C. CHOPPER
CONVERTORS)**

This Australian standard was prepared by Committee EL/27, Power Electronics. It was approved on behalf of the Council of the Standards Association of Australia on 16 June 1983 and published on 8 August 1983.

The following interests are represented on Committee EL/27:

Australian Electrical and Electronic Manufacturers Association

Bureau of Steel Manufacturers of Australia

Confederation of Australian Industry

Department of Defence

Electricity Supply Association of Australia

Monash University

Railways of Australia Committee

Telecom Australia

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

Australian Standard[®]

**SEMICONDUCTOR
CONVERTORS**

**Part 3 — SEMICONDUCTOR
DIRECT D.C.
CONVERTORS
(D.C. CHOPPER
CONVERTORS)**

First published 1983

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 3075 8

PREFACE

This standard was prepared by the Association's Committee on Power Electronics. It is based on IEC 146-3, Semiconductor Convertors, and acknowledgment is made of the assistance received from this source.

IEC 146-3 was examined in terms of Australian practice and amended where necessary. In the main the amendments consist of editorial changes not involving a change in the basic sense of the statement concerned, e.g. renumbering of clauses and some re-arrangement to ensure conformity with the style of Australian standards.

Technical changes are minor, being consistent with the need to comply with other Australian standards which are called up by reference. In general the standard is technically similar with IEC 146-3.

CONTENTS

	<i>Page</i>
1 SCOPE	3
2 APPLICATION	3
3 REFERENCED DOCUMENTS	3
4 DEFINITIONS	3
4.1 General	3
4.2 Basic definitions	3
4.3 Multiple direct d.c. convertor	3
4.4 Characteristics related to convertors	4
4.5 Characteristics related to direct d.c. convertors	4
5 SERVICE CONDITIONS	5
5.1 Normal service conditions	5
5.2 Unusual service conditions to be identified by purchaser	5
5.3 Performance requirements to be stipulated by purchaser	6
6 RATED VALUES	7
6.1 Rated values for direct d.c. convertors	7
6.2 Load duty identification	7
6.3 Rated input direct voltage value for battery sources	7
7 TESTS	7
7.1 Tests to be performed	7
7.2 Preliminary light-load test	8
7.3 Checking of auxiliary devices	9
7.4 Rated continuous output current	9
7.5 Temperature rise	9
7.6 Frequency variation	9
7.7 Rated continuous load/light-load tests	9
7.8 Audible noise	10
7.9 Supply overvoltage and transient energy test	10
7.10 Short-circuit current	10
7.11 Long-time current	10
7.12 Restart	10
7.13 Mechanical	10

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows, and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

STANDARDS ASSOCIATION OF AUSTRALIA

Australian Standard
for
SEMICONDUCTOR CONVERTORS

PART 3—SEMICONDUCTOR DIRECT D.C. CONVERTORS
(D.C. CHOPPER CONVERTORS)

1 SCOPE. This standard specifies requirements for semi-conductor direct d.c. convertors (d.c. chopper convertors) with regard to rated values, testing and performance characteristics.

2 APPLICATION. These requirements apply to all types of semiconductor direct d.c. convertors, i.e. d.c. to d.c. convertors without an a.c. link. The requirements of AS 1955, Parts 1 and 2, shall also apply to semiconductor direct d.c. convertors in so far as they are not in contradiction to the requirements herein.

For some special applications, e.g. electric traction equipment, additional requirements may apply.

NOTE: This standard may also be used for certain d.c. switches in control applications, if applicable.

3 REFERENCED DOCUMENTS. The following standards are referred to in this standard:

AS 1852	International Electrotechnical Vocabulary 1852(05) — 1970 Fundamental Definitions 1852(11) — 1970 Static Convertors
AS 1955	Semiconductor Convertors Part 1 — General Part 2 — Semiconductor Self-commutated Convertors
AS 2064	Limits of Electromagnetic Interference Generated by Industrial, Scientific, Medical and Similar Radio-frequency Equipment

4 DEFINITIONS.

4.1 General. For the purpose of this standard the definitions given in Clauses 4.2, 4.3 and 4.4 apply.

NOTE: Some of the following definitions have been taken from or are equivalent to, definitions contained in AS 1852, or are being considered by IEC for inclusion in IEC 50 (AS 1852). A number have been expanded with notes or have been reformulated in order to cover the subject dealt with in this standard more precisely. Definitions pertaining to d.c. convertors have been added.

In the present definitions, adjectives which are implicit by virtue of the subject of this standard are often omitted for brevity and clarity, e.g. semiconductor, electronic, etc.

4.2 Basic Definitions.

4.2.1 Converter—an operative unit for electronic power conversion comprising one or more electronic valve devices, essential switching devices and filters if necessary, and other auxiliaries, if any.

NOTE: The word valve is used throughout this standard in its generally accepted electronic sense which includes semiconductor valves.

4.2.2 Self-commutated converter—a converter in which the commutating voltages are supplied by components within the converter.

NOTE: Examples include convertors in which the commutating voltages are built up within the semiconductor devices (as in transistors and thyristors which can be turned on by the gate) or in which they are supplied outside the semiconductor devices by means of capacitors.

Excluded are convertors requiring special characteristics from the load to commutate.

4.2.3 Direct d.c. converter—a self-commutated converter for conversion from a.c. to d.c. without an a.c. link.

4.2.4 Non-reversible direct d.c. converter—a direct d.c. converter in which the direction of the power flow is in only one direction.

4.2.5 Reversible direct d.c. converter—a direct d.c. converter in which the direction of the power flow is reversible.

4.2.6 Assembly (valve device)—electrically and mechanically combined assembly of valve device stacks, complete with all its connections and auxiliaries in its own mechanical structure.

4.2.7 Transfer factor—the ratio of the voltage on the load side to the voltage on the input side, both voltages being measured in arithmetic mean values.

NOTES:

1. The transfer factor may be modified by variation of the conducting interval of the principal arm or by variation of the elementary frequency.
2. Where the transfer factor is larger than one, the converter may be called a step-up direct d.c. converter. Where less than one the converter may be called a step-down direct d.c. converter.

4.3 Multiple Direct D.C. Converter.

4.3.1 General A multiple direct d.c. converter is a combination of more than one direct d.c. converter related in such a manner that they may not be considered as independent.

NOTE: Combinations of direct d.c. convertors may be divided into—

- (a) those being supplied by a common source;
- (b) those being supplied by a common source and supplying a common load;
- (c) those supplying a common load.

Such combinations are multiple direct d.c. convertors if, for example, they are characterized by control system relationship as being—

- (i) operated at the same frequency;
- (ii) phase-related;
- (iii) frequency-related;
- (iv) voltage-related;
- (v) current-related.