

AS 2024—1991

Australian Standard[®]

**High voltage a.c. switchgear and
controlgear—Switch—fuse
combinations**

This Australian Standard was prepared by Committee EL/7, Power Switchgear. It was approved on behalf of the Council of Standards Australia on 20 August 1990 and published on 28 March 1991.

The following interests are represented on Committee EL/7:

Australian–British Chamber of Commerce
Australian Electrical and Electronic Manufacturers Association
Confederation of Australian Industry
Electricity Supply Association of Australia
Institution of Engineers, Australia
Railways of Australia Committee
Testing Authorities
The Workcover Authority, New South Wales

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications. This information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

AS 2024—1991

Australian Standard[®]

**High voltage a.c. switchgear and
controlgear—Switch—fuse
combinations**

First published as AS 2024—1977.
Second edition 1991.

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 6534 9

PREFACE

This Standard was prepared by the Standards Australia Committee on Power Switchgear to supersede AS 2024-1977, *High voltage fuse/switch combinations and fuse/circuit-breaker combinations*.

This Standard covers only switch-fuse combinations in which fuse strikers cause the switch to open when a fuse operates.

It does not cover fuse circuit-breaker combinations.

This Standard is based on IEC document 17A(Central Office)209, Draft-Revision of IEC Publication 420: *High-voltage alternating current switch-fuse combinations*, but incorporates significant editorial and technical amendments including the specification of much higher prospective TRV for Test Duties 4 and 5 and the deletion of restrictions on the selection of fuse-links in the IEC Standard to enable the interruption of transformer currents due to a short-circuit on the secondary.

Where this Standard deviates technically from IEC document 17A (Central Office)209 by way of different or additional requirements a rule is drawn in the margin against the clause or table, or part thereof, affected. These deviations are summarized in Appendix C.

It is intended to be read in conjunction with AS 2650, *High voltage A.C. switchgear and controlgear - Common requirements*, and the clause numbering herein follows that of AS 2650.

This Standard makes reference to the application guide in IEC 282-1 and to IEC 787. However, after publication, reference should be made instead to AS 1033.3, *High voltage fuses (for rated voltages exceeding 1000 V) Part 3: Application guide*.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

	<i>Page</i>
1 SCOPE AND GENERAL	4
2 SERVICE CONDITIONS	5
3 DEFINITIONS	5
4 RATINGS	6
5 DESIGN AND CONSTRUCTION	9
6 TYPE TESTS	10
7 ROUTINE TESTS	22
8 GUIDE TO SELECTION OF SWITCH-FUSE COMBINATIONS FOR SERVICE	22
9 INFORMATION TO BE GIVEN WITH ENQUIRIES, TENDERS, AND ORDERS	25
10 TRANSPORT, STORAGE, ERECTION AND MAINTENANCE	25
APPENDICES	
A EXAMPLE OF THE COORDINATION OF FUSES, SWITCH AND TRANSFORMER	27
B JUSTIFICATION OF THE PROCEDURE FOR DETERMINING TRANSFER CURRENT AND OF PARAMETERS ASSOCIATED WITH TEST DUTY 4	29
C SUMMARY OF TECHNICAL DIFFERENCES BETWEEN THIS STANDARD AND IEC DOCUMENT 17A(CENTRAL OFFICE)209	31

STANDARDS AUSTRALIA

Australian Standard

High voltage a.c. switchgear and controlgear—Switch-fuse combinations

1 SCOPE AND GENERAL

1.1 Scope This Standard specifies requirements for three-pole switch-fuse combinations having rated voltages above 1 kV and up to but not including 52 kV, for use on 50 Hz three-phase a.c. systems.

It covers functional assemblies of switches or switch-disconnectors complying with AS 1025.1 in combination with current-limiting fuses complying with AS 1033.2, with strikers, which together are able to interrupt currents up to the rated short-circuit breaking current of the switch-fuse combination as follows:

- (a) The fuses extend the short-circuit rating of the combination beyond that of the switch alone. The fuse strikers cause all poles of the switch to open when a fuse element melts.
- (b) The switch of a switch-fuse combination may, in addition to the fuse strikers, be operated by either an overcurrent release or a shunt release.

This Standard covers combinations forming part of ring main units.

This Standard does not cover switch-fuse units with dependent manual operation, fuse-circuit-breakers, switch-fuse units specially designed for motor circuit applications, e.g. with special overload requirements, switch-fuse units for switching capacitor banks, or combinations of a switch and fuses in which all poles of the switch are not caused to open by the operation of a fuse striker.

NOTES:

1. Switch-fuse combinations are subsequently referred to as 'combinations' in this Standard.
2. The term 'fuse' used in this Standard may designate either a fuse or a fuse-link where it does not result in ambiguity in the meaning of text.
3. Switches in combinations need not comply with the short-circuit making requirements of AS 1025.1 for compliance with this Standard when the current limiting effects of the fuse-links are taken into account.
4. Earthing switches complying with AS 1306 may, in addition, form part of a combination. However if the earthing switch is required to have a short-circuit making current, its rated making current needs to be verified by test in accordance with AS 1025.1.

1.2 Application This Standard has to be read in conjunction with AS 2650. Its clauses are aligned with the clause numbers and headings in AS 2650 and the application of the specific requirements of AS 2650 is stated throughout this Standard.

1.3 Referenced documents The following documents are referred to in this Standard:

AS	
1025	High voltage a.c. switchgear and controlgear—Switches and switch-disconnectors
1025.1	Part 1: For rated voltages above 1 kV and less than 52 kV
1033	High voltage fuses (for rated voltages exceeding 1000 V)
1033.1	Part 1: Expulsion type
1033.2	Part 2: Current-limiting (powder-filled) type
1265	Bushings for alternating voltages above 1000 V
1306	High voltage a.c. switchgear and controlgear—Disconnectors (isolators) and earthing switches
1852	International electrotechnical vocabulary
1852(441)	Switchgear, controlgear and fuses
2006	High voltage a.c. switchgear and controlgear—Circuit-breakers for rated voltages above 1000 V
2086	High voltage a.c. switchgear and controlgear—Metal-enclosed—Rated voltages above 1 kV up to and including 72.5 kV
2261	High voltage a.c. switchgear and controlgear—Insulation-enclosed for rated voltages above 1 kV up to and including 36 kV
2650	High voltage a.c. switchgear and controlgear—Common requirements
2712	Preferred numbers and their use
IEC	
282	High voltage fuses
282-1	Part 1: Current limiting fuses
787	Application guide for the selection of fuse-links of high-voltage fuses for transformer applications