



Traffic signal lanterns



This Australian Standard® was prepared by Committee LG-006, Road Traffic Signals. It was approved on behalf of the Council of Standards Australia on 30 September 2014. This Standard was published on 21 October 2014.

The following are represented on Committee LG-006:

- Australian Industry Group
 - AUSTRROADS
 - Brisbane City Council
 - CIE Australia
 - Department of Planning, Transport and Infrastructure, SA
 - Department of Transport and Main Roads, Qld
 - IES: The Lighting Society
 - Intelligent Transport Systems Australia
 - Lighting Council of Australia
 - Main Roads Western Australia
 - Roads and Maritime Services
 - VicRoads
-

This Standard was issued in draft form for comment as SRA 2144.

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Standard through their representation on the Committee and through the public comment period.

Keeping Standards up-to-date

Australian Standards are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting www.standards.org.au

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

Australian Standard[®]

Traffic signal lanterns

Original as AS E32—1947.
Previous edition AS/NZS 2144:2002.
Revised and designated as AS 2144:2014.

COPYRIGHT

© Standards Australia Limited

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968.

Published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001, Australia

ISBN 978 1 74342 860 3

PREFACE

This Standard was prepared by Standards Australia Committee LG-006, Road Traffic Signals, to supersede AS/NZS 2144:2002. It is one of a number of Standards which set out requirements for the equipment associated with traffic signal installations. These include the following:

AS

2144	Traffic signal lanterns (this Standard)
2339	Traffic signal posts and attachments
2353	Pedestrian push-button assemblies
2578	Traffic signal controllers
2703	Vehicle loop detector sensors
2979	Traffic signal mast arms
4113	Traffic signal lamps
4113.1	Part 1: Lamps for 240 V a.c. operation
4113.2	Part 2: Lamps for a.c. operation at extra-low voltage
4191	Portable traffic signal systems
4192	Illuminated flashing arrow signs
4852	Variable message signs
4852.1	Part 1: Fixed signs
4852.2	Part 2: Portable signs
5156	Electronic speed limit signs

The objective of this Standard is to ensure that, with the exception of replaceable items such as LED arrays, lanterns will continue to function effectively for a period of at least 20 years; furthermore, that surface finishes applied to the exterior of lanterns (e.g. powder coatings, paint) will last for at least 10 years without the need for further treatment.

The major changes that have been introduced in this edition are due to the changes that have occurred in technology since the previous (2002) edition. The principal differences between this and the previous edition are as follows:

- (a) Incandescent lamps are no longer covered by this Standard as they are considered obsolescent.
- (b) Requirements for lanterns operating at extra-low voltage (ELV) have been added.
- (c) Environmental tests are now required and a clause defining them has been added.

Statements expressed in mandatory terms in footnotes to figures are deemed to be requirements of this Standard.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the appendix to which they apply. A normative appendix is an integral part of a Standard, whereas an informative appendix is only for information and guidance.

CONTENTS

	<i>Page</i>
FOREWORD.....	5
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE.....	6
1.2 REFERENCED DOCUMENTS.....	6
1.3 DEFINITIONS.....	7
1.4 MARKING	9
SECTION 2 SIGNAL COLOURS AND DISPLAYS	
2.1 SIGNAL COLOURS	10
2.2 SIGNAL DISPLAYS	10
SECTION 3 PHOTOMETRIC PERFORMANCE	
3.1 GENERAL.....	12
3.2 APPEARANCE OF VEHICULAR ASPECTS WITH A CIRCULAR DISPLAY.....	12
3.3 LUMINOUS INTENSITY DISTRIBUTION OF VEHICULAR ASPECTS WITH A CIRCULAR DISPLAY.....	12
3.4 APPEARANCE OF VEHICULAR ASPECTS THAT DISPLAY SYMBOLS	16
3.5 LUMINANCE DISTRIBUTION OF VEHICULAR ASPECTS THAT DISPLAY SYMBOLS	17
3.6 APPEARANCE OF PEDESTRIAN AND BICYCLE ASPECTS THAT DISPLAY SYMBOLS	18
3.7 LUMINANCE DISTRIBUTION OF PEDESTRIAN AND BICYCLE ASPECTS THAT DISPLAY SYMBOLS.....	18
3.8 VEILING REFLECTIONS	19
3.9 SUN-PHANTOM.....	20
SECTION 4 MECHANICAL AND PHYSICAL FEATURES AND PROPERTIES	
4.1 GENERAL ARRANGEMENT.....	21
4.2 MASS OF LANTERN ASPECTS.....	24
4.3 SEALING OF OPTICAL SYSTEM.....	24
4.4 MATERIALS AND METHODS OF CONSTRUCTION.....	24
4.5 SURFACE FINISH.....	25
4.6 WEATHER RESISTANCE	25
4.7 OPERATING TEMPERATURES	25
4.8 ENVIRONMENTAL TESTS.....	25
SECTION 5 ELECTRICAL REQUIREMENTS	
5.1 COMPLIANCE WITH AS/NZS 3100	28
5.2 SUPPLY VOLTAGE.....	28
5.3 PROVISION OF CONNECTION TO SUPPLY	29
5.4 BUILT-IN TRANSFORMERS	30
5.5 DESIGN AND GENERAL	30
5.6 COMPONENTS AND CONSTRUCTION	31

SECTION 6 OPERATIONAL REQUIREMENTS

6.1	GENERAL.....	32
6.2	LIGHT OUTPUT STATES.....	32
6.3	SIGNAL SWITCHING RESPONSE TIMES.....	33
6.4	PROGRESSIVE FAILURE OF LEDS.....	34
6.5	DIMMING OF ASPECTS	34

SECTION 7 OPTICAL SYSTEM COMPONENTS AND ANCILLARY DEVICES

7.1	ASSEMBLY OF OPTICAL SYSTEM	35
7.2	PROPERTIES OF OPTICAL COMPONENTS	35
7.3	LED ARRAYS	35
7.4	DISPLAY OF SYMBOLS	35
7.5	VISORS AND LOUVRES.....	36
7.6	TARGET BOARDS (FOR VEHICULAR LANTERNS).....	36
7.7	ANTI-SUN-PHANTOM DEVICES.....	37

APPENDICES

A	INFORMATION TO BE SUPPLIED WITH INQUIRY OR ORDER	45
B	LIST OF REFERENCED DOCUMENTS.....	46
C	BIBLIOGRAPHIC REFERENCES	48
D	TEST CONDITIONS AND PROCEDURES FOR PHOTOMETRIC AND COLORIMETRIC MEASUREMENTS	49
E	DERIVATION OF INITIAL LED ASPECT INTENSITIES	62
F	RECOMMENDED DIMENSIONS FOR VISORS AND THE ATTACHMENT OF TARGET BOARDS	66
G	EXAMPLES OF LIGHT OUTPUT GRAPHS FOR DEDICATED CONTROL WIRE DIMMING.....	70

FOREWORD

The Standard includes requirements for the dimensions of certain features of traffic signal lanterns and associated components, arising from a specific desire on the part of road and traffic authorities for uniformity in the appearance of traffic signalling equipment to road users, and from the need to facilitate the compatibility of equipment from different manufacturers.

NOTE: In particular, Appendix F gives recommended dimensions for visors and the attachment of target boards, with the objective of achieving interchangeability between components supplied by different manufacturers.

The photometric requirements for vehicular lanterns have been derived from the considerable body of research which has been conducted in Australia into factors affecting the visibility of these signals.

NOTE: See references in Appendix C.

The photometric requirements apply to new lanterns. In service, the photometric performance will deteriorate, sometimes appreciably. Therefore, to ensure that the lanterns continue to perform at a satisfactory level, a maintenance program will be necessary.

It is recommended that the tests necessary to determine compliance with this Standard be conducted by laboratories that are independently accredited and having competence to carry out the type of measurements involved.

STANDARDS AUSTRALIA

Australian Standard
Traffic signal lanterns

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE

This Standard specifies requirements for the design, construction and performance of traffic signal lanterns that use light emitting diode (LED) light sources and are intended to control the movement of vehicles, including bicycles, and pedestrians. It does not apply to the external control equipment that may be necessary for the functioning of the lanterns.

For vehicular lanterns, two basic levels of performance are specified, namely, for general purpose lanterns and for extended range lanterns. Requirements are also specified for lanterns that display symbols.

NOTES:

- 1 Requirements for the use of traffic signal lanterns in the control of vehicular and pedestrian traffic are set out in the AS 1742 series.
- 2 See Appendix A for the information which should be supplied with an inquiry or order for traffic signal lanterns that comply with this Standard.

1.2 REFERENCED DOCUMENTS

The Standards referred to in this document are listed in Appendix B.

NOTE: See Appendix C for bibliographic references.

1.3 DEFINITIONS

For the purpose of this Standard, the definitions below apply.

NOTE: Definitions of lighting quantities are given in AS 1852.845.

1.3.1 Aspect

A single optical system of a traffic signal lantern.

1.3.2 Beam axis (for vehicular lanterns)

A straight line passing through the geometric centre of the lens in the direction of maximum luminous intensity of the light emitted by the lantern, as determined in accordance with Paragraph D.1 of Appendix D.

1.3.3 Bicycle lantern

A lantern which is intended for the control of bicycle traffic.

1.3.4 Chromaticity

A term referring to colour quality expressed numerically.

1.3.5 Chromaticity coordinates

Two numbers that fix the position of a point on a colour diagram in order to numerically and graphically represent the colour of an object or light source.

NOTE: In essence, the numbers represent the proportions of two of three primary colours in a mixture that matches the colour specified. These proportions are often expressed in terms of the coordinates x, y in the CIE colorimetric system (see AS/NZS 2633).