

Australian Standard®

**Disturbances in mains supply
networks**

**Part 1: Limitation of harmonics
caused by household and similar
electrical appliances**

This Australian Standard was prepared by Committee EL/34, Electric Waveform Distortion. It was approved on behalf of the Council of Standards Australia on 15 March 1991 and published on 13 May 1991.

The following interests are represented on Committee EL/34:

Australian Electrical and Electronic Manufacturers Association
Bureau of Steel Manufacturers of Australia
Confederation of Australian Industry
Department of Defence
Electricity Supply Association of Australia
Institution of Engineers, Australia
Institution of Radio and Electronics Engineers, Australia
Monash University
Railways of Australia Committee
Telecom Australia
University of Sydney
University of Wollongong
Water Board, Sydney

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up-to-date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

Australian Standard®

**Disturbances in mains supply
networks**

**Part 1: Limitation of harmonics
caused by household and similar
electrical appliances**

First published as AS 2279.1—1979.
Second edition 1991.

PREFACE

This Standard was prepared by the Standards Australia Committee on Electric Waveform Distortion. It is one part of a Standard on disturbances in mains supply networks, the four parts being as follows:

Part 1—*Limitation of harmonics caused by household and similar electrical appliances*

Part 2—*Limitation of harmonics caused by industrial equipment*

Part 3—*Limitation of voltage fluctuations caused by household and similar electrical appliances*

Part 4—*Limitation of voltage fluctuations caused by industrial equipment*

This Standard should be read in conjunction with the Regulations, Service Rules and Installation Rules of the supply authority approving the connection.

Part 1 of this Standard applies to semiconductor controlled domestic electrical appliances and similar equipment, with ratings not exceeding 4.8 kV.A, and provides guidance for electricity suppliers, manufacturers of electrical appliances or equipment and users of the appliance or equipment, on tolerable harmonic content which may be produced by the appliance or equipment. The use of a common Standard by all parties is intended to improve the electromagnetic compatibility of electrical equipment connected to the mains, by the reduction of interfering waveforms and disturbances.

Part 1 specifies the limiting values of harmonic content produced by an electrical appliance when tested under specified conditions. Reference impedance networks are specified along with practical test methods and calculations. Guidance is provided on the implementation of these requirements.

In the preparation of Part 1, recommendations of the International Electrotechnical Commission were followed to the extent considered possible under conditions peculiar to Australian distribution systems.

CONTENTS

	<i>Page</i>
FOREWORD	3
1 SCOPE	4
2 REFERENCED DOCUMENTS	4
3 DEFINITIONS	4
4 REFERENCE IMPEDANCES	5
5 TEST METHODS AND CONDITIONS	5
6 LIMITS FOR APPLIANCES	7
APPENDIX A CALCULATION OF HARMONIC VOLTAGE RATIO	11

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

FOREWORD

Many household appliances and similar electrical equipment include electronic power supplies and control devices which may introduce disturbances into the mains supply network to which they are connected. In particular, appliances incorporating phase-control or burst-firing circuits may produce substantial harmonics and voltage fluctuations. Appliances equipped with asymmetrical control devices also produce d.c. in the supply system.

Such electrical appliances should not adversely affect the supply network characteristics, the supply voltage, or the performance of any other equipment connected to the supply network. Provision must, therefore, be made to limit such disturbing effects to achieve electromagnetic compatibility (EMC) between these appliances and other electrical equipment.

STANDARDS AUSTRALIA

Australian Standard

Disturbances in mains supply networks

Part 1—Limitation of harmonics caused by household and similar electrical appliances

1 SCOPE Part 1 of this Standard applies to semiconductor controlled electrical appliances for household and similar purposes, supplied directly from low-voltage distribution networks. Irrespective of the type of control, disturbances, which may be introduced into the mains supply networks by such appliances, include harmonics of the fundamental frequency.

Part 1 specifies:

- (a) Maximum permissible values of harmonic content which may be produced by an appliance tested individually under specified conditions.
- (b) The reference impedance networks and reference impedances to which these values refer.
- (c) Practical methods of test and calculation.
- (d) Guidance on practical application of the requirements.

The characteristics given in Part 1 of this Standard relate to appliances with a rating not exceeding 4.8 kV.A that can be connected to a.c. networks with a nominal frequency of 50 Hz and the following nominal voltages:

240/415 V, three-phase, three-wire or four-wire.

240 V, single-phase, two-wire.

NOTES:

- 1 240 V nominal includes rated voltages of 200 V to 250 V and 415 V nominal includes rated voltages between 380 V and 480 V.
- 2 4.8 kV.A is the maximum rating of plugs and socket-outlets complying with AS 3112.

Such equipment includes but is not limited to appliances for cooking or space heating, thermal appliances, motor-driven or magnetically driven appliances, portable tools, light dimmers and radio or television receivers.

Part 1 does not apply to the following equipment, for which limits are specified in Part 2:

- (a) Equipment subject to individual consideration by the supply authority before it may be connected to the system.
- (b) Appliances intended exclusively for industrial, professional or commercial purposes.
- (c) Equipment with ratings exceeding 4.8 kV.A.

2 REFERENCED DOCUMENTS The following documents are referred to in this Standard:

AS

1675 Current transformers—Measurement and protection

3100 Approval and test specification—Definitions and general requirements for electrical materials and equipment

~~3122~~¹ Approval and test specification—Plugs and socket-outlets

3 DEFINITIONS For the purpose of this Standard the following definitions apply:

3.1 Point of common coupling (PCC)—the point in the public supply network, electrically nearest to the consumer in whose installation the appliance under consideration is, or is to be, connected, at which other consumers' installations are, or may be, connected.

3.2 Harmonics—sinusoidal quantities, the frequencies of which are whole multiples of a frequency selected as the fundamental.

NOTE: For this Standard the fundamental frequency is the supply system frequency, i.e. 50 Hz.

3.3 Harmonic distortion—the departure of a waveform from sinusoidal shape that is caused by the addition of one or more harmonics to the fundamental.

3.4 Harmonic order (n)—the ratio between the harmonic frequency and the fundamental frequency.

3.5 Harmonic component—a component of order greater than 1 of the Fourier series of a periodic quantity.

3.6 Harmonic ratio—for a harmonic (voltage or current) of order n , the ratio, expressed as a percentage, of the r.m.s. value of the harmonic to the r.m.s. value of the fundamental.