

# Australian Standard<sup>®</sup>

## Methods of chemical and physical testing for the dairying industry

### Method 2.7: Liquid milks—Determination of calcium

AS 2300.2.7—2008

#### PREFACE

This Standard was prepared by the Standards Australia Committee FT-024, Food Products and Subcommittee FT-024-05, Dairy Products to supersede AS 2300.2.7—1988.

After a periodic review, the Committee recommended a new edition. This edition confirms the method without technical changes, but updates the referenced documents and reflects the current editorial style and includes a clause on uncertainty in measurement.

AS 2300 comprises a series of methods and related Standards for chemical and physical testing of milk and dairy products, including the preparation of samples for testing.

Standards in the AS 2300 series are divided into categories according to type of product to be tested, as follows:

#### AS

- 2300.1 General methods and principle
- 2300.2 Liquid milks
- 2300.4 Dried milk and dried milk products
- 2300.5 Condensed milk
- 2300.6 Cheese
- 2300.7 Butter
- 2300.8 Anhydrous milk fat
- 2300.9 Analysis of ice-cream and frozen milk products
- 2300.10 Caseins, caseinates and coprecipitates
- 2300.11 Cultured milk products

#### FOREWORD

This method is based on classical procedures, but it should be recognized that other procedures using more advanced instrumentation are available, for example atomic absorption and inductively coupled plasma spectrophotometry.

## METHOD

### 1 SCOPE

This Standard sets out a routine method for the determination of the calcium content of milk and of milk reconstituted from evaporated, condensed or dried milk.

### 2 APPLICATION

The method is applicable to raw milk, pasteurized milk, homogenized milk, reconstituted milk, skim or low fat milk, UHT milk, sterilized milk, and cream.

### 3 REFERENCED DOCUMENT

The following document is referred to in this Standard.

AS/NZS

2243 Safety in laboratories

2243.2 Part 2: Chemical aspects

### 4 PRINCIPLE

The protein in the sample is precipitated with trichloroacetic acid. The calcium contained in the filtrate is precipitated as calcium oxalate which is separated by centrifuging, dissolved in sulphuric acid and the oxalate solution titrated with potassium permanganate.

### 5 REAGENTS

Use only reagents of recognized analytical reagent grade and freshly distilled water or water of equivalent purity. The following reagents are required:

- (a) Acetic acid solution (20 percent V/V)—dilute 20 mL of glacial acetic acid ( $\rho_{20}$  1050 kg/m<sup>3</sup>) to 100 mL.
- (b) Ammonia solution strong—mix equal volumes of ammonia ( $\rho_{20}$  approximately 900 kg/m<sup>3</sup>) and water.
- (c) Ammonia solution, weak—dilute 2 mL of ammonia ( $\rho_{20}$  approximately 900 kg/m<sup>3</sup>) to 100 mL with water.
- (d) Ammonium oxalate solution—saturated solution at room temperature.
- (e) Methyl red solution—0.5 g/L solution in 95 percent ethanol.
- (f) Potassium permanganate solution (0.004 mol/L) (prepared, allowed to stand overnight and filtered)—standardized under acidic conditions.
- (g) Sulphuric acid solution (200 mL/L)—slowly add with stirring 200 mL of sulphuric acid ( $\rho_{20}$  1840 kg/m<sup>3</sup>) to 500 mL of water. Cool and dilute to 1 L with distilled water.

CAUTION: DO NOT ADD WATER TO ACID.

- (h) Trichloroacetic acid solution, weak—120 g/L solution.
- (i) Trichloroacetic acid solution, strong—200 g/L solution.