

Australian Standard[®]

Powered industrial trucks

Part 12: Hazardous areas

This Australian Standard was prepared by Committee ME/26, Industrial Trucks. It was approved on behalf of the Council of Standards Australia on 27 September 1995 and published on 5 January 1996.

The following interests are represented on Committee ME/26:

Association of Employers of Waterside Labour
Australian Chamber of Commerce and Industry
Australian Industrial Truck Association
Department of Occupational Health, Safety and Welfare, W.A.
Metal Trades Industry Association of Australia
Occupational Health and Safety Authority, Victoria
Port of Melbourne Authority
WorkCover Authority of N.S.W.

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 94068.

Australian Standard[®]

Powered industrial trucks

Part 12: Hazardous areas

PREFACE

This Standard was produced by the Standards Australia Committee on Industrial Trucks to supersede, in part, AS 2359.1—1985, *SAA Industrial Truck Code, Part 1: Design and manufacture*.

That original edition has been extensively modified in two ways: first by being split into several parts and second, by having much of the original material replaced with ISO documents, to which the Australian versions are technically equivalent.

This Standard is Part 12 of the new series. As is the case with Parts 1 and 2, it is entirely local in content and contains no international material.

Other Standards in this series are as follows:

- Part 1: General requirements
- Part 2: Operation
- Part 3: Counterbalanced fork-lift trucks—Stability tests
- Part 4: Reach and straddle fork-lift trucks—Stability tests
- Part 5: Control symbols
- Part 6: Safety code
- Part 7: Terminology
- Part 8: Pallet stackers and high-lift platform trucks—Stability tests
- Part 9: High-lift rider trucks—Overhead guards—Specification and testing
- Part 10: Fork-lift trucks—Hook-on type fork arms—Vocabulary
- Part 11: Fork-lift trucks—Hook-on type fork arms and fork carriers—Mounting dimensions

The term 'normative' has been used in this Standard to define the application of the appendix to which it applies. A 'normative' appendix is an integral part of a Standard.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

	<i>Page</i>
1 SCOPE	4
2 REFERENCED DOCUMENTS	4
3 SPECIFIC REQUIREMENTS	5
4 MARKING	7

APPENDICES

A MAINTENANCE OF VEHICLES THAT ARE USED IN HAZARDOUS AREAS	8
B TEST REQUIREMENTS	9

Currently in preview, click buy full version

Originated as part of AS B270—1968.
Previous edition AS 2359.1—1985.
Revised and redesignated in part as AS 2359.12—1996.

STANDARDS AUSTRALIA

Australian Standard

Powered industrial trucks

Part 12: Hazardous areas

1 SCOPE This Standard specifies requirements that can be applied to a vehicle, so that the vehicle is able to operate safely in areas that may be hazardous because of the presence of an explosive gas/vapour atmosphere or combustible dusts. This part should be read in conjunction with any other relevant parts of this series. Procedures for the maintenance of vehicles in hazardous areas are given in Appendix A and performance testing requirements are given in Appendix B.

NOTES:

- 1 Explosive gas atmospheres and combustible dusts are classified in accordance with the appropriate parts of AS 2430.
- 2 This Standard does not apply to —
 - (a) areas where inherently explosive dusts are present; and
 - (b) underground working of coal mines.
- 3 Precautions should be taken to reduce accidents from hazards other than explosive gas atmospheres and combustible dusts. Actual and potential hazards can arise from the following:
 - (a) Poor visibility.
 - (b) Floor or ground surfaces which are low-friction, excessively rough or excessively sloping.
 - (c) Toxic atmospheres.
 - (d) Restricted ventilation that may allow carbon monoxide to increase or oxygen to reduce.
 - (e) Dusts that may be conductive and so create a short-circuit causing a vehicle to run out of control, particularly if the vehicle is electrically powered.
 - (f) Inadequate maintenance.

2 REFERENCED DOCUMENTS The following documents are referred to in this Standard:

AS

- | | |
|--------|--|
| 1019 | Internal combustion engines—Spark emission control devices |
| 1915 | Electrical equipment for explosive atmospheres—Battery-operated vehicles |
| 2236 | Electrical equipment for explosive atmospheres—Dust-excluding ignition-proof (DIP) enclosure |
| 2359 | Powered industrial trucks |
| 2359.1 | General requirements |
| 2380 | Electrical equipment for explosive atmospheres—Explosion-protection techniques |
| 2380.1 | Part 1: General requirements |
| 2381 | Electrical equipment for explosive atmospheres—Selection, installation and maintenance |