

Australian Standard[®]

**Measurement of fluid flow in closed
conduits**

**Part 6.2. Volumetric methods—
By volume**

[ISO title: Measurement of liquid flow in closed conduits—Method by
collection of the liquid in a volumetric tank]

This Australian Standard was prepared by Committee CE/24, Measurement of Water Flow in Open Channels and Closed Conduits. It was approved on behalf of the Council of Standards Australia on 3 August 1993 and published on 20 December 1993.

The following interests are represented on Committee CE/24:

Association of Consulting Engineers of Australia
Department of Water Resources, New South Wales
Engineering and Water Supply Department, South Australia
Forestry Commission of New South Wales
Institute of Instrumentation and Control, Australia
Melbourne Water
Monash University
Snowy Mountains Engineering Corporation
University of New South Wales
University of Queensland
Water Authority of Western Australia
Water Board, Sydney— Illawarra— Blue Mountains
Water Resources Commission, Queensland

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

Australian Standard®

**Measurement of fluid flow in closed
conduits**

**Part 6.2: Volumetric methods—
By volume**

First published as AS 2360.6.2—1993.

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 8498 X

PREFACE

This Standard was prepared by the Standards Australia Committee on Measurement of Water Flow in Open Channels and Closed Conduits. It is identical with and has been reproduced from ISO 8316:1987, *Measurement of liquid flow in closed conduits—Method by collection of the liquid in a volumetric tank*.

Under arrangements made between Standards Australia and the international Standards bodies, ISO and IEC, as well as certain other Standards organizations, users of this Australian Standard are advised of the following:

- (a) Copyright is vested in Standards Australia.
- (b) The number of this Standard is not reproduced on each page; its identity is shown only on the cover and title pages.
- (c) There may be occasional dual language sections, but English is always one of the languages reproduced.
- (d) Where any cross-references to page numbers appear within the text, these relate to page numbering in the international Standard and are to be disregarded.

This Standard is one of a series, to be published progressively, which deals with methods of measurement of fluid flow in closed conduits. The following Parts were published concurrently with this Part:

AS

- | | |
|----------|--|
| 2360 | Measurement of fluid flow in closed circuits |
| 2360.0 | Part 0: Vocabulary and symbols |
| 2360.1.1 | Part 1.1: Pressure differential methods—Measurement using orifice plates, nozzles or Venturi tubes—Conduits with diameters from 50 mm to 1200 mm |
| 2360.1.2 | Part 1.2: Pressure differential method—Measurement using orifice plates or nozzles—Conduits with diameters less than 50 mm |
| 2360.1.3 | Part 1.3: Pressure differential methods—Measurement using orifice plates, nozzles or Venturi tubes—Guide to the use of methods specified in Parts 1.1 and 1.2 |
| 2360.1.4 | Part 1.4: Pressure differential methods—Measurement using orifice plates, nozzles or Venturi tubes—Guide to the effect of departure from the conditions specified in Part 1.1 |
| 2360.1.5 | Part 1.5: Pressure differential methods—Measurement using orifice plates, nozzles or Venturi tubes—Pulsating flow, in particular sinusoidal or square wave intermittent periodic-time fluctuations |
| 2360.6.1 | Part 6.1: Volumetric methods—By mass |
| 2360.6.2 | Part 6.2: Volumetric methods—By volume (<i>this Standard</i>) |
| 2360.7.1 | Part 7.1: Assessment of uncertainty in the calibration and use of flow measurement devices—Linear calibration relationships |
| 2360.7.2 | Part 7.2: Assessment of uncertainty in the calibration and use of flow measurement devices—Non-linear calibration relationships |

At the date of publication of this Part the following Parts, with the numbers of the parent international Standards in parenthesis, had not been published:

Pressure differential methods—Measurement using orifice plates, nozzles or Venturi tubes—Connections for pressure signal transmissions between primary and secondary elements (ISO 2186)

Pitot static tube methods—Measurement of velocity at a point of the cross-section of a conduit (ISO 7145)

Pitot static tube methods—Measurement using Pitot-static tubes (ISO 3966)

Pitot static tube methods—Measurement in swirling or asymmetric flow conditions using ISO 3966 or ISO 3354 (ISO 7194)

Current meters method—Measurement of clean water in full conduits and under regular flow conditions using current meters (ISO 3354)

Non-radioactive tracer methods—Review of alternative methods (ISO 2975.1)

Non-radioactive tracer methods—Measurement using constant rate injection (ISO 2975.2)

Non-radioactive tracer methods—Measurement using transit time (ISO 2975.6)

Weighing methods—Verification of static type (ISO 9368.1)

Weighing methods—Verification of dynamic type (ISO 9368.2, not published)

When published, the details for the above unpublished Australian Standards will be listed in the Catalogue of Australian Standards and Other Products.

For the purposes of this Australian Standard, the ISO text should be modified as follows:

- (i) Wherever the words 'International Standard' appear, referring to this Standard, they should be read as 'Australian Standard'.
- (ii) Substitute a full stop (.) for a comma (,) as a decimal marker.
- (iii) The references to other publications should be replaced by references to Australian Standards as follows:

<i>Reference to International Standard</i>		<i>Australian Standard</i>	
ISO		AS	
4006	Measurement of fluid flow in closed conduits—Vocabulary and symbols	2360	Measurement of fluid flow in closed conduits—Vocabulary and symbols
4185	Measurement of liquid flow in closed conduits—Weighting method	2360.0 2360.6.1	Part 0: Vocabulary and symbols Part 6.1: Volumetric methods—By mass
4373	Measurement of liquid flow in open channels—Water level measuring devices	3778 3778.6.5	Measurement of water flow in open channels Part 6.5: Measuring devices, instruments and equipment—Water level measuring devices
5168	Measurement of fluid flow—Estimation of uncertainty of flow-rate measurement	3778.2.4	Part 2.4: General—Estimation of uncertainty of a flow-rate measurement

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

	<i>Page</i>
1 Scope and field of application	1
2 References	1
3 Symbols and definitions	1
4 Principle	2
5 Apparatus	5
6 Procedure	7
7 Calculation of flow-rate	8
8 Calculation of the overall uncertainty in the flow-rate measurement	9
 Annexes	
A Corrections to the measurement of filling time	13
B Density of pure water at standard atmospheric pressure of 101,325 kPa	17
C Example of a volumetric flow-rate installation using the dynamic gauging method	17
D Example of a volumetric flow-rate installation using the standing start and finish method	18
E Student's <i>t</i> -distribution	21

Measurement of fluid flow in closed conduits

Part 6.2: Volumetric methods—By volume

1 Scope and field of application

This International Standard specifies methods for the measurement of liquid flow in closed conduits by determining the volume of liquid collected in a volumetric tank in a known time interval. It deals in particular with the measuring apparatus, the procedure, the method for calculating the flow-rate and the assessment of uncertainties associated with the measurements.

The method described may be applied to any liquid provided that

- a) its vapour pressure is sufficiently low to ensure that any escape of liquid by vaporization from the volumetric tank does not affect the required measurement accuracy;
- b) its viscosity is sufficiently low so as not to alter or delay unduly the measurement of the level in the volumetric tank;
- c) it is non-toxic and non-corrosive.

Theoretically there is no limit to the application of this method, but, for practical reasons, this method of measurement is normally used for flow-rates less than approximately 1,5 m³/s and is used on the whole in fixed laboratory installations only. However, there is a variation of this method which uses a natural or artificial storage pond as a volumetric tank, but this application is not dealt with in this International Standard.

Owing to its high potential accuracy, this method is often used as a primary method for calibrating other methods or devices for volume flow-rate measurement or for mass flow-rate measurement; for the latter method or device, it is necessary to know the density of the liquid accurately.

If the installation for flow-rate measurement by the volumetric method is used for purposes of legal metrology, it shall be certified and registered by the national metrology service. Such installations are then subject to periodic inspection at stated intervals. If a national metrology service does not exist, a certified record of the basic measurement standards (length, time and temperature), and error analysis in accordance with this International Standard and ISO 5168, shall also constitute certification for legal metrology purposes.

Annex A forms an integral part of this International Standard. Annexes B to E, however, are given for information only.

2 References

- ISO 100, *Measurement of fluid flow in closed conduits — Vocabulary and symbols.*
- ISO 185, *Measurement of liquid flow in closed conduits — Weighing method.*
- ISO 4373, *Measurement of liquid flow in open channels — Water level measuring devices.*
- ISO 5168, *Measurement of fluid flow — Estimation of uncertainty of a flow-rate measurement.*

3 Symbols and definitions

3.1 Symbols (see also ISO 4006)

Table 1

Symbol	Quantity	Dimensions	SI unit
e_R	Random uncertainty, in absolute terms	*	*
E_R	Random uncertainty, as a percentage	—	—
e_S	systematic uncertainty, in absolute terms	*	*
E_S	systematic uncertainty, as a percentage	—	—
q_m	Mass flow-rate	MT ⁻¹	kg/s
q_V	Volume flow-rate	L ³ T ⁻¹	m ³ /s
t	Filling time of the tank	T	s
V	Discharged or measured volume	L ³	m ³
z	Liquid level in the tank	L	m
ρ	Density	ML ⁻³	kg/m ³

* The dimensions and units are those of the quantities in question.