

AS 2361—1990
NZS 6608—1990

Australian Standard®
New Zealand Standard

**Freight containers—Automatic
identification—Operating
parameters**

This Standard was prepared under a joint arrangement by Standards Australia and the Standards Association of New Zealand. It was approved for publication on behalf of the Council of Standards Australia on 7 March 1990 and on behalf of the Standards Council of New Zealand on 14 March 1990. It was published on 11 June 1990.

The following organizations are represented on the Committees responsible for this Standard:

Standards Australia Committee TE/—, Telecommunications and Electronics Standards Board

AUSSAT

Australian Broadcasting Authority

Australian Electrical and Electronic Manufacturers Association

Australian Electronics Industry Association

Australian Information Industry Association

Australian Telecommunications User Group

Civil Aviation Authority

Confederation of Australian Industry

Consumer Electronics Suppliers Association

CSIRO, Division of Applied Physics

Department of Defence

Department of Industry Technology and Commerce

Department of Transport and Communications

Federation of Australian Commercial Television Stations

Federation of Australian Radio Broadcasters

Institution of Engineers, Australia

Institution of Radio and Electronics Engineers, Australia

Overseas Telecommunications Corporation (OTC)

Regulatory Authorities (Electrical)

Telecom Australia

University of Queensland

Additional interests participating in preparation of Standard:

Associated Container Transportation, Australia (ACTA)

Association of Australian Port and Marine Authorities

Australian Customs Service

Manufacturers and Suppliers of Electronic Identification Systems.

Standards Association New Zealand 60/—, Electrotechnical Divisional Committee

Review of Standards. To keep abreast of progress in industry, Joint Australian/New Zealand Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Joint Standards and related publications will be found in the Standards Australia and Standards New Zealand Catalogue of Publications; this information is supplemented each month by the magazines 'The Australian Standard' and 'Standards New Zealand', which subscribing members receive, and which give details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Joint Standards, addressed to the head office of either Standards Australia or Standards New Zealand, are welcomed. Notification of any inaccuracy or ambiguity found in a Joint Australian/New Zealand Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in Australia in draft form for comment in Australia as DR 88192 and in New Zealand as DZ 6608.

AS 2361—1990
NZS 6608—1990

Australian Standard®
New Zealand Standard

**Freight containers—Automatic
identification—Operating
parameters**

In Australia
First published as AS 2361—1990.

In New Zealand
First published as NZS 6608—1990.

PUBLISHED JOINTLY BY:

STANDARDS AUSTRALIA
1 The Crescent,
Homebush NSW 2140 Australia

STANDARDS NEW ZEALAND
Level 10, Standards House,
155 The Terrace,
Wellington 6001 New Zealand

ISBN 0 7262 6210 2

PREFACE

This Standard is issued as a Joint Standard under the terms of the Memorandum of Understanding between Standards Australia and the Standards Association of New Zealand with the objective of reducing technical barriers to trade between the two nations.

This Standard was prepared on behalf of the Standards Australia Telecommunications and Electronics Standards Board to provide guidance for continuing development work in the field of automatic electronic identification of freight containers.

The Standard does not provide a detailed technological solution to the problem but seeks to encourage future development along the most productive lines within defined operational parameters.

CONTENTS

	<i>Page</i>
FOREWORD	3
1 SCOPE	4
2 REFERENCED DOCUMENTS	4
3 SAFETY	4
4 OPERATING FREQUENCY AND POWER	4
5 TRANSPONDERS (TAGS)	4
6 INTERROGATION DEVICE	5
APPENDIX A. LIST OF REFERENCED DOCUMENTS	8

© Copyright — STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Users of Standards are reminded that copyright subsists in all Standards Australia and Standards New Zealand publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia or Standards New Zealand may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia or Standards New Zealand. Permission may be conditional on an appropriate royalty payment. Australian requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia. New Zealand requests should be directed to Standards New Zealand.

Up to 10 percent of the technical content pages of a Standard may be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia or Standards New Zealand.

Inclusion of copyright material in computer software programs is also permitted without royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia or Standards New Zealand at any time.

FOREWORD

The major inadequacy of present freight distribution systems is the lack of an efficient automatic electronic tracking system. Present freight tracking systems are manpower intensive, inefficient, and susceptible to errors. In addition, tracking information is obtained only on entry to and exit from a distribution system. While it is possible to put a tracer on freight moving through a system, this is a manual operation that is both expensive and time consuming. Unless tracking information is available at various points within the distribution system, it is not possible to re-route freight, to apply priorities in the most economic way, or to change priorities. Currently, logistics managers cannot exercise efficient control over freight movements within distribution systems.

Over the past few years, technological progress in the area of electronic identification systems has advanced to the stage where the application of technology can provide significant cost and operational benefits to distribution systems worldwide. While total benefits will not accrue until entire systems are implemented, major benefits can be gained in the short term by implementing the tracking concept in conjunction with electronic freight management systems.

Many different types of systems are being developed and applied in the field of transportation. Each type consists of interrogation devices at various points within the distribution system and transponders (tags) that are programmed and affixed to containers as they enter the system.

One type uses a pulsed infrared beam which is received by a battery-powered transponder (active tag) which responds by transmitting a low-power radiofrequency signal containing the programmed identification data. The signal is received by the interrogation device.

A second type uses a continuous radiofrequency beam which is received by the transponder (semi-passive tag), coded with the programmed identification data, and reflected to the interrogation device.

A third type uses a totally passive tag (no batteries) which transmits its programmed data when it enters the low frequency, low power electromagnetic field generated by an interrogation device.

Operation does not rely on contact or close proximity between tag and interrogation device as is the case with bar coding of packages, a system found to be unsuited to many transport applications.

Containers may be fitted with two or more identically programmed transponders in order to facilitate interrogation under different modes of approach to an interrogation device.

Where interrogation devices are provided at each freight terminal or transshipment point, the containers from each ship, aircraft, train, or other vehicle can be interrogated and their identities can be stored temporarily in data logging devices or downloaded directly into computers, together with the geographic location of the interrogation device and the date/time of the interrogation.

Where containers are stacked awaiting transshipment, portable interrogation devices could be used to locate particular containers requiring priority or special treatment. Accordingly, the combination of automatic identification and manual location can provide means for managerial intervention at reasonable cost.

An automatic electronic freight tracking system as described can provide real time information on the location of containers within a distribution system. Accordingly managers would be able to identify, record, account for, locate and control the dispatch, receipt, routing or re-routing of freight at convenient points in a distribution system.

STANDARDS AUSTRALIA/STANDARDS ASSOCIATION OF NEW ZEALAND

Australian/New Zealand Standard**Freight containers—Automatic identification—Operating parameters**

1 SCOPE. This Standard specifies operating parameters, conditions and constraints for transponder tags and interrogation devices used for the automatic electronic identification of freight containers used on land, sea, or in the air.

The Standard also deals with the data to be contained within the tag, the interrogation device, and the host computer equipment/system.

2 REFERENCED DOCUMENTS. The documents referred to in this Standard are listed in Appendix A.

3 SAFETY. Automatic identification equipment will be used in areas in which both occupational and non-occupational exposure limits apply. In accessible areas, emission levels of radiated energy from electronic automatic identification equipment shall therefore comply with Standard for non-occupational exposure and shall not exceed the specified limits for non-occupational exposure in Australia or New Zealand, depending on the Country of use.

For radiofrequency radiation, it is recommended that, notwithstanding the specified limits, the design and application of the equipment be such that exposure levels are As Low As Reasonably Achievable, economic and social conditions being taken into account (see Note 2).

NOTES:

1. For radiofrequency radiation, see IRPA Guidelines, also AS 2772.1 and AS 2772.2 (for use in Australia), NZS 6609.1 and NZS 6609.2 (for use in New Zealand).
2. The recommendation known as the ALARA principle made by ICRP in 1955 (see ICRP 9, Paragraph 52) was further developed in 1973 (see ICRP 22, Paragraph 12) and endorsed by WHO in 1981 (see WHO Environmental Health Criteria 16, Clause 1.2.6). The adverb 'Reasonably' replaces 'Readily' (see ICRP 22, Paragraph 20).
3. For laser radiation, see AS 2211.
4. For light and near-infrared radiation, see ACGIH limits.

Where equipment is to operate in areas which may be hazardous due to the presence of flammable gases or combustible dusts, the equipment shall be explosion-protected, i.e. it shall comply with AS 2380.7 or any other technique suitable for the particular area involved (see AS 1076.1).

Where equipment has to be designed and operated in order to achieve a negligible possibility of inadvertent initiation of electro-explosive device (EEDs), reference should be made to BS 6657.

4 OPERATING FREQUENCY AND POWER. Equipment using radiofrequency shall be approved in respect of both operating frequency and power emission by the Department of Transport and Communications (for use in Australia) or by the Communications Division, Ministry of Commerce (for use in New Zealand).

5 TRANSPONDERS (TAGS)

5.1 Size and mass. The maximum dimensions and mass of a transponder including its means of mounting shall be—

breadth:	200 mm
length:	400 mm
depth:	20 mm
mass:	250 g

5.2 Operability. The transponder shall be fully operational when installed within $\pm 15^\circ$ of its intended orientation.

5.3 Method of fixing. The transponder shall be capable of being fixed to wood, plastic, or metal in a manner capable of withstanding normal freight handling procedures.

5.4 Environmental withstand. The transponder shall be physically robust and shall withstand the condition specified in Table 1.

5.5 Data content. The transponder shall be arranged to hold the data specified in ISO 6346 which are as follows:

- (a) Owner code: 4 capital letters
- (b) Serial number: 6 Arabic numerals
- (c) Check digit: 1 Arabic numeral

Other data may be incorporated as desired.

5.6 Battery life. Where a battery is incorporated, a transponder shall provide a normal operating life of eight years based on 20 transactions per day.