

Australian Standard®

**Methods of sampling and testing
retroreflective materials and devices
for road traffic control purposes**

Part 1: Retroreflective materials

DD



STANDARDS AUSTRALIA 

This Australian Standard was prepared by Committee MS/49, Retroreflective Devices. It was approved on behalf of the Council of Standards Australia on 22 June 1990 and published on 12 November 1990.

The following interests are represented on Committee MS/49:

- Australian Road Federation
- Australian Road Research Board
- Austrroads
- Confederation of Australian Industry
- Confederation of Construction Contractors
- CSIRO, National Measurement Laboratory
- Metal Trades Industry Association of Australia
- Railways of Australia Committee
- University of New South Wales

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up-to-date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue and publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

Australian Standard®

**Methods of sampling and testing
retroreflective materials and devices
for road traffic control purposes**

Part 1: Retroreflective materials

AS 2445.1 first published as part of SAA Int 354—1955.
Revised and redesignated AS 1906.1—1976.
AS 1906.1—1976 revised and redesignated
in part as AS 2445.1—1990.

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
STANDARDS HOUSE, 80 ARTHUR ST, NORTH SYDNEY NSW

ISBN 0 7262 6411 3

PREFACE

This Standard was prepared by the Standards Australia Committee on Retroreflective Devices to supersede (in part) AS 1906.1—1976, *Retroreflective materials and devices for road traffic control purposes, Part 1: Retroreflective materials*.

This work has been carried out simultaneously with a revision of AS 1906.1. It now contains all of the test methods which were previously included in the 1976 edition of that Standard.

A reference to wrinkling has been included in AS 1906.1 as a potential form of degradation. It has not yet been determined under what, if any, circumstances wrinkling can be tolerated, nor has a suitable test method yet been developed. These matters are being investigated by the Committee and will result in either an amendment to this Standard or an inclusion in a future revision.

CONTENTS

	<i>Page</i>
1 SCOPE	3
2 REFERENCED DOCUMENTS	3
3 DEFINITIONS	3
4 SAMPLING	3
5 TESTING	3

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the Head Office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

STANDARDS AUSTRALIA

Australian Standard

Methods of sampling and testing retroreflective materials and devices for road traffic control purposes

Part 1: Retroreflective materials

1 SCOPE This Standard sets out methods of sampling and testing retroreflective materials, as specified in AS 1906.1, for use in the manufacture of road signs and related traffic control devices. It does not apply to retroreflective pavement markings, markers placed directly on the pavement surface or post-mounted delineators.

2 REFERENCED DOCUMENTS The following documents are referred to in this Standard:

AS	
1449	Wrought alloy steels—Stainless and heat-resisting steel plate, sheet and strip
1580	Method of test for paints and related materials
1580.403.1	Method 403.1: Scratch resistance
1734	Aluminium and aluminium alloys—Flat sheet, coiled sheet and plate
1906	Retroreflective materials and devices for road traffic control purposes
1906.1	Part 1: Retroreflective materials
2445	Methods of sampling and testing retroreflective materials and devices for road traffic control purposes
2445.2	Method 2: Retroreflective devices (non-pavement application)
CIE	
Publication No 13.2 (1974)	Method of measuring and specifying colour rendering—Properties of light sources
Publication No 20 (1972)	Recommendations for the integrated irradiance and spectral distribution of simulated solar radiation for testing purposes

3 DEFINITIONS For the purpose of this Standard, the definitions given in AS 1906.1 apply.

4 SAMPLING Test pieces shall be selected in a random manner.

5 TESTING

5.1 Preparation of test pieces

5.1.1 Conditioning of test pieces Unless otherwise specified in a particular test, where conditioning of test pieces is required prior to testing in any of the tests prescribed in this Standard, the conditioning shall consist in the storing of the specimen at $20 \pm 2^\circ\text{C}$ and $50 \pm 5\%$ relative humidity for 24 h. The subsequent test shall be carried out at the same temperature and relative humidity unless otherwise specified in a particular test. Before conditioning, test pieces shall be washed with a mild detergent.

5.1.2 Mounting of test pieces—physical property and adhesion tests Where tests prescribed in Clauses 5.6, 5.7 and 5.9 are to be performed using a test piece mounted on a substrate, the test pieces shall be applied to polished (mirror finish) 0.9 mm stainless steel sheet, 18/8 austenitic, Grade AS 1449/302, in the degreased condition.

For material having pressure-sensitive adhesive, the pressure of application of the material to the stainless steel substrate shall be obtained by use of a steel roller 80 ± 5 mm diameter and 45 ± 2 mm wide, covered with rubber approximately 5 mm thick and having a Shore A Durometer hardness of 80 ± 5 . The mass of the roller shall be 2.0 ± 0.1 kg.

For material having heat-activated adhesive, the method of application of the material to the stainless steel substrate shall be strictly in accordance with the application instructions of the manufacturer of the retroreflective material.

5.1.3 Mounting of test pieces—other tests For tests prescribed in Clauses 5.2, 5.3, 5.4, 5.10, 5.11, 5.12 and 5.13, the method of mounting the test piece shall be the same as in Clause 5.1.2 except that the substrate shall be a 2 mm thick panel of aluminium complying with the requirements of AS 1734 for alloy 5052-H36, 5052-H38, 5251-H36, 5251-H38, or 6061-T6. The panel shall be degreased and lightly acid-etched prior to mounting the test piece.