

2455

Under Revision See DR9374

Superseded by AS/NZS 2455.1:1995

WITHDRAWN 19950705

AS 2455—1989

Australian Standard®

Textile floor coverings — Laying practice



D

This Australian Standard was prepared by Committee TX/9, Carpets. It was approved on behalf of the Council of Standards Australia on 12 December 1988 and published on 20 March 1989.

The following interests are represented on Committee TX/9:

Australian Chemical Specialties Manufacturers Association
Australian Retailers Association
Australian Wool Corporation
AWTA Textile Testing
Carpet Institute of Australia
Commercial Carpet Suppliers' Association of New South Wales
Confederation of Australian Industry
CSIRO, Division of Wool Technology
Department of Administrative Services—Australian Construction Services
Department of Business and Consumer Affairs, N.S.W.
Government Supply Department, N.E.W.
Melbourne College of Textiles
Plastics Institute of Australia
Royal Australian Institute of Architects
Textile Clothing & Footwear Council of Australia
University of New South Wales

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up-to-date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

Australian Standard®

**Textile floor coverings—Laying
practice**

First published as AS 2455—1981.
Second edition 1989.

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
STANDARDS HOUSE, 80 ARTHUR ST, NORTH SYDNEY NSW

ISBN 0 7262 5494 0

PREFACE

This Standard was prepared by the Standards Australia Committee on Carpets under the direction of the Textile Standards Board to supersede the 1981 edition.

In the preparation of the Standard, consideration was given to requirements included in AS 1884, *Floor coverings—Resilient sheet and tiles—Laying and maintenance practices*, and in BS 5325, *Code of practice for installation of textile floor coverings*.

At the time that this Standard was published a separate Standard on underlay materials for soft floor coverings was being prepared. When this Standard becomes available, it should be consulted, where relevant.

CONTENTS

	<i>Page</i>
SECTION 1. SCOPE AND GENERAL	
1.1 SCOPE	3
1.2 REFERENCED DOCUMENTS	3
1.3 DEFINITIONS	3
1.4 MATERIALS	3
1.5 SITE INSPECTION AND REPORT	4
1.6 EXCHANGE OF INFORMATION	4
SECTION 2. CONDITIONING AND LAYING	
2.1 CONDITIONING OF FLOOR COVERINGS AND SUBFLOOR	6
2.2 UNDERLAYS	6
2.3 LAYING REQUIREMENTS	7
APPENDICES	
A SITE INFORMATION TO BE SUPPLIED TO CONTRACTOR	11
B DETERMINATION OF DRYNESS OF CONCRETE SUBFLOORS	12
C THE PRINCIPLES OF STRETCHING TEXTILE FLOOR COVERINGS	14

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the Head Office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

STANDARDS AUSTRALIA

Australian Standard

Textile floor coverings—Laying practice

SECTION 1. SCOPE AND GENERAL

1.1 SCOPE. This Standard sets out requirements for laying textile floor coverings (carpets). It gives details of the work necessary in preparing subfloor surfaces, together with the procedures that should be adopted where textile floor coverings are laid over various types of subfloors and where underfloor heating units are installed. Details of information to be supplied to the contractor are also specified (see Appendix A).

NOTE: Underfloor heating units refers to any panel heating appliance or system whereby the subfloor structure is warmed intentionally for space heating purposes.

1.2 REFERENCED DOCUMENTS. The following documents are referred to in this Standard:

- AS
1684 SAA Timber Framing Code
2454 Textile floor coverings—Terminology, definitions and structure classification

1.3 DEFINITIONS. For the purpose of this Standard, the definitions below apply.

NOTE: The terminology used in the Standard relative to textile floor coverings and their laying practice is that defined in AS 2454.

1.3.1 Crotch—the junction of the lower edge of the riser with the rear-most edge of the stair tread.

1.3.2 Planeness (of a surface)—a surface of a grade such that when a straightedge 1.5 m long is placed on it at any position, no part is more than 1 mm below the straightedge.

1.3.3 Purchaser—the principal to the contract or the person authorized by the principal to superintend the work on his behalf.

1.3.4 Screed topping—a bed of fine concrete or other suitable material applied to a subfloor and brought to a defined level (see Figure 1.1).

1.3.5 Smoothness (of a surface)—a surface of a grade such that when a straightedge 150 mm long is placed on it at any position, no part of it is more than 1 mm below the straightedge.

1.3.6 Soft floor laying contractor—the firm or person authorized by the purchaser to carry out the laying of the floor covering.

NOTE: The soft floor contractor referred to in this Standard as 'the contractor'.

1.3.7 Subfloor—the surface on which the floor covering or the underlay is to be laid (see Figure 1.1).


1.3.8 Underlay—a coherent layer of material placed between the subfloor and the textile floor covering.

NOTE: 'Hard underlay' (e.g. sheet material, screed topping or floor leveling compound) provides a smooth, plane surface on which to lay the textile floor covering. 'Soft underlay' provides a cushioning effect (see Figure 1.1).


1.4 MATERIALS.

NOTE: Where a relevant Australian Standard does not exist, the requirements of this Clause are matters for agreement between the purchaser, the contractor, and the supplier of the textile floor covering, underlay or adhesive, as appropriate.

1.4.1 Textile floor coverings. Textile floor coverings shall comply with the requirements of the relevant Australian Standards. Where applicable, the textile floor covering referred to in this Standard shall be suitable for use above subfloor heating where the temperature of the upper surface of the subfloor does not exceed 27°C. Wherever possible, if defects are found, the manufacturer should be contacted.



(a) Concrete floor



(b) Wood floor

FIGURE 1.1 ILLUSTRATION OF CONCRETE AND WOOD FLOORS AND EXPLANATION OF TERMS