

Australian Standard[®]

**Valves for compressed gas
cylinders (diameter-indexed outlet)**

This Australian Standard was prepared by Committee ME/2, Gas Cylinders. It was approved on behalf of the Council of Standards Australia on 17 August 1990 and published on 12 November 1990.

The following interests are represented on Committee ME/2:

ACT Administration—Office of City Management
Aluminium Development Council
Australian Assembly of Fire Authorities
Australian Chamber of Commerce
Australian Gas Association
Australian Liquefied Petroleum Gas Association
Australian Underwater Federation
Bureau of Steel Manufacturers of Australia
Confederation of Australian Industry
Department of Defence
Department of Employment, Vocational Education, Training and Industrial Relations, Qld
Department of Industrial Relations, N.S.W.
Department of Labour and Industry, Tas.
Department of Labour, S.A.
Department of Labour, Victoria
Department of Occupational Health, Safety and Welfare, W.A.
Department of Resource Industries, Qld
Fire Protection Industry Association of Australia
Insurance Council of Australia
Railways of Australia Committee
Welding Technology Institute of Australia
WorkCover Authority, N.S.W.
Work Health Authority, N.T.

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 87237.

Australian Standard[®]

**Valves for compressed gas
cylinders (diameter-indexed outlet)**

First published as AS 2474—1981.
Second edition 1990.

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 6533 0

PREFACE

This Standard was prepared by the Standards Australia Committee on Gas Cylinders to supersede AS 2474—1981. As the previous edition provided only for self-sealing outlet connections, it was considered necessary to provide for additional types of outlet connections, especially when dealing with inert gases. The new edition of AS 2473—1990, *Valves for compressed gas cylinders (threaded outlets)* also specifies connector type E as the alternative outlet connection.

CONTENTS

	<i>Page</i>
1 SCOPE	3
2 REFERENCED DOCUMENTS	3
3 DEFINITIONS	3
4 CLASSIFICATION AND DESIGNATION	3
5 MATERIALS	3
6 MANUFACTURING CONSIDERATIONS	3
7 TESTING	3
8 MARKING	3
APPENDIX A SCHEME FOR ALLOCATION OF CONNECTION DESIGNATIONS FOR GASES AND GAS MEASURES	10

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

STANDARDS AUSTRALIA

Australian Standard

**Valves for compressed gas cylinders
(diameter-indexed outlet)**

1 SCOPE This Standard specifies outlet connection dimensions for a system of diameter-indexed valve connections for a limited range of nominated gases.

NOTE: Requirements for other aspects of the valves are specified by reference to AS 2473. Requirements for valves employing the pin-indexed outlet connections (for medical application) are specified in AS 2472.

This Standard does not apply to valves for portable gas cylinders of less than 11 kg water capacity for self-contained breathing apparatus, or to valves for fire extinguishers.

2 REFERENCED DOCUMENTS The following documents are referred to in this Standard:

AS

- 1721 General purpose metric screw threads
 2030 SAA Gas Cylinders Code
 2030.1 Part 1: Cylinders for compressed gases other than acetylene
 2472 Valves for medical gas cylinders
 2473 Valve for compressed gas cylinders (threaded outlet)

3 DEFINITIONS For the purpose of this Standard, the definitions given in AS 2030.1 apply.

4 CLASSIFICATION AND DESIGNATION The valve outlet and outlet connection details shall be as designated in Table 1 for the particular gas. Dimensions and tolerances shall comply with Figures 1 to 6 as nominated in Table 1.

NOTE: Appendix A provides the basis for allocation of outlet connections within the system of diameter-indexed connections.

5 MATERIALS Materials shall comply with AS 2473.

6 MANUFACTURING CONSIDERATIONS

6.1 General Valve bodies shall not be manufactured as castings.

6.2 Valve stem thread The valve stem (inlet) thread shall comply with AS 2473.

6.3 Valve operations Diameter-indexed outlet valves are intended to be operated by the connection or disconnection of the outlet-connecting parts. If valve is spindle operated, the valve shall comply with AS 2473.

6.4 Pressure rating The maximum service pressure for which the valve is rated shall be nominated by the valve manufacturer and shall be verified by testing in accordance with AS 2473.

7 TESTING Testing shall be in accordance with AS 2473, except that, in addition to leak testing of any spindle gland, a leakage test in accordance with AS 2473 shall be applied with the outlet-connecting parts fully engaged and fully disengaged.

8 MARKING Valves shall be permanently and legibly marked on the body with the manufacturer's name or mark, and sufficient information to determine the maximum service pressure for which the valve is designated.

TABLE 1
OUTLET CONNECTION DESIGNATION FOR LISTED GASES

Gas	Outlet connection	Reference figure
Air	B	2
Acetylene	A	1
Argon	E	5
Carbon dioxide	F	6
Helium	E	5
Hydrogen	C	3
Krypton	E	5
Neon	E	5
Nitrogen	E	5
Oxygen	D	4
Xenon	E	5

NOTE: Additional gases and outlet connection types are expected to be added in accordance with the scheme of allocation given in Appendix A.