

Australian Standard[®]

Cylinders for dissolved acetylene

STANDARDS
Australia



This Australian Standard® was prepared by Committee ME-002, Gas Cylinders. It was approved on behalf of the Council of Standards Australia on 4 September 2006. This Standard was published on 27 September 2006.

The following are represented on Committee ME-002:

- Air Conditioning and Refrigeration Wholesalers Association
 - Australasian Institute of Engineer Surveyors
 - Australian Chamber of Commerce and Industry
 - The Australian Gas Association
 - Australian Liquefied Petroleum Gas Association
 - Certification Bodies (Australia)
 - Department for Administrative and Information Services, S.A.
 - Fire Protection Association of Australia
 - Institute of Materials Engineering Australasia
 - Pressure Equipment Associated Incorporated
 - Victorian WorkCover Authority
 - Welding Technology Institute of Australia
 - WorkCover New South Wales
-

This Standard was issued in draft form for comment as DR 06249.

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Standard through their representation on the Committee and through public comment period.

Keeping Standards up-to-date

Australian Standards® are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting www.standards.org.au

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

STANDARDS AUSTRALIA

RECONFIRMATION

OF

AS 2527—2006

Cylinders for dissolved acetylene

RECONFIRMATION NOTICE

Technical Committee ME-002 has reviewed the content of this publication and in accordance with Standards Australia procedures for reconfirmation, it has been determined that the publication is still valid and does not require change.

Certain documents referenced in the publication may have been amended since the original date of publication. Users are advised to ensure that they are using the latest versions of such documents as appropriate, unless advised otherwise in this Reconfirmation Notice.

Approved for reconfirmation in accordance with Standards Australia procedures for reconfirmation on 22 May 2017.

The following are represented on Technical Committee ME-002:

Australasian Fire and Emergency Service Authorities Council
Australia New Zealand Industrial Gas Association
Australian Chamber of Commerce and Industry
Engineers Australia
Environmental Protection Authority New Zealand
Fire Protection Association Australia
Gas Energy Australia
Gas Technical Regulation Committee
International Accreditation New Zealand
National Association of Testing Authorities Australia
SafeWork NSW
The Australian Gas Association
Welding Technology Institute of Australia
Worksafe New Zealand
WorkSafe Victoria

NOTES

Currently in preview, click buy full vers.

Australian Standard[®]

Cylinders for dissolved acetylene

Originated as AS 189—1962.
Previous edition AS 2527—1997.
Third edition 2006.

COPYRIGHT

© Standards Australia

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia, GPO Box 476, Sydney, NSW 2001, Australia

ISBN 0 7337 7751 1

PREFACE

This Standard was prepared by the Australian members of the Joint Standards Australia/Standards New Zealand Committee ME-002, Gas Cylinders to supersede AS 2527—1997, *Cylinders for dissolved acetylene*. After consultation with stakeholders from both countries, Standards Australia and Standards New Zealand decided to develop this Standard as an Australian, rather than an Australian/New Zealand Standard.

The objective of this revision is to align the shell specifications with current world practice, allowing a range of seamless steel and welded steel shells made to ISO and other recognized international Standards.

Cylinder design details are provided by reference to Australian and acceptable international Standards that give details of materials, design and manufacturing test regimes.

This Standard also sets out requirements for the porous filler and the solvent together with the cylinder markings.

This Standard allows seamless-steel cylinders as well as welded steel cylinders as suitable shells for acetylene gas use. Obsolete cylinder standards listed as shell specifications in the previous edition have been deleted.

This Standard takes into account ISO 3807, *Dissolved acetylene cylinders—Basic requirements*; the main deviation from that Standard being the inclusion of the simulated external fire test.

The term ‘normative’ has been used in this Standard to define the application of the appendix to which it applies. A ‘normative’ appendix is an integral part of a Standard.

CONTENTS

	<i>Page</i>
1 SCOPE.....	4
2 REFERENCED DOCUMENTS.....	4
3 DEFINITIONS.....	4
4 CYLINDER SHELL	4
5 POROUS FILLER	5
6 SOLVENT	5
7 TYPE TESTS.....	5
8 RECORD OF DATA	6
9 MARKING	7

APPENDICES

A LIST OF REFERENCED DOCUMENTS	8
B SELECTION AND NUMBERS OF CYLINDERS FOR TESTING	9
C ULLAGE TEST AT ELEVATED TEMPERATURES	10
D PERFORMANCE UNDER BACKFIRE	11
E PERFORMANCE UNDER SIMULATED EXTERNAL FIRE CONDITION	15
F METHOD FOR DETERMINATION OF POROSITY OF FILLER MATERIAL	18

STANDARDS AUSTRALIA

Australian Standard
Cylinders for dissolved acetylene**1 SCOPE**

This Standard specifies the basic requirements for steel cylinders of 5 kg to 160 kg water capacity intended for the storage and transport of dissolved acetylene. Requirements for the porous filler, the solvent, and the cylinder marking are also specified.

NOTE: AS 2030.2 specifies requirements for the filling, inspection and maintenance of cylinders for compressed acetylene dissolved in a solvent.

2 REFERENCED DOCUMENTS

A list with the titles of the documents referred to in this Standard is given in Appendix A.

3 DEFINITIONS

For the purposes of this Standard, the definitions in AS 2030.1 and the following definitions apply:

3.1 Cylinder manufacturer

The organization that produced the completed, but not necessarily charged, acetylene cylinder.

3.2 Dissolved acetylene cylinder

A cylinder and a valve, with safety devices, containing a porous filler, and a solvent for the storage of dissolved acetylene.

3.3 Maximum acetylene charge

The mass of acetylene nominated by the acetylene cylinder manufacturer as being that which may be charged into the cylinder exclusive of the mass of dissolved acetylene to saturate the solvent at atmospheric pressure and at 15°C.

3.4 Tare mass

The combined mass of the cylinder, the valve, well packing, safety devices, the porous filler, the solvent, the dissolved acetylene sufficient to saturate the solvent at atmospheric pressure and at 15°C, and any valve protection features that are permanently attached directly to the cylinder.

4 CYLINDER SHELL**4.1 Shell specification**

The cylinder shell shall be of steel, and shall be manufactured in accordance with one of the following Standards, but the cylinder markings shall be in accordance with this Standard:

- (a) AS 2469.
- (b) AS 2470.
- (c) AS 2875.
- (d) ISO 4706.