

STANDARDS AUSTRALIA

---

**RECONFIRMATION**

**OF**

**AS 2582.6—2003**

**Complete, filled transport packages—Methods of test  
Method 6: Vibration test at fixed low frequency**

---

**RECONFIRMATION NOTICE**

Major stakeholders of this publication have reviewed the content of this publication and in accordance with Standards Australia procedures for reconfirmation, it has been determined that the publication is still valid and does not require change.

Certain documents referenced in the publication may have been amended since the original date of publication. Users are advised to ensure that they are using the latest versions of such documents as appropriate, unless advised otherwise in this Reconfirmation Notice.

Approved for reconfirmation in accordance with Standards Australia procedures for reconfirmation on 11 September 2020.

NOTES

Currently in preview, click buy full vers.

## Complete, filled transport packages— Methods of test

### Method 6: Vibration test at fixed low frequency

#### PREFACE

This Standard was prepared by Standards Australia Committee PK-012, Physical Testing of Packages and Containers, to supersede (in part) AS 2582.6—1983, *Complete, filled transport packages—Methods of test, Part 6: Vibration test*. This Standard is identical with and has been reproduced from ISO 2247:2000, *Packaging—Complete, filled transport packages and unit loads—Vibration tests at fixed low frequency*.

As this Standard is reproduced from an International Standard, the following modifications apply:

- (a) Its number does not appear on each page of text and its identity is shown on the cover and title page.
- (b) In the source text, ‘this International Standard’ should read ‘this Australian Standard.’
- (c) Substitute a full point for a comma when referring to a decimal marker.

References to International Standards should be replaced by references to equivalent Australian Standards as follows:

<i>Reference to International Standard</i>		<i>Australian Standard</i>	
ISO		AS	
2206	Packaging—Complete, filled transport packages—Identification of parts when testing	2582	Complete, filled transport packages—Methods of test
		2582.1	Part 1: Identification of parts when testing
2233	Packaging—Complete, filled transport packages and unit loads—Conditioning for testing	2582.2	Part 2: Conditioning for testing
2234	Packaging—Complete, filled transport packages—Stacking tests using a static load	2583.3	Part 3: Stacking tests using a static load

## INTRODUCTION

It is the responsibility of the user of this International Standard to establish appropriate health and safety practice in accordance with relevant legislation.

Currently in preview, click buy full version

## 1 Scope

This International Standard specifies methods to carry out vibration tests on complete, filled transport packages and unit loads using sinusoidal excitation at fixed frequency. These tests may be used to assess the performance of packages and unit loads in terms of the strength or the protection that they offer to their contents when subjected to low frequency vibration. These tests may be performed either as a single test to investigate the effects of low frequency vibration or as a part of a sequence of tests designed to measure the ability of a package or unit load to withstand a distribution system that includes a vibration hazard at low frequency or repetitive shocks.

## 2 Normative references

The following normative documents contain provisions which, through reference in this test, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 2206, *Packaging — Complete, filled transport packages — Identification of parts when testing.*

ISO 2233, *Packaging — Complete, filled transport packages and unit loads — Conditioning for testing.*

ISO 2234, *Packaging — Complete, filled transport packages and unit loads — Stacking tests using static load.*

## 3 Term and definition

For the purposes of this International Standard, the following term and definition applies.

### 3.1

#### **test specimen**

a complete, filled transport package or unit load

## 4 Principle

The test specimen is placed on a vibration table and subjected to a vibration using an approximately sinusoidal excitation at a fixed low frequency. The atmospheric conditions, the duration of the test, the peak acceleration, the attitude of the test specimen and any method of restraint are predetermined.

NOTE — When required, a load may be superimposed on the test specimen to simulate conditions at the bottom of a stack.