

AS 2606—1983

Australian Standard[®]

**VIBRATION AND SHOCK—
VOCABULARY**

This Australian standard was prepared by Committee ME/41, Vibration and Shock. It was approved on behalf of the Council of the Standards Association of Australia on 7 December 1982 and published on 5 April 1983.

The following interests are represented on Committee ME/41:

Association of Consulting Engineers Australia
Australian Gas Association
Australian Mining Industry Council
Australian Shipbuilders Association
Confederation of Australian Industry
Construction Equipment Importers and Manufacturers of Australia
CSIRO, National Measurement Laboratory
Department of Defence
Department of Health, N.S.W.
Department of Industrial Relations, N.S.W.
Department of Industry and Commerce (Commonwealth and N.S.W.)
Department of Science and Technology (Commonwealth)
Federation of Automotive Products Manufacturers
Institute of Technology, N.S.W.
Institute of Quarrying
Institution of Mechanical Engineers Australia
Metropolitan Water Sewerage and Drainage Board
Monash University
National Association of Testing Authorities Australia
University of Melbourne
University of Newcastle
University of New South Wales
University of Queensland

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

Australian Standard[®]

**VIBRATION AND SHOCK—
VOCABULARY**

First published 1983

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 2884 2

PREFACE

This standard was prepared by the Association's Committee on Vibration and Shock as one of a series relating to mechanical vibration and shock. It is based on, and is substantially in agreement with, the corresponding International Standard ISO 2041, Vibration and Shock—Vocabulary.

The aim is to provide a common language for those working in the field of mechanical vibration and shock, with a view to eliminating ambiguities and misunderstanding.

Except as indicated in this preface, the entries in this standard are identical with those of ISO 2041. A few of the entries in ISO 2041 have been omitted as they are not directly applicable to vibration and shock (most of the terms omitted are applicable to acoustics and are covered in AS 1633), and a few of the definitions in ISO 2041 have been altered in meaning where this was considered to be essential to conform to accepted Australian usage.

A few of the definitions common to acoustics have been presented in a different form, using the definitions already available in AS 1633. To facilitate cross-reference between this standard and ISO 2041, the numbering of the entries in ISO 2041 has been retained, despite the omission of some of the entries of the ISO text.

ISO 2041 contains two annexes, Annex A giving definitions of certain mathematical terms and Annex B giving definitions of certain auxiliary terms. The definitions of the mathematical terms have been omitted from this standard as they are not particular to vibration and shock technology and are already well established. The definitions of the auxiliary terms have been retained where those terms are essential for use in vibration and shock technology (see Appendix B).

A constant length of four digits has been used for the entry numbers in this standard but it should be noted that, except in Section 2, the entry numbers in ISO 2041 have only three digits, i.e. 1.01..., 2.01..., 3.01..., 4.01....

The following standards were referred to in the preparation of this standard:

AS 1633	Glossary of Acoustic Terms
ISO 2041	Vibration and Shock—Vocabulary
ISO 1925	Balancing—Vocabulary
BS 3015	Glossary of Terms Relating to Mechanical Vibration and Shock

CONTENTS

	<i>Page</i>
SECTION 1. GENERAL	3
SECTION 2. VIBRATION	8
SECTION 3. MECHANICAL SHOCK	15
SECTION 4. TRANSDUCERS	17
APPENDICES	
A (Vocabulary)	
B Auxiliary Terminology	19
ALPHABETICAL INDEX	21

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

STANDARDS ASSOCIATION OF AUSTRALIA

Australian Standard

for

VIBRATION AND SHOCK—VOCABULARY

SECTION 1. GENERAL

No	Term	Definition
1.001	displacement relative displacement	A vector quantity that specifies the change of position of a body, or particle, with respect to a reference frame. NOTES: 1. The reference frame is usually a set of axes at a mean position or a position of rest. In general, the displacement can be represented by a rotation vector, a translation vector, or both. 2. A displacement is designated as relative displacement if it is measured with respect to a reference frame other than the primary reference frame designated in the given case. The relative displacement between two points is the vector difference between the displacement of the two points. 3. Various modifiers such as peak, r.m.s., and average or mean, are often used. The time intervals over which these modifier values are taken should be indicated or implied.
1.002	velocity relative velocity	A vector that specifies the time-derivative of displacement. NOTES: 1. The reference frame is usually a set of axes at a mean position or a position of rest. In general, the velocity can be represented by a rotation vector, a translation vector, or both. 2. A velocity is designated as relative velocity if it is measured with respect to a reference frame other than the primary reference frame designated in a given case. The relative velocity between two points is the vector difference between the velocities of the two points. 3. Various modifiers such as peak, r.m.s., and average or mean, are often used. The time intervals over which these modifier values are taken should be indicated or implied.
1.003	acceleration	A vector that specifies the time-derivative of velocity. NOTES: 1. The reference frame is usually a set of axes at a mean position or a position of rest. In general, the acceleration can be represented by a rotation vector, a translation vector, or both. 2. An acceleration is designated as relative acceleration if it is measured with respect to a reference frame other than the primary reference frame designated in a given case. The relative acceleration between two points is the vector difference between the accelerations of the two points. 3. Various modifiers such as peak, r.m.s. and average or mean, are often used. The time intervals over which these modifier values are taken should be indicated or implied. 4. Acceleration may be oscillatory, in which case simple harmonic components can be defined by the acceleration amplitude (and frequency), or random, in which case the r.m.s. acceleration (and bandwidth and probability density distribution) can be used to define the probability that acceleration will have values within any given range. Accelerations of short time duration are defined as transient accelerations. Non-oscillatory accelerations are defined as sustained accelerations if of long duration, or, if of short duration, as acceleration pulses.
1.004	acceleration of gravity, g	The acceleration produced by the force of gravity at the surface of the Earth. It varies with the latitude and elevation of the point of observation. NOTES: 1. By international agreement, the value $9.806\ 65\ \text{m/s}^2$ has been chosen as the standard acceleration due to gravity (g_n). 2. Acceleration magnitude is frequently expressed as a multiple of g_n .
1.005	jerk	A vector that specifies the time-derivate of acceleration.
1.006	inertial reference system inertial reference frame	A coordinate system in which the laws of inertia (classical mechanics) are valid. NOTE: An inertial reference systems signifies a coordinate system which is not accelerating.
1.007	inertia force inertial force	The reaction force exerted by a mass when it is being accelerated.
1.008	oscillation	The variation, usually with time, of the magnitude of a quantity with respect to a specified reference when the magnitude is alternately greater and smaller than some mean value.