

Australian Standard[®]

Safety devices for gas cylinders

This Australian Standard was prepared by Committee ME/2, Gas Cylinders. It was approved on behalf of the Council of Standards Australia on 11 September 1989 and published on 11 December 1989.

The following interests are represented on Committee ME/2:

ACT Administration—Office of City Management
Aluminium Development Council
Australian Assembly of Fire Authorities
Australian Chamber of Commerce
Australian Liquefied Petroleum Gas Association
Australian Underwater Federation
Bureau of Steel Manufacturers of Australia
Confederation of Australian Industry
Department of Defence
Department of Industrial Affairs, Qld
Department of Industrial Relations and Employment, N.S.W.
Department of Labour, S.A.
Department of Labour, Vic.
Department of Labour and Industry, Tas.
Department of Mines, Qld
Department of Occupational Health, Safety and Welfare, W.A.
Fire Protection Industry Association of Australia
Insurance Council of Australia
Railways of Australia Committee
The Australian Gas Association
Work Health Authority, N.T.

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review, and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 87157.

AS 2613—1989

Australian Standard[®]

Safety devices for gas cylinders

First published as AS B281 — 1969.
Revised and redesignated as AS 2613 — 1983.
Second edition 1989.

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 5927 6

PREFACE

This Standard was prepared by the Standards Australia Committee on Gas Cylinders to supersede AS 2613—1983. The new edition is considered to be necessary to provide more specific requirements and clarification for the testing of pressure-relief valves.

A proposal from the gas cylinder industry was the basis for Appendix D and Appendix H. These Appendices treat pressure-relief valves as a special category of device, and introduce a repeat cycle in the test to show performance after an initial sequence of start-to-discharge, reseal, lift, full discharge, and reseal.

This edition has been restructured to separate performance requirements from test methods. Changes of a technical nature are made in Clauses 1.4, 4.1, 4.3, and 4.6.

Investigations of safety relief of LP gas fuel vessels for automotive vehicles have confirmed that the effects of any safety device discharge channel can be critical. The requirements for discharge from an automotive LP gas vessel have been incorporated in a new edition of AS 1425, *SAA Automotive LP Gas Code*. For gas cylinders covered by any Part of AS 2030, *SAA Gas Cylinder Code*, safety relief device rating is to take into account the full effects of any discharge channel.

It is recognized that not all types of safety devices for gas cylinders fit into the categories provided by the Standard and it should be noted that certain government departments may have regulations setting different requirements from those in this Standard, e.g. the Navigation Act Classified List of Dangerous Goods and Air Navigation Orders.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

	<i>Page</i>
SECTION 1. SCOPE AND GENERAL	
1.1 SCOPE	4
1.2 REFERENCED DOCUMENTS	4
1.3 DESIGNATION	4
1.4 DEFINITIONS	4
SECTION 2. SELECTION AND PERFORMANCE REQUIREMENTS	
2.1 SELECTION	6
2.2 FLOW RATE	6
2.3 FLOW-RATING PRESSURE OF A PRESSURE-RELIEF VALVE	6
2.4 START-TO-DISCHARGE PRESSURE OF A PRESSURE-RELIEF VALVE	6
2.5 RATED BURSTING PRESSURE OF A BURSTING DISC DEVICE	6
SECTION 3. MATERIALS, DESIGN, AND CONSTRUCTION	
3.1 GENERAL	7
3.2 DESIGN	7
SECTION 4. PERFORMANCE UNDER TEST	
4.1 GENERAL	8
4.2 TYPE TESTS (OF ALL TYPES OF DEVICES)	8
4.3 PRODUCTION TESTS OF PRESSURE-RELIEF VALVES	8
4.4 PRODUCTION TESTS OF SAFETY DEVICES OTHER THAN PRESSURE-RELIEF VALVES	8
4.5 RETESTS	8
4.6 AFTER-SERVICE RETESTS	8
SECTION 5. IDENTIFICATION AND MARKINGS	
5.1 ALL SAFETY DEVICES	9
5.2 INDIVIDUAL COMPONENTS OF BURSTING DISC ASSEMBLIES	9
5.3 FUSIBLE PLUG	9
5.4 PRESSURE-RELIEF VALVES	9
5.5 COMBINATION SAFETY DEVICES	9
APPENDICES	
A TEST METHOD FOR YIELD TEMPERATURE OF A SEPARATE FUSIBLE PLUG	10
B TEST METHOD FOR YIELD TEMPERATURE OF A FUSIBLE MATERIAL	11
C SUGGESTED SAMPLE SELECTION FOR TEST PURPOSES	12
D TEST METHOD FOR START-TO-DISCHARGE, LIFT, FULL DISCHARGE, AND RESEAL OF LP GAS PRESSURE-RELIEF VALVES	13
E TEST METHOD FOR START-TO-DISCHARGE, LIFT, FULL DISCHARGE, AND RESEAL FOR PRESSURE RELIEF VALVES	15
F TEST METHOD FOR BURSTING PRESSURE OF A BURSTING DISC	16
G TEST METHOD FOR EXTRUSION OF AN UNREINFORCED FUSIBLE OR REINFORCED FUSIBLE PLUG	16
H TEST METHODS FOR FLOW RATING OF GAS SAFETY RELIEF DEVICES	17
J TEST METHOD FOR BURSTING PRESSURE AND YIELD TEMPERATURE OF A COMBINED BURSTING DISC/FUSIBLE PLUG DEVICE	18
K FORMAT OF APPROVAL APPLICATION	19

STANDARDS AUSTRALIA

Australian Standard
Safety devices for gas cylinders

SECTION 1. SCOPE AND GENERAL

1.1 SCOPE. This Standard specifies the designations, and the requirements for design, construction, testing, and marking of safety devices required by the AS 2030 series Standards to be fitted to gas cylinders.

NOTES:

1. Safety devices to this Standard are also suitable for use in accordance with AS 1425 for LP gas fuel vessels, but it should be noted that the performance values required by the AS 2030 series and AS 1425 are not necessarily the same. Where intended for use in accordance with AS 1425, the term 'gas cylinder' should be read to include 'LP gas fuel vessel'.
2. Fitment of safety devices on cylinders used for certain gases is prohibited (see requirements for fitment of safety devices specified in the various Parts of AS 2030).

1.2 REFERENCED DOCUMENTS. The following documents are referred to in this Standard:

AS	
1425	SAA Automotive LP Gas Code
1821	Suppliers quality systems for design, development production and installation
1822	Suppliers quality systems for production and installation
1823	Suppliers quality inspection systems
2030	SAA Gas Cylinders Code
2030.1	Part 1: Cylinders for compressed gases other than acetylene
2527	Cylinders for dissolved acetylene
BS	
1042	Measurement of fluid flow in closed conduits Part 1: Pressure differential devices Section 1.1: Specification for square-edged orifice plates, nozzles and venturi tubes inserted in circular cross-section conduits running full Section 1.4: Guide to the use of devices specified in Sections 1.1 and 1.2
CGA*	
Pamphlet S-1.1	Safety relief device standards Part 1: Cylinders for compressed gases.

1.3 DESIGNATION. Safety devices shall be designated as follows:

- (a) Type BD—Bursting disc.
- (b) Type FP1—Fusible plug or reinforced fusible plug, utilizing a fusible material with yield temperature not more than 77°C nor less than 69°C (74°C nominal).
- (c) Type FP2—Fusible plug or reinforced fusible plug, utilizing a fusible material with yield temperature not more than 104°C nor less than 98°C (100°C nominal).
- (d) Type BD/FP1—Series combination bursting disc/fusible plug, utilizing a fusible material with yield temperature not more than 77°C nor less than 69°C (74°C nominal).
- (e) Type BD/FP2—Series combination bursting disc/fusible plug, utilizing material with yield temperature not more than 104°C nor less than 98°C (100°C nominal).
- (f) Type PRV—Pressure-relief valve.
- (g) Type PRV/FP1—Parallel combination pressure-relief valve/ fusible plug, utilizing a fusible material with yield temperature not more than 77°C nor less than 69°C (74°C nominal).
- (h) Type PRV/FP2—Parallel combination pressure-relief valve/ fusible plug, utilizing a fusible material with yield temperature not more than 104°C nor less than 98°C (100°C nominal).

1.4 DEFINITIONS. For the purpose of this Standard, the definitions given in AS 2030 and those below apply.

1.4.1 Safety device—a device, including the approach channel, the operating part, and the discharge channel, intended to protect a gas cylinder against overpressure or bursting.

1.4.2 Safety device channel—the passage or passages through which fluid discharge by operation of the safety device must pass from the gas cylinder to the atmosphere.

1.4.3 Safety device approach channel—the parts of the safety device channel on the gas cylinder contents side of the operating part, inclusive of any piping attached to the inlet side of the device.

1.4.4 Safety device discharge channel—that part of the safety device channel on the gas cylinder atmospheric side of the operating part, including any piping attached to the outlet side of the device.

1.4.5 Operating part—the part that closes the safety device channel, but, which when moved from this position as a result of the action of heat or pressure or a combination of the two, permits discharge of fluid from the gas cylinder.

1.4.6 Bursting disc—an operating part of a safety device in the form of a disc which closes the safety device channel. The disc is intended to burst at a predetermined pressure to permit discharge of fluid.

NOTE: Types of disc include flat, preformed, reinforced, and grooved discs.

1.4.7 Pressure opening—orifice against which the operating part functions.

1.4.8 Rated bursting pressure (of a bursting disc)—the maximum pressure at which the bursting disc is designed to burst at the rated temperature when in the pressure opening for which it is designed.

1.4.9 Rated temperature (of a bursting disc)—the temperature at which the rated bursting pressure of a disc is to be determined.

NOTE: Unless otherwise specified, rated temperature is taken as 65°C.

* Compressed Gas Association (U.S.A.)