

AS 2670.1—1990
ISO 2631/1—1985

Australian Standard[®]

**Evaluation of human exposure to
whole-body vibration**

Part 1: General requirements

This Australian Standard was prepared by Committee AV/10, Vibration and Shock — Human Effects. It was approved on behalf of the Council of Standards Australia on 8 May 1989 and published on 10 December 1990.

The following interests are represented on Committee AV/10:

Association of Australian Acoustical Consultants
Australian and New Zealand Environment Council
Australian Coal Association
Confederation of Australian Industry
Construction and Mining Equipment Association of Australia
CSIRO, National Measurement Laboratory
Department of Defence
Department of Minerals and Energy, N.S.W.
Federal Chamber of Automotive Industries
Railways of Australia Committee
Royal Institution of Naval Architects
University of Newcastle
The Workcover Authority, N.S.W.

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

Australian Standard[®]

**Evaluation of human exposure to
whole-body vibration**

Part 1: General requirements

First published as part of AS 2670—1983.
AS 2670—1983 revised and redesignated
in part as AS 2670.1—1990.

PREFACE

This Standard was prepared by the Standards Australia Committee on Vibration and Shock — Human Effects. It is identical with and has been reproduced from ISO 2631/1—1985, *Evaluation of human exposure to whole-body vibration— Part 1: General requirements*

For the purposes of this Australian Standard, the ISO text should be modified as follows:

- (a) Substitute a point (.) for a comma (,) as a decimal marker.
- (b) The references to other publications should be replaced by references to Australian Standards:

<i>Reference to International Standard</i>	<i>Australian Standard</i>
ISO 266 Acoustics — Preferred frequencies for measurements	AS 2533 Acoustics — Preferred frequencies for measurements
IEC 255 Octave, half-octave and third-octave band filters intended for the analysis of sounds and vibrations	Z41 Octave, half-octave and one-third octave band pass filters intended for the analysis of sound and vibrations

CONTENTS

	<i>Page</i>
0 INTRODUCTION	3
1 SCOPE AND FIELD OF APPLICATION	4
2 REFERENCES	4
3 CHARACTERIZATION OF VIBRATION EXPOSURE	4
4 VIBRATION EVALUATION GUIDE	6
BIBLIOGRAPHY	17

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

Evaluation of human exposure to whole-body vibration

Part 1: General requirements

0 Introduction

Vehicles (air, land and water), as well as machinery (for example, in industry and agriculture), expose man to mechanical vibration which can interfere with comfort, working efficiency and, in some circumstances, health and safety. Various methods of rating the severity of exposure and defining limits of exposure based on laboratory or field data have been developed in the past for specific applications. None of these methods can be considered applicable in all situations and consequently none has been universally accepted.

In view of the complex factors determining the human response to vibrations, and in view of the shortage of consistent quantitative data concerning man's perception of vibration and his reactions to it, this International Standard has been prepared first, to facilitate the evaluation and comparison of data gained from continuing research in this field; and, second, to give provisional guidance as to acceptable human exposure to whole body vibration. The limits proposed in this International Standard seem to be a fair compromise between the available data and should satisfy the need for recommendations which are simple and suitable for general application. These limits are defined explicitly in numerical terms to avoid ambiguity and to encourage precise measurement in practice. However, when using these criteria and limits it is important to bear in mind the restrictions placed upon their application.

Because of the wide variety of possible conditions and effects of human exposure to vibrations, and because of the existing shortage of firm data, more detailed guidance is hardly warranted at the present time. Nevertheless, it is hoped that this International Standard not only proves useful in the assessment of existing or predicted vibration environments but also stimulates the reporting and critical evaluation of new findings about the effects of vibration on man.

There are basically three kinds of human exposure to vibration, namely:

a) Vibrations transmitted simultaneously to the whole body surface or substantial parts of it. This occurs when the body is immersed in a vibrating medium. There are circumstances in which this is of practical concern; for example, when high intensity sound in air or water excites vibrations of the body.

b) Vibrations transmitted to the body as a whole through the supporting surface, namely, the feet of a standing man, the buttocks of a seated man or the supporting area of a reclining man. This kind of vibration is usual in vehicles, in vibrating buildings and in the vicinity of working machinery.

c) Vibrations applied to particular parts of the body such as the head or limbs; for example, by vibrating handles, pedals or head-rests, or by the wide variety of powered tools and apparatus held in the hand.

It is also possible to recognize the condition in which an indirect vibration nuisance is caused by the vibration of external objects in the visual field (for example, an instrument panel).

This International Standard, however, applies chiefly to the common conditions (1) above; and, in particular, where the vibration is applied through the principal supporting surface to the body of a standing or seated man. In the case of vibrations applied directly to a reclining or recumbent man, insufficient data are available to make a firm recommendation; this is particularly true of vibration transmitted directly to the head, when tolerability is generally reduced. Tolerance may also be reduced when conditions (b) and (c) exist together. Provisionally, however, the limits for the standing or seated man may also be used for the reclining or recumbent man. It shall be appreciated that some circumstances will arise in which the rigorous application of these limits would be inappropriate.

This International Standard comprises the following parts:

Part 1: General requirements.

Part 2: Evaluation of human exposure to vibration and shock in buildings (1 to 80 Hz).¹⁾

Part 3: Evaluation of exposure to whole-body z-axis vertical vibration in the frequency range 0,1 to 0,63 Hz.

Part 4: Evaluation of crew exposure to vibration on board sea-going ships (1 to 80 Hz).¹⁾

¹⁾ At present at the stage of draft.