

Australian Standard™

**Petroleum liquids and gases—Fidelity
and security of dynamic measurement—
Cabled transmission of electric and/or
electronic pulsed data**

This Australian Standard was prepared by Committee ME-049, Oil and Gas Measurement. It was approved on behalf of the Council of Standards Australia on 14 July 2002 and published on 12 August 2002.

The following are represented on Committee ME-049:

Australian Gas Association
Australian Institute of Petroleum
Australian Liquefied Petroleum Gas Association
Australian Petroleum Production and Exploration Association
CSIRO Telecommunications and Industrial Physics
East Australian Pipeline
National Association of Testing Authorities, Australia
National Standards Commission

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Australia web site at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Australian Standard*, has a full listing of revisions and amendments published each month.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.com.au, or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001.

Australian Standard™

**Petroleum liquids and gases—Fidelity
and security of dynamic measurement—
Cabled transmission of electric and/or
electronic pulsed data**

Revised as AS 2707—1984.
Second edition 2002.

COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd
GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 4726 4

PREFACE

This Standard was prepared by the Standards Australia Committee ME-049, Oil and Gas Measurement to supersede AS 2707—1984, *Petroleum liquids and gases—Fidelity and security of dynamic measurement—Cabled transmission of electric and/or electronic pulsed data*.

In this revision the number of security levels have been reduced to three, i.e. levels A, B and C.

Basic principles of ensuring that the data are either sound (level C), can be identified as faulty (level B) or can be corrected (level A), have been applied throughout.

The objective of the Standard is to ensure the integrity of the primary indication of the measurement for the petroleum industry.

This Standard is based on but not equivalent to sections of the Institute of Petroleum's *Petroleum measurement manual*, Part XIII, *Fidelity and security of measurement data transmission systems*, Section 1: *Electrical and/or electronic pulsed data cabled transmission for fluid metering systems* (ISBN 085 293 235 9).

CONTENTS

	<i>Page</i>
1 SCOPE.....	4
2 REFERENCED DOCUMENTS	4
3 DEFINITIONS	4
4 LEVELS OF SECURITY.....	6
5 SYSTEM DESIGN PRINCIPLES AND QUALITY	7
6 PRECAUTIONS	11
7 INSTALLATION.....	14
8 COMMISSIONING AND TESTING.....	16
9 INSPECTION AND MAINTENANCE.....	17

STANDARDS AUSTRALIA

Australian Standard

Petroleum liquids and gases—Fidelity and security of dynamic measurement—Cabled transmission of electric and/or electronic pulsed data**1 SCOPE**

This Standard provides guidelines for ensuring the fidelity and security of transmitted signals and data transmission systems utilized for the metering of fluids.

In order to achieve different levels of security which can be applied to such systems, criteria and recommendations for the design, installation, use and maintenance of the relevant equipment are laid down.

For the majority of applications, the lower levels are considered to be adequate and there is no known system for which Level A security is considered to be a necessity.

This Standard does not define which levels of security are to be used for a particular system application.

2 REFERENCED DOCUMENTS

The following documents are referred to in this Standard:

Institute of Petroleum

Petroleum measurement manual

Part XIII Fidelity and security of measurement data transmission systems, Section 1: Electrical and/or electronic pulsed data cabled transmission for fluid metering systems

AS/NZS

3000 Electrical installations (known as the Australian/New Zealand Wiring Rules)

3 DEFINITIONS

For the purpose of this Standard, the definitions below apply.

3.1 Accuracy

The measure of the closeness of a measurement to the conventional true value.

3.2 Analogue

The continuous current or voltage signal whose amplitude represents the measured variable, e.g. a 4 mA–20 mA signal from a pressure transducer proportional to the pressure being measured, a resistance measurement of a RTD made proportional to the temperature being measured.

3.3 Digital data

The data transmitted by pulsed codes. Data may be transmitted either in serial form along a single pair of conductors, e.g. RS232-C, or alternatively be presented as sets of d.c. levels on a number of parallel wires, e.g. Binary Coded Decimal (BCD) data.

3.4 Frequency signal

The signal in the form of continuous waveform where the measured quantity is represented by the waveform, or its period, e.g. from the vibrating element of a density meter.