

AS 2748—1991

ISO 2210: 1989

Australian Standard[®]

**Information technology—Data
communication—25-pole DTE/DCE
interface connector and contact
number assignments**

This Australian Standard was prepared by Committee IT/1, Information Systems—Interconnection. It was approved on behalf of the Council of Standards Australia on 8 March 1991 and published on 15 April 1991.

The following interests are represented on Committee IT/1:

Aussat
Australian Association of Permanent Building Societies
Australian Bankers Association
Australian Bureau of Statistics
Australian Committee of Directors and Principals
Australian Computer Society
Australian Computer Users Association
Australian Information Industry Association
Australian Telecommunication Users Group
Australian Vice Chancellors Committee
Confederation of Australian Industry
CSIRO, Institute of Information and Communication Technologies
Department of Defence
Department of Industry, Technology and Commerce
Information Exchange Steering Committee
Life Insurance Federation of Australia
OTC
Standards Association of New Zealand
Telecom Australia

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

Australian Standard[®]

**Information technology—Data
communication—25-pole DTE/DCE
interface connector and contact
number assignments**

First published as AS 1484.4—1973.
AS 1484.4—1973 revised and redesignated
AS 2748—1985.
Second edition 1991.

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 6839 9

PREFACE

This Standard was prepared by the Standards Australia Committee on Information Systems—Interconnection to supersede AS 2748—1985, *Data communication—25-pin DTE/DCE interface connector and pin assignments*. It is identical with and has been reproduced from ISO 2110:1989, *Information technology—Data communication—25-pole DTE/DCE interface connector and contact number assignments*.

The Standard is one of a series of Open Systems Interconnection (OSI) Standards which are currently under development. Since OSI Standards are developmental, there may be some minor difficulties encountered in their implementation. For this reason, Standards Australia will be providing, through the OSI Help Desk, a service to coordinate and disseminate information concerning difficulties which are identified in using this Standard.

Under arrangements made between Standards Australia and the international Standards bodies, ISO and IEC, as well as certain other Standards organizations, users of this Australian Standard are advised of the following:

- (a) Copyright is vested in Standards Australia.
- (b) The number of this Standard is not reproduced on each page; its identity is shown only on the cover and title pages.

For the purpose of this Australian Standard, the ISO text should be modified as follows:

- (i) *Terminology* The words 'Australian Standard' should replace the words 'International Standard' wherever they appear.
- (ii) *References* The references to other publications should be replaced by references to Australian Standards as follows:

<i>Reference to International Standard or other Publication</i>	<i>Australian Standard</i>
ISO 261	AS 1721
ISO general purpose metric screw threads—General plan	General purpose metric screw
8480	—
Information processing—Data communication—DTE/DCE interface back-up control operation using the 25-pole connector	
CCITT S.16	—
Connection to the telex network of an automatic terminal using a V.22 (1) DCE/DTE interface	
V.19	—
Modems for parallel data transmission using telephone signalling frequencies	
V.20	—
Parallel data transmission modems standardized for universal use in the general switched telephone network	
V.21	—
300 bits per second duplex modem standardized for use in the general switched telephone network	
V.22	—
1200 bits per second duplex modem standardized for use on the general switched telephone network and on point-to-point 2-wire leased telephone-type circuits	
V.22.b.	—
2400 bits per second modem using the frequency division technique standardized for use on the general switched telephone network and on point-to-point 2-wire leased telephone-type circuits	
V.23	—
600/1200-baud modem standardized for use in the general switched telephone network	
V.24	—
List of definitions for interchange circuits between data terminal equipment and data circuit-terminating equipment	

<i>Reference to International Standard or other Publication</i>	<i>Australian Standard</i>
V.25 Automatic answering equipment and/or parallel automatic calling equipment on the general switched telephone network including disabling of echo control devices for both manually and automatically established calls	—
V.25 bis Automatic calling and/or answering equipment on the general switched telephone network (GSTN) using the 100-series interchange circuits	—
V.26 2400 bits per second modem standardized for use on 4-wire leased telephone-type circuits	—
V.26 bis 2400/1200 bits per second modem standardized for use in the general switched telephone network	—
V.26 ter 2400 bits per second duplex modem using the echo cancellation technique standardized for use on the general switched telephone network and on point-to-point 2-wire leased telephone-type circuits	—
V.27 4800 bits per second modem with manual equalizer standardized for use on leased telephone-type circuits	—
V.27 bis 4800/2400 bits per second modem with automatic equalizer standardized for use on leased telephone-type circuits	—
V.27 ter 4800/2400 bits per second modem standardized for use in the general switched telephone network	—
V.28 Electrical characteristics for unbalanced double-current interchange circuits	—
V.29 9600 bits per second modem standardized for use on point-to-point 4-wire leased telephone-type circuits	—
V.31 Electrical characteristics for single-current interchange circuits controlled by contact closure	—
V.31 bis Electrical characteristics for single-current interchange circuits using photocouplers	—
V.32 A family of two-wire duplex modems operating at data signalling rates up to 9600 bit/s for use on the general switched telephone network and on leased telephone-type circuits	—
V.33 14400 bits per second modem standardized for use on point-to-point 4-wire leased telephone-type circuits	—
X.20 Interface between data terminal equipment (DTE) and data circuit-terminating equipment (DCE) for start-stop transmission services on public data networks	—
X.20 bis Use on public data networks of data terminal equipment (DTE) which is designed for interfacing to asynchronous duplex V-series modems	—
X.21 bis Use on public data networks of data terminal equipment (DTE) which is designed for interfacing to synchronous V-series modems	—
X.24 List of definitions for interchange circuits between data terminal equipment (DTE) and data circuit-terminating equipment (DCE) on public data networks	—

<i>Reference to International Standard or other Publication</i>	<i>Australian Standard</i>
IEC 50(581)	—
807-2	—

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

Information technology—Data communication—25-pole DTE/DCE interface connector and contact number assignments

1 Scope

This International Standard specifies the 25-pole connector and the assignment of contact numbers at the interface between data terminal equipment (DTE) and data circuit-terminating equipment (DCE) or parallel automatic calling equipment (ACE). It is applicable to voice band modems, public data network (PDN) facilities, telegraph signal converters, and automatic calling equipment where CCITT¹⁾ Recommendations V.24 and V.28 are applicable.

In the case of the PDN attachment through the X.20 interface, the functions of the interchange circuits are in accordance with CCITT Recommendation X.24.

In the case of the V.20 type outstation interface, the electrical characteristics are in accordance with CCITT Recommendation V.31 or V.31 bis.

International Standard ISO/IEC 2110 additionally provides the dimensions of the connector housing, as well as the recommended means of providing a locking device (latching block) and connector shielding.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 261 : 1973, *ISO general purpose metric screw threads — General plan.*

ISO 6480 : 1987, *Information processing — Data communication—DTE/DCE interface back-up control operation using the 25-pole connector.*

CCITT Recommendation S.16 : 1989, *Connection to the telex network of an automatic terminal using a V.24 [1] DCE/DTE interface.*

CCITT Recommendation V.19 : 1989, *Modems for parallel data transmission using telephone signalling frequencies.*

CCITT Recommendation V.20 : 1989, *Parallel data transmission modems standardized for universal use in the general switched telephone network.*

CCITT Recommendation V.21 : 1989, *300 bits per second duplex modem standardized for use in the general switched telephone network.*

CCITT Recommendation V.22 : 1989, *1 200 bits per second duplex modem standardized for use on the general switched telephone network and on point-to-point 2-wire leased telephone-type circuits.*

CCITT Recommendation V.22 bis : 1989, *2 400 bits per second duplex modem using the frequency division technique standardized for use on the general switched telephone network and on point-to-point 2-wire leased telephone-type circuits.*

CCITT Recommendation V.23 : 1989, *600/1 200-baud modem standardized for use in the general switched telephone network.*

CCITT Recommendation V.24 : 1989, *List of definitions for interchange circuits between data terminal equipment and data circuit-terminating equipment.*

CCITT Recommendation V.25 : 1989, *Automatic answering equipment and/or parallel automatic calling equipment on the general switched telephone network including disabling of echo control devices for both manually and automatically established calls.*

CCITT Recommendation V.25 bis : 1989, *Automatic calling and/or answering equipment on the general switched telephone network (GSTN) using the 100-series interchange circuits.*

CCITT Recommendation V.26 : 1989, *2 400 bits per second modem standardized for use on 4-wire leased telephone-type circuits.*

1) International Telegraph and Telephone Consultative Committee.