

Australian Standard[®]

Aluminium ores — Sampling

**Part 6: Methods for checking the
bias of sampling**

This Australian Standard was prepared by Committee MN/3, Aluminium Ores. It was approved on behalf of the Council of Standards Australia on 8 October 1993 and published on 17 January 1994.

The following interests are represented on Committee MN/3:

Aluminium Development Council
CSIRO, Division of Mineral Products
CSIRO, Division of Mineral and Process Engineering
Department of Primary Industries and Energy

Additional interests participating in preparation of Standard:

Aluminium ore mining companies
Aluminium smelters
Producers of alumina
Producers of aluminium products
Superintending organization

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 88211.

Australian Standard[®]

Aluminium ores — Sampling

**Part 6: Methods for checking the
bias of sampling**

First published as AS 2806.6—1994.

PREFACE

This Standard was prepared by the Standards Australia Committee on Aluminium Ores, under the direction of the Multitechnics Standards Policy Board. It is Part 6 of the AS 2806 series of Standards on the sampling of aluminium ores. Other parts of this series are as follows:

- Part 1: Sampling procedures
- Part 3: Preparation of samples
- Part 4: Determination of heterogeneity of constitution
- Part 5: Methods for checking the precision of sampling
- Part 7: Determination of quality variation

This Standard should be read in conjunction with other Standards in the series.

This Standard is technically equivalent to ISO 10226:1991, *Aluminium ores—Experimental methods for checking the bias of sampling*.

The term 'informative' has been used in this Standard to define the application of the Appendices to which it applies. An 'informative' appendix is for information and guidance only.

 CONTENTS

	<i>Page</i>
1 SCOPE	3
2 REFERENCED DOCUMENTS	3
3 GENERAL REQUIREMENTS	3
4 SAMPLING AND SAMPLE PREPARATION METHODS	4
5 ANALYSIS OF EXPERIMENTAL DATA	4
 APPENDIX A NUMERICAL EXAMPLES OF DETERMINING THE BIAS OF SAMPLING	 7

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

STANDARDS AUSTRALIA

Australian Standard

Aluminium ores—Sampling

Part 6: Methods for checking the bias of sampling

1 SCOPE This Standard specifies experimental methods for checking the bias of the sampling of aluminium ores, where the sampling is carried out in accordance with the methods specified in AS 2806.1. These methods may also be applied for checking the bias of sample preparation, where the sample preparation is carried out in accordance with the methods specified in AS 2806.3. These methods for analysing experimental data may also be applied for checking a possible significant difference in the result obtained from the samples of one lot collected at different places, for example, a loading point and a discharging point.

NOTE: Numerical examples of calculations are given in Appendix A.

2 REFERENCED DOCUMENTS The following documents are referred to in this Standard:

AS
2806 Aluminium ores—Sampling
2806.1 Part 1: Sampling procedures
2806.3 Part 3: Preparation of samples

3 GENERAL REQUIREMENTS In the methods specified in this Standard, the results obtained from the method to be checked for bias (referred to as Method B) are compared with the results of a reference method (referred to as Method A) which is considered to produce practically unbiased results from a technical and empirical viewpoints.

In the event that there is no statistically significant difference between the results obtained from Method B and those obtained from Method A, Method B may be adopted as a routine method.

NOTE: In this Standard, bias is assessed by application of the *t*-test (one-sided) at the 5% level of significance by determining whether the difference between the results of Method A and Method B are due to random chance variations, or whether the results are statistically different.

The number of paired sets of measurements (data sets) shall not be less than 20. The number of data sets required depends on the standard deviation of the differences based on 20 data sets and on the value of the bias, δ , to be detected as specified in Clause 5.

Any chemical or physical characteristic may be used. The most commonly used characteristics are alumina, moisture and silica content. Bias may not always be present for just one parameter; therefore several parameters, preferably all those that would subsequently be of interest, should be examined to determine whether bias exists. Characteristics to be tested need to be determined before the experiment begins.

Where increments for Method A and Method B can be taken from closely adjacent portions of the ore, it is recommended that sample preparation and testing be carried out on each increment individually. A comparison should never be made using combined data from increments, subsamples or gross samples.