

Australian Standard<sup>®</sup>

---

**Off-street parking**

**Part 2: Commercial vehicle  
facilities**

---

This Australian Standard was prepared by Committee CE/1, Off-street Parking Guidelines. It was approved on behalf of the Council of Standards Australia on 14 February 1989 and published on 14 April 1989.

---

The following interests are represented on Committee CE/1:

Australian Automobile Association  
Australian Council of Local Government Associations  
Australian Council of Local Government Engineers Associations  
Australian Road Transport Federation  
Bicycle Federation of Australia  
Building Owners and Managers Association of Australia  
Commercial Vehicle Industry Association of Australia  
Department of Health, New South Wales  
Department of Transport and Works  
Institution of Engineers, Australia  
Local Government Planners Association of New South Wales  
Monash University  
National Association of Australian State Road Authorities  
National Capital Development Commission  
National Parking Association  
Royal Australian Institute of Architects  
State Bicycle Advisory Committee, New South Wales  
Traffic Authority of New South Wales  
University of Queensland  
University of Sydney  
University of Wollongong  
Urban Transit Authority of New South Wales  
Western Australian Institute of Technology

Additional interests participating in preparation of this Standard:

Australian Road Research Board  
Traffic Engineering Services  
Central District Ambulance Service

---

**Review of Australian Standards.** To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

---

This Standard was issued in draft form for comment as DR 86092.

Australian Standard<sup>®</sup>

---

**Off-street parking**

**Part 2: Commercial vehicle  
facilities**

---

First published as AS 2890.2—1989.

PUBLISHED BY STANDARDS AUSTRALIA  
(STANDARDS ASSOCIATION OF AUSTRALIA)  
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 5535 1

## PREFACE

This Standard was prepared by Standards Australia's Committee on Off-street Parking Guidelines.

This is Part 2 of the AS 2890 series which covers the design of off-street parking areas for motor vehicles including light vehicles and motorcycles, commercial vehicles and buses. Other Standards in the series deal with car parking and bus facilities.

In determination of the turning paths of vehicles, reference was made to the following publications:

- (a) Vaughan, Rodney G and Sims, Arthur G. *Determination of Swept Paths of Vehicles*, Traffic Accident Research Unit, Department of Motor Transport, New South Wales, Report No 3/70, July 1970.
- (b) Hill, G.J. 'Prediction of Vehicle Swept Paths', *The Highway Engineer*, December 1978.
- (c) Green, P.N. 'Simulation of Vehicle Manoeuvres', *The Journal of the Institution of Highway Engineers*, July 1980.

Reference was also made to the *Australian Design Rules for Motor Vehicles and Trailers* (3rd edition), issued by the Federal Department of Transport and published under the auspices of Australian Transport Advisory Council (ATAC). Acknowledgment is made of the assistance received from the above sources.

## CONTENTS

	<i>Page</i>
<b>SECTION 1. SCOPE AND GENERAL</b>	
1.1 SCOPE .....	3
1.2 APPLICATION .....	3
1.3 DEFINITIONS .....	3
<b>SECTION 2. DESIGN CRITERIA</b>	
2.1 GENERAL .....	5
2.2 CLASS OF COMMERCIAL VEHICLES .....	5
2.3 DESIGN VEHICLE DIMENSIONS .....	5
2.4 SERVICE AREA DIMENSIONS .....	6
2.5 MULTIBAY SERVICE AREAS .....	6
2.6 INTERNAL ROADS .....	7
2.7 GRADIENTS IN SERVICE AREAS .....	7
2.8 CLEARANCES AROUND COMMERCIAL VEHICLES .....	8
2.9 HEIGHT LIMITS .....	8
2.10 DESIGN TEMPLATES .....	8
<b>SECTION 3. ACCESS DRIVEWAYS TO OFF-STREET PARKING AREAS</b>	
3.1 GENERAL .....	9
3.2 LOCATION PRINCIPLES .....	9
3.3 ACCESS DRIVEWAY DIMENSIONS .....	9
<b>APPENDICES</b>	
A DESIGN VEHICLE CHARACTERISTICS .....	11
B TEMPLATES FOR DESIGN VEHICLES .....	14

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

## STANDARDS AUSTRALIA

**Australian Standard**  
**Off-street parking**

**Part 2: Commercial vehicle facilities**

**SECTION 1. SCOPE AND GENERAL**

**1.1 SCOPE.** This Standard sets out the minimum requirements for the layout of off-street parking facilities for the loading and unloading of commercial vehicles.

**NOTES:**

1. The requirements specified in this Standard may be varied in order to comply with the requirements of the determining Authority or dependent upon circumstances applicable to a particular development (e.g. road frontage type, access to the development, and intensity of development and its use).
2. The design vehicle characteristics and use of vehicle types are described in Appendix A.

**1.2 APPLICATION.** This Standard shall be applied in the design of off-street parking facilities for commercial vehicles whether they are surface areas or multistorey.

**1.3 DEFINITIONS.** For the purpose of this Standard, the definitions given in the 'Australian Design Rules (ADRs) for Motor Vehicles and Trailers' and those below apply.

**1.3.1 Apron**—the manoeuvring area in front of the loading dock including the service bay (see Figure 1.1).

**1.3.2 Apron extent**—distance past the last service bay required for manoeuvring parallel to the dock (see Figure 1.1).

**1.3.3 Apron width**—distance between the loading dock and furthest forward manoeuvring point, and is made up of two distinct dimensions: the entry clearance and the bay length (see Figure 1.1).

**1.3.4 Bay length**—overall length of the service bay (see Figure 1.1).

**1.3.5 Driveway**—crossing of a footpath or public area to join the carriageway and the service area at the property line.

**1.3.6 Entry angle**—the angle through which a design vehicle turns before commencing the reverse manoeuvre.

**1.3.7 Entry clearance**—distance between the vehicle entry path (near side) and the point furthest from the service bay reached during the forward manoeuvre (see Figure 1.1).

**1.3.8 Loading dock**—specific area set aside for loading and unloading a commercial vehicle. Commonly the operation is carried out from a raised platform to which the vehicle is backed. Loading and unloading can, however, take place from the side or from ground level.

**1.3.9 Minimum apron width**—distance between the furthest point reached during the forward manoeuvre and the first position at which vehicle is aligned parallel to the service bay ready for reversing to the final position against the dock (see Figure 1.1). If the vehicle is allowed to protrude into the manoeuvring area of the vehicles, this is the furthest forward the loading dock can be placed.

**1.3.10 Service area**—the area in a development set aside for the manoeuvring, laybye and loading or unloading of commercial vehicles for the delivery of goods or freight.

**1.3.11 Service bay**—specific area in a loading dock which is delineated for the vehicle. When a service bay is of minimum dimensions a vehicle has to place the body or trailer into its final alignment at the point of entry into the bay. As the width of the service bay is widened, the additional clearance may be used for the final alignment of the vehicle to penetrate into the service bay thus reducing the required width of pavement.