

Australian/New Zealand Standard™

Damp-proof courses and flashings



AS/NZS 2904:1995

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee BD-029, Damp-proof Courses and Flashings. It was approved on behalf of the Council of Standards Australia on 4 August 1995 and on behalf of the Council of Standards New Zealand on 14 August 1995. This Standard was published on 5 November 1995.

The following are represented on Committee BD-029:

Aluminium Development Council (Australia)
Auckland Manufacturers Association
Australian Chamber of Commerce and Industry
Australian Institute of Building Surveyors
Australian Institute of Building
Clay Brick and Paver Institute (Australia)
Concrete Masonry Association of Australia
Department of Local Government and Co-operatives (Australia)
Master Plumbers and Mechanical Services Association of Victoria
Metal DPC Manufacturers (Australia)
Plastics and Chemicals Industry Association (Australia)
Royal Australian Institute of Architects

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Web Shop at www.saiglobal.com.au or Standards New Zealand website at www.standards.co.nz and looking up the relevant Standard in the on-line catalogue.

For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia or Standards New Zealand at the address shown on the back cover.

This Standard was issued in draft form for comment as DR 94170 (in part).

Australian/New Zealand Standard[™]

Damp-proof courses and flashings

Originally published in Australia as part of SAA Int. 326—1953 and SAA Int. 327—1953.
Previous edition AS 2904—1986.
Originally revised in part and designated AS/NZS 2904:1995.
Reissued incorporating Amendment No. 1 (March 1998).
Reissued incorporating Amendment No. 2 (February 2013).

COPYRIGHT

© Standards Australia Limited/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Australia) or the Copyright Act 1994 (New Zealand).

Jointly published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001 and by Standards New Zealand, Private Bag 2439, Wellington 6140.

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee BD-029, Damp-proof Courses and Flashings, to supersede AS 2904—1986. It is issued as a Joint Standard.

This Standard incorporates Amendment No. 1 (March 1995) and Amendment No 2 (February 2013). The changes required by the Amendment are indicated in the text by a marginal bar and amendment number against the clause, note, table, figure or part thereof affected.

- A2 | This Standard does not cover mortar-type damp-proof courses as these are covered in AS 3700, *Masonry structures*, and AS 4773.2, *Masonry in small buildings*, Part 2: *Construction*.

The Standard includes performance requirements and a list of commonly used materials deemed to be satisfactory. The Committee examined the range of damp-proof courses and flashings in common use. Since these materials have proved to be quite satisfactory for a long period of time, it seemed unreasonable that they should have to demonstrate full compliance with a set of performance requirements aimed primarily at new products.

There are five groups of materials in current use, viz. metals, bitumen-coated metals, polyethylene coated metals, bitumen-impregnated materials, and polyethylene. These are fully specified in this Standard together with relevant tests and any limitations on their use.

- A1 | The performance requirements are based on the appropriate test methods from previous Standards, updated and metricated. An impact test originally used for polyethylene has been applied to all damp-proof courses and flashings to provide a suitable level of robustness.

The 'deemed to satisfy' provisions are specific to the materials detailed in Clause 7 of the Standard. Products not complying with these minimum manufacturing requirements would require full assessment of performance in the same way as any new material or combination of materials. New materials or combinations may require additional criteria of acceptance and this would be considered in future editions of the Standard.

The objective of this Standard is to provide manufacturers and users of damp-proof courses and flashings with specifications covering the manufacturer and performance of damp-proof courses and flashings for use in building applications.

CONTENTS

	<i>Page</i>
1 SCOPE.....	4
2 NEW MATERIALS.....	4
3 REFERENCED DOCUMENTS.....	4
4 DEFINITIONS.....	5
5 GENERAL REQUIREMENTS.....	5
6 PERFORMANCE REQUIREMENTS.....	7
7 MATERIALS DEEMED TO BE SATISFACTORY.....	9
8 PACKING AND MARKING.....	13

APPENDICES

A MEANS FOR DEMONSTRATING COMPLIANCE WITH THIS STANDARD.....	14
B ROLL LABELLING.....	16

STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Australian/New Zealand Standard
Damp-proof courses and flashings

1 SCOPE

This Standard specifies requirements for damp-proof course and flashing materials of the sheet membrane, strip and collar type for use in building construction.

NOTES:

- A2 | 1 For mortar-type damp-proof courses, see AS 3700 and AS 4773.2. This Standard does not include vapour barriers.
- 2 Alternative methods for determining compliance with this Standard are given in Appendix A.

2 NEW MATERIALS

This Standard shall not be interpreted as preventing the use of materials that meet the performance requirements set out in the Standard, but are not specifically referred to herein.

3 REFERENCED DOCUMENTS

The following documents are referred to in this Standard:

	AS	
	1199	Sampling procedures and tables for inspection by attributes
A2	1397	Continuous hot-dip metallic coated steel sheet and strip—Coatings of zinc and zinc alloyed with aluminium and magnesium
	1399	Guide to AS 1199—Sampling procedures and tables for inspection by attributes
	1463	Polyethylene pipe extrusion compounds
	1566	Copper and copper alloys—Rolled flat products
	1804	Soft lead sheet and strip
	2341	Methods of testing bitumen and related roadmaking products
	2341.8	Method 8: Determination of matter insoluble in toluene
	2341.12	Method 12: Determination of penetration of residual bitumen
	2341.18	Method 18: Determination of softening point of tar (ring and ball method)
A2	3700	Masonry structures
	4347	Damp-proof courses and flashings—Methods of test
	4347.1	Method 1: Determination of water permeability
	4347.2	Method 2: Determination of continuity of coating on metal centres
	4347.3	Method 3: Determination of pliability of bitumen coating on metal centres
	4347.4	Method 4: Determination of pliability—Materials with fabric or felt base
	4347.5	Method 5: Determination of compression properties
	4347.6	Method 6: Determining impact resistance
	4347.7	Method 7: Determination of thickness of bitumen coating and thickness or mass of metallic centre
	4347.8	Method 8: Preparation of coating bitumen for testing
	4347.9	Method 9: Determining thickness
	4347.10	Method 10: Determination of mass of desaturated base and percentage saturation