

Australian Standard[®]

**Wheelchair occupant restraint
assemblies for motor vehicles**

This Australian Standard was prepared by Committee ME/48, Restraint Systems in Vehicles. It was approved on behalf of the Council of Standards Australia on 4 February 1994 and published on 16 May 1994.

The following interests are represented on Committee ME/48:

ACROD
Australian Automobile Association
Federal Chamber of Commerce and Industries
Australian College of Rehabilitation Medicine
Commercial Vehicle Industry Association of Australia
Department of Transport and Communication
Department of Veterans Affairs
Federal Chamber of Automotive Industries
Federation of Automotive Products Manufacturers
Roads and Traffic Authority of N.S.W.
University of N.S.W.
Vic Roads

Additional interests participating in preparation of Standard:

Motor vehicle and restraint manufacturers
Regency Park Centre for Young Disabled (Adelaide)
Royal North Shore Hospital (Sydney)
Royal South Sydney Hospital
Spastic Society of Victoria
University of Adelaide

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

All details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 91161.

Australian Standard[®]

**Wheelchair occupant restraint
assemblies for motor vehicles**

First published as AS 2942—1987.
Second edition 1994.

Incorporating:
Amdt 1—1998

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 8813 6

PREFACE

This Standard was prepared by the Standards Australia Committee on Restraint Systems in Vehicles, to supersede AS 2942—1987.

Because the first edition of this Standard was rapidly accepted and adopted into legislation in most Australian States, more information is required to verify the acceptability of given wheelchair occupant restraint assembly 'kits' available for purchase, and the removal of some previously specified installation requirements that are now subject to vehicle registration authorities' specification and approval.

This edition differs from AS 2942—1987 in the following ways:

- (a) The marking requirements now include part numbers on each readily separable component or subassembly and, where alternative or additional components may be available, an indication of compatibility between components.
- (b) The packaging requirements now separately specify the information to be displayed externally to assist with selection of an appropriate assembly, and information to be contained within the packaging.
- (c) The intent of the instructions for use and for installation has been modified so that it is now required that this information be supplied as guidelines by the restraint manufacturer. However, it is not mandatory for the restraint manufacturer to ensure that these guidelines are adopted. Manufacturers of restraint assemblies are required, where practical, to design components so that incorrect use, orientation and restraint geometry is not possible.
- (d) The range of sizes and types of wheelchairs compatible with a restraint assembly is now fully specified within the Standard or, where a restriction to this range applies, by the restraint manufacturer. References to occupant garment sizes and thickness of cushions have been deleted.
- (e) The method of test for dynamic performance of restraints has been amended to improve clarity, and remove interpretations previously required. The positioning of restraint assembly mounting points on the test trolley has been more precisely specified.
- (f) 'Guidelines for vehicle reinforcement', previously Appendix C, has been deleted as more specific requirements are now necessary to meet some vehicle registration authority specifications.
- (g) 'Guidelines for vehicles used for transport of occupants in wheelchairs', previously Appendix D, has now been deleted as unnecessary. Advice on vehicles is obtainable from vehicle registration authorities.
- (h) 'Guidelines for wheelchairs used in vehicles', now Appendix A, has been amended as its recommendations were subject to misinterpretation, resulting in refusal to permit a wheelchair occupant to travel in a vehicle in their usual wheelchair.

It recognizes that a wheelchair that best serves the overall needs of its owner may not be ideal for restraint in motor vehicles, and that prohibiting the use of such wheelchairs in a vehicle is not practical despite some additional risks of injury.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the appendix to which they apply. A 'normative' appendix is an integral part of a Standard, whereas an 'informative' appendix is only for information and guidance.

CONTENTS

	<i>Page</i>
FOREWORD	4
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE	5
1.2 REFERENCED DOCUMENTS	5
1.3 DEFINITIONS	5
1.4 RESTRAINT TYPES	9
SECTION 2 DESIGN, CONSTRUCTION, AND TESTING	
2.1 GENERAL	10
2.2 WHEELCHAIR RESTRAINTS	10
2.3 OCCUPANT RESTRAINTS	12
2.4 WHEELCHAIR LOCATIONS	14
2.5 DETACHABLE RESTRAINTS	14
2.6 ASSEMBLY ADJUSTMENT	14
2.7 CORROSION PROTECTION	16
2.8 SURFACE FINISH	17
2.9 DYNAMIC PERFORMANCE REQUIREMENTS	17
SECTION 3 MARKING AND INSTRUCTIONS	
3.1 INSTALLATION INSTRUCTIONS	19
3.2 MARKING AND PACKAGING	20
3.3 INSTRUCTIONS FOR USE	21
SECTION 4 DETERMINATION OF CLEARSPACE REQUIREMENTS	
4.1 GENERAL	23
4.2 CLEARSPACE AROUND A WHEELCHAIR POSITION	23
4.3 SPACING BETWEEN ADJACENT RESTRAINT POSITIONS	23
APPENDICES	
A GUIDELINES FOR USE OF WHEELCHAIR OCCUPANT RESTRAINT ASSEMBLIES	26
B POTENTIAL FOR INADEQUATE RELEASE OF WHEELCHAIR RESTRAINT COMPONENTS	31
C POTENTIAL FOR PARTIAL ENGAGEMENT OF WHEELCHAIR RESTRAINT COMPONENTS	32
D POTENTIAL FOR WEBBING SLIPPAGE AT ADJUSTMENT DEVICE	33
E ANTHROPOMETRIC DATA	35
F METHOD OF TEST FOR DYNAMIC PERFORMANCE OF WHEELCHAIR OCCUPANT RESTRAINT ASSEMBLIES	36
G TEST SEAT	41
H EXAMPLE OF INSTRUCTIONS FOR INSTALLATION OF ANCHORAGE	43

FOREWORD

Wheelchair occupant restraint assemblies complying with this Standard will give protection in most accidents if they are properly installed and attached, and worn correctly. In general, wheelchairs are not well suited to the requirements of vehicular seating, and the safety of passengers is best assured by the use of normal passenger seats and seat belts. Wheelchair occupants should transfer to passenger seats in vehicles and use the seat belt provided whenever that is practicable, and unoccupied wheelchairs should be restrained.

Effective restraint for people occupying wheelchairs requires the wheelchair to be secured in the transporting vehicle, with the occupant restrained by a seat belt which itself is secured directly to the vehicle or to parts which are themselves secured to the vehicle. The wheelchair contributes to restraint of the occupant by virtue of the support provided by the wheelchair seat, backrest and armrests. The complete restraint for the occupant includes the wheelchair itself, i.e. includes restraints for the occupant and the wheelchair.

There are currently no recognized Standards covering wheelchairs suitable for vehicular seating, and, even if such Standards could be rapidly implemented, the problems of vehicular transport for people occupying non-complying wheelchairs would remain for many years. However, provided that suitable restraints are fitted, tests have shown that some types of wheelchairs can survive a severe impact without fractures of the frame.

This Standard specifies restraints for wheelchairs and their occupants and does not specify strength requirements for wheelchair structures or for vehicle structures used to anchor wheelchair occupant restraint assemblies. Rather, the manufacturer of wheelchair occupant restraint assemblies is required to provide details of strength requirements at the anchorage of a restraint assembly. Vehicle regulatory authorities require approval of restraint installation, and should be consulted for advice on reinforcement of vehicle structures at anchorages.

To allow for various applications, the Standard allows for designs that do not require any wheelchair modifications, those in which parts of the restraint assembly are fitted onto the wheelchair restraint assemblies, wheelchairs that incorporate a child safety seat complying with AS 1754 *Child restraint systems for use in motor vehicles*, and wheelchair frames manufactured with integral restraint components.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

STANDARDS AUSTRALIA

Australian Standard

Wheelchair occupant restraint assemblies for motor vehicles

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE This Standard specifies requirements for restraint assemblies for commonly available manual and electric wheelchairs and their occupants in motor vehicles.

This Standard does not apply to the restraint of wheelchair occupants who are driving a vehicle.

NOTES:

- 1 It is a requirement of most States and Territories that their vehicle registration authorities approve the installation of a wheelchair occupant restraint assembly.
- 2 Appendix A gives guidelines for wheelchairs for use in vehicles.

1.2 REFERENCED DOCUMENTS The following documents are referenced in this Standard:

AS

1753 Webbing for restraining devices for occupants of motor vehicles

AS/NZS

1754 Child restraint systems for use in motor vehicles

2596 Seat belt assemblies for motor vehicles

4475 Restraint systems for motor vehicles—Performance tests

4475.1 Method 1: Determination of webbing durability in adjustment duty

4475.2 Method 2: Determination of webbing durability in withdrawing and retracting duty through a sash guide

4475.3 Method 3: Determination of fatigue resistance of a flexible member

4475.4 Method 4: Determination of adjustment device forces

4475.5 Method 5: Determination of locking angle of tilt-lock adjustment device

4475.6 Method 6: Determination of free-end device strength

ADR*

4 Seat belts

11 Internal sunrises

21 Instrument panel

1.3 DEFINITIONS For the purpose of this Standard, the definitions below apply.

1.3.1 Anchor fitting—the terminal part of an occupant restraint strap designed to transfer forces of restraint to the vehicle, or to the structure of the wheelchair restraint assembly.

1.3.2 Anchor point—the point where the centre-line of an occupant restraint strap passes into the anchor fitting or changes direction. For anchor fittings which are designed to pivot or are secured by a single bolt, the anchor point is the intersection of the axis of rotation, or the centre-line of the bolt, with the surface of the supporting structure. (See also Clause 1.3.20.)

1.3.3 Anchorage—that part of a vehicle designed to transfer loads from a wheelchair occupant restraint assembly to vehicle structure.

* Australian Design Rules for motor vehicles and trailers. This reference refers to the latest edition of the design rule, in place at the time this Standard is used.