



## Plastics pipes and fittings for gas reticulation

### Part 1: Polyamide pipes

STANDARDS  
Australia

Currently in preview, click buy full version

This Australian Standard® was prepared by Committee PL-021, PVC, ABS and Polyamide Pipe Systems. It was approved on behalf of the Council of Standards Australia on 12 October 2007.

This Standard was published on 31 December 2007.

---

The following are represented on Committee PL-021:

- Australian Chamber of Commerce and Industry
  - Australian Nuclear Science and Technology Organisation
  - Certification Interests (Australia)
  - CSIRO Manufacturing and Infrastructure Technology
  - Energy Networks Association
  - Engineers Australia
  - New Zealand Local Government
  - Master Plumbers, Gasfitters and Drainlayers New Zealand
  - New Zealand Water and Waste Association
  - Plastics Industry Pipe Association of Australia
  - Plastics New Zealand
  - Water Services Association of Australia
- 

This Standard was issued in draft form for comment as DR 05468.

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Standard through their representation on the Committee and through the public comment period.

---

#### **Keeping Standards up-to-date**

Australian Standards® are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting [www.standards.org.au](http://www.standards.org.au)

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at [mail@standards.org.au](mailto:mail@standards.org.au), or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

---

Australian Standard®

**Plastics pipes and fittings for gas  
reticulation**

**Part 1: Polyamide pipes**

Originally as AS 2944.1—1987.  
Second edition 2007.  
Revised incorporating Amendment No. 1 (November 2018).

**COPYRIGHT**

© Standards Australia Limited

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968.

Published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001, Australia

ISBN 0 7337 8479 8

## PREFACE

This Australian Standard was prepared by the Australian members of the Joint Standards Australia/Standards New Zealand Committee PL-021, PVC, ABS and Polyamide Pipe Systems to supersede AS 2944.1—1987. After consultation with stakeholders in both countries, Standards Australia and Standards New Zealand decided to develop this Standard as an Australian Standard rather than an Australian/New Zealand Standard.

*This Standard incorporates Amendment No. 1 (November 2018). The changes required by the Amendment are indicated in the text by a marginal bar and amendment number against the clause, note, table, figure or part thereof affected.*

This Standard complements AS 2944.2, *Plastics pipes and fittings for gas reticulation — Part 2: Polyamide Fittings* and AS 2943, *Plastics pipes and fittings for gas reticulation — Polyamide compounds*.

The objective of this Standard is to provide minimum requirements for the manufacture and performance of polyamide pipes for pressure applications for use by manufacturers, specifiers and purchasers of these products.

In the preparation of this Standard, consideration has been given to international best practice.

The test criteria specified apply to pipes at the time of manufacture. Pipes which have been in service, might not meet the same performance requirements.

The term ‘normative’ has been used in this Standard to define the application of the appendix to which it applies. A ‘normative’ appendix is an integral part of a Standard.

Statements expressed in mandatory terms in notes to tables and figures are deemed to be requirements of this Standard. Notes to text are for information and guidance only.

## CONTENTS

	<i>Page</i>
1 SCOPE.....	5
2 REFERENCED DOCUMENTS.....	5
3 DEFINITIONS.....	5
4 NOTATION.....	6
5 CLASSIFICATION.....	6
6 COMPOSITION.....	6
7 DIAMETER AND WALL THICKNESS.....	6
8 LENGTH.....	7
9 FREEDOM FROM DEFECTS.....	7
10 TEST REQUIREMENTS.....	8
11 MARKING.....	9
 APPENDICES	
A MEANS FOR DEMONSTRATING COMPLIANCE WITH THIS STANDARD .....	10
B METHOD FOR DETERMINING DEFECTS.....	13
C METHOD OF TEST FOR SQUEEZE-OFF PROPERTIES OF PIPE.....	15

## FOREWORD

In this Standard, to determine the nominal pressure class for both PA11 and PA12 pipes, the service (design) co-efficient of (C) with a minimum value of 3.0 is used (refer to 97.5% LPL).

Wall thicknesses for the pipes specified have been calculated from formulas that take into account the hydrostatic design stress of the material and working pressure and diameter of the pipes, however, the wall thickness of some pipes in this Standard has been increased in order to sustain envisaged soil loadings. In the interests of serviceability of the pipes and irrespective of the calculated minimum wall thickness, this Standard does not provide for a wall thickness of less than 1.0 mm.

For special applications, the design wall thickness of pipes can be calculated from the following formula for use at service pressures up to and including 575 kPa at temperatures in the range  $-20^{\circ}\text{C}$  to  $+35^{\circ}\text{C}$ :

$$T_{\min} = \frac{PD_{\text{m}}}{2S + P} \quad T_{\min} = \frac{PD_{\text{m max}}}{2S + P}$$

where

- $P$  = design pressure of pipe, in kilopascals
- $D_{\text{m max}}$  = maximum mean outside diameter of pipe, in millimetres
- $T_{\min}$  = minimum wall thickness of pipe, in millimetres
- $S$  = hydrostatic design stress at  $23^{\circ}\text{C}$  or 1000 kPa

## STANDARDS AUSTRALIA

### Australian Standard Plastics pipes and fittings for gas reticulation

#### Part 1: Polyamide pipes

#### 1 SCOPE

This Standard specifies requirements for polyamide pipes for use in gas mains and services for direct burial and reliner applications. Such pipes are intended for use in the distribution of natural gas, manufactured gas, liquefied petroleum gas (LPG) and LPG/air mixtures at pressures up to 400 kPa.

#### 2 APPLICATION

Determination of compliance with this Standard shall be in accordance with Appendix A.

#### 3 REFERENCED DOCUMENTS

The following documents are referred to in this Standard:

AS

1199 Sampling procedures for inspection by attributes  
1199.1 Part 1: Sampling schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection

2943 Plastics pipes and fittings for gas reticulation—Polyamide compounds

AS/NZS

1462 Methods of test for plastics pipes and fittings  
1462.1 Part 1: Method for determining the dimensioning of pipes and fittings  
1462.3 Part 3: Method for determining the impact characteristics of pipes  
1462.6 Part 6: Method for hydrostatic pressure testing of pipes

A1

AS ISO/IEC

17025 General requirements for the competence of testing and calibration laboratories

HB

18 Conformity assessment  
18.28 Guide 28: Guidance on a third-party certification system for products

#### 4 DEFINITIONS

For the purpose of this Standard, the definitions below apply.

##### 4.1 Hoop stress

Stress in a pipe under pressure acting tangentially to the perimeter of a transverse section.

##### 4.2 Hydrostatic design strength

Estimated hoop stress, due to internal hydrostatic pressure, that can be applied continuously at a specified temperature with a high degree of certainty that failure will not occur. It is obtained by the application of a safety factor to the extrapolated 50-year long-term hydrostatic strength value.