



Standards

Association of

Australia



Australian Standard[®]
2979—1987

TRAFFIC SIGNAL MAST ARMS



This Australian Standard was prepared by Committee LG/6, Road Traffic Signals. It was approved on behalf of the Council of the Standards Association of Australia on 30 April 1987 and published on 6 July 1987.

The following interests are represented on Committee LG/6:

Australian Electrical and Electronic Manufacturers Association
Australian Road Research Board
Confederation of Australian Industry
Department of Territories (Commonwealth)
Department of Transport (Commonwealth)
Metal Trades Industry Association of Australia
National Association of Australian State Road Authorities
Railways of Australia Committee
State Traffic Authorities
The University of Melbourne, Department of Geography
The University of New South Wales, Department of Transport Engineering

Representatives of the manufacturers of traffic signal mast arms also participated in the drafting of this Standard.

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up-to-date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all SAA publications will be found in the Catalogue of SAA Publications; this information is supplemented each month by SAA's journal 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of the Association, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 86022.

AUSTRALIAN STANDARD


TRAFFIC SIGNAL MAST ARMS

AS 2979—1987

First published 1987

**PUBLISHED BY THE STANDARDS ASSOCIATION OF AUSTRALIA
STANDARDS HOUSE, 80 ARTHUR ST, NORTH SYDNEY, N.S.W.**

ISBN 0 7262 4674 3



PREFACE

This Standard was prepared by the Association's Committee on Road Traffic Signals and is one of a group of Standards which set out requirements for the equipment associated with traffic signal installations, viz:

- AS 2144 Traffic Signal Lanterns.
- AS 2339 Traffic Signal Posts and Attachments.
- AS 2353 Pedestrian Push-button Assemblies.
- AS 2578 Traffic Signal Controllers.
Part 1—Physical and Electrical Compatibility.
- AS 2703 Vehicle Loop Detector Sensors.
- AS 2979 Traffic Signal Mast Arms. (This Standard.)

This Standard applies to the following basic categories of traffic signal mast arms:

- (a) Traffic signal mast arms which are used principally for the support of traffic signal lanterns (known as mast arms).
- (b) Traffic signal mast arms which, as well as providing for the support of traffic signal lanterns, are also used to support road lighting luminaires (known as joint-use mast arms).

The Standard designates three specific types of traffic signal mast arm, viz Types A, B and C, based on design and constructional considerations. Each of the designated types is applicable to the basic categories of traffic signal mast arm described in (a) and (b) above. The design and constructional differences which apply for the three designated types of traffic signal mast arm are intended to provide for—

- (i) different practices in the termination of traffic signal and public lighting cables; and
- (ii) different design wind velocities to cater for conditions in various geographic regions.

Whilst slip-base and impact absorbing street lighting columns are available, no comparable designs exist for traffic signal mast arms because of the different performance requirements which apply, especially the significant torsional loads that they must withstand.

© Copyright — STANDARDS ASSOCIATION OF AUSTRALIA 1987

Users of Standards are reminded that copyright subsists in all SAA publications. No part of this publication may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing of the Standards Association of Australia.

CONTENTS

	<i>Page</i>
SECTION 1. SCOPE AND GENERAL	
1.1 SCOPE	4
1.2 OBJECTIVES	4
1.3 REFERENCED DOCUMENTS	4
1.4 DEFINITIONS	4
1.5 TYPE DESIGNATIONS	4
SECTION 2. REQUIREMENTS FOR MAST ARMS	
2.1 GENERAL FORM AND CONSTRUCTION	6
2.2 STRUCTURAL REQUIREMENTS	6
2.3 PHYSICAL ARRANGEMENT AND DIMENSIONS	6
2.4 PROVISION FOR TRAFFIC SIGNAL CABLES	6
2.5 FINISH	7
2.6 PROVISION FOR ASSEMBLY	7
2.7 MARKING AND INSTRUCTIONS	7
SECTION 3. REQUIREMENTS FOR JOINT-USE MAST ARMS	
3.1 APPLICATION	18
3.2 STRUCTURAL REQUIREMENTS	18
3.3 PHYSICAL ARRANGEMENT AND DIMENSIONS	18
3.4 PROVISION FOR PUBLIC LIGHTING CABLES	18
APPENDIX A. INFORMATION TO BE PROVIDED WITH ENQUIRY OR ORDER	20

STANDARDS ASSOCIATION OF AUSTRALIA

Australian Standard
TRAFFIC SIGNAL MAST ARMS

SECTION 1. SCOPE AND GENERAL

1.1 SCOPE. This Standard sets out requirements for traffic signal mast arms which are designed to support traffic signal lanterns and associated equipment above the roadway. It applies to—

- (a) traffic signal mast arms, as defined in Clause 1.4.1; and
- (b) joint-use mast arms, as defined in Clause 1.4.2.

The Standard does not specify details of design except insofar as these matters are controlled by the specified requirements.

The Standard does not apply to traffic signal posts (see AS 2339), nor to the installation of mast arms and their foundations.

NOTE: See Appendix A for the information which should be supplied with an enquiry or order for mast arms to this Standard.

1.2 OBJECTIVES. The objectives of the Standard are to—

- (a) ensure that mast arms will present a reasonably uniform appearance to road users;
- (b) provide for rationalization in the range of sizes required and in the functional performance requirements; and
- (c) provide for uniformity in the fixings and attachments used.

1.3 REFERENCED DOCUMENTS. The following Standards are referred to in this Standard:

- AS 1170 SAA Loading Code. Part 2: Wind Forces
- AS 1250 SAA Steel Structures Code.
- AS 1650 Galvanized Coatings
- AS 1798 Preferred Dimensions of Lighting Columns and Bracket Arms.
- AS 2144 Traffic Signal Lanterns.
- AS 2339 Traffic Signal Posts and Attachments.
- AS 2353 Pedestrian Push-button Assemblies.
- AAS. TC Standard Specifications for Structural Supports for Highway Signs, Luminaires and Traffic Signals.

4 DEFINITIONS. For the purpose of this Standard, the definitions given in AS 1798, AS 2144 and those below apply.

1.4.1 Traffic signal mast arm—a free standing structure comprising a vertical section and outreach arm used for the support of traffic signal lanterns and associated equipment.

NOTE: Throughout this Standard traffic signal mast arms are referred to as 'mast arms'.

1.4.2 Joint-use mast arms—a mast arm which incorporates a lighting outreach assembly for the support of a street lighting luminaire(s). It combines the functions of a traffic signal mast arm and street lighting column.

1.4.3 Nominal height—the vertical distance between the bottom of the baseplate and the lowest point of the overhead lantern mounting assembly when loaded as specified in Clause 2.2.4.1(b).

NOTE: See AS 1798 for the definition of nominal height for street lighting columns.

1.4.4 Mast-arm projection—the horizontal distance between a vertical line through the centre of the baseplate and the angle plate to which the overhead lantern mounting assembly is attached.

NOTE: See AS 1798 for the definition of 'arm projection' for street lighting columns.

1.4.5 Overhead lantern mounting assembly—a luminaire, attached at the extremity of the outreach arm, which is designed for the mounting of traffic signal lanterns.

1.4.6 Column lantern fixings—attachments provided on the vertical section of the mast arm which are designed for the mounting of traffic signal lanterns.

1.5 TYPE DESIGNATIONS. For the purpose of this Standard, mast arms and joint-use mast arms shall be designated Type A, Type B or Type C in accordance with the following:

- (a) *Type A.* Type A mast arms and Type A joint-use mast arms shall—
 - (i) be designed on the basis of a design wind velocity of 40 m/s;
 - (ii) incorporate facilities for terminating traffic signal cables within the vertical section; and
 - (iii) provide for mounting on a baseplate using four bolts equally spaced on a pitch circle diameter of 350 mm.
- (b) *Type B.* Type B mast arms and Type B joint-use mast arms shall—
 - (i) be designed on the basis of a design wind velocity of 45 m/s;
 - (ii) incorporate facilities for terminating traffic signal cables in an externally mounted junction box; and
 - (iii) provide for mounting on a baseplate using four bolts equally spaced on a pitch circle diameter of 500 mm.

* American Association of State Highway and Transportation Officials, 341 National Press Building, Washington D.C., USA.