

Australian Standard™

**Workplace air quality—Sampling and
analysis of volatile organic compounds
by solvent desorption/gas
chromatography**

Part 2: Diffusive sampling method

This Australian Standard was prepared by Committee CH-031, Methods for the Examination of Workplace Atmospheres. It was approved on behalf of the Council of Standards Australia on 3 November 2003 and published on 24 December 2003.

The following are represented on Committee CH-031:

Australian Aluminium Council
Australian Chamber of Commerce and Industry
Australian Institute of Occupational Hygienists
Australian Mines and Metals Association
Bureau of Steel Manufacturers of Australia
Clean Air Society of Australia & New Zealand
Coal Services
Commonwealth Department of Health and Aging
Department for Administrative and Information Services, S.A.
Department of Mineral Resources, N.S.W.
National Association of Testing Authorities, Australia
WorkCover New South Wales

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Australia web site at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Global Standard*, has a full listing of revisions and amendments published each month.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.com.au, or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001.

Australian Standard™

**Workplace air quality—Sampling and
analysis of volatile organic compounds
by solvent desorption/gas
chromatography**

Part 2: Diffusive sampling method

Originated as part of AS 2896—1987.
Revised and redesignated in part as AS 2986.2—2003.

COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd
GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 5621 2

PREFACE

This Standard was prepared by the Standards Australia Committee CH-031, Methods for Examination of Workplace Atmospheres, to supersede, in part, AS 2986—1987, *Workplace atmospheres—Organic vapours—Sampling by solid absorption techniques*.

This Standard is identical with and has been reproduced from ISO 16200-2:2000, *Workplace air quality—Sampling and analysis of volatile organic compounds by solvent desorption/gas chromatography*, Part 2: *Diffusive sampling method*.

The objective of this Standard is to provide a method for sampling, using a personal pump and analysis of organic compounds by gas chromatography in workplace atmospheres.

As this Standard is reproduced from an International Standard, the following applies:

- (a) Its number appears on the cover and title page while the International Standard number appears only on the cover.
- (b) In the source text, ‘this part of ISO 16200’ should read ‘this Australian Standard’.
- (c) A full point should be substituted for a comma when referring to a decimal marker.

None of the documents referenced in this Standard have been adopted as Australian Standards.

This Standard is Part 2 of the following series:

AS

- | | |
|--------|--|
| 2986 | Workplace air quality—Sampling and analysis of volatile organic compounds by solvent desorption/gas chromatography |
| 2986.1 | Part 1: Pumped sampling method |
| 2986.2 | Part 2: Diffusive sampling method |

The Committee acknowledges advice from NATA (National Association of Testing Authorities) that, in Australia, some clauses in this Standard, which are given as advisory, are mandatory requirements for laboratories seeking NATA accreditation. Specifically:

- (i) Clause 4.4.1: Traceability of calibration blend solutions to national or international Standards is a NATA requirement.
- (ii) Clause 6: Preparation of field blanks is a NATA requirement.
- (iii) Clause 10: Estimations of uncertainty are required by NATA to be prepared in accordance with the principles of ISO GUM.*

The term ‘informative’ has been used in this Standard to define the application of the annex to which it applies. An ‘informative’ appendix is only for information and guidance.

* ‘Guide to the Expression of Uncertainty in Measurement’ issued by BIPM, IEC, IFCC, ISO, IUPAC, IUPAP and OIML, Geneva, 1993.

CONTENTS

1	Scope	1
2	Normative references	1
3	Principle	1
4	Reagents and materials	2
5	Apparatus	4
6	Sampling	5
7	Procedure	6
7.1	Desorption	6
7.2	Analysis	6
7.3	Determination of desorption efficiency	6
7.4	Calibration of uptake rate	7
8	Calculations	8
8.1	General	8
8.2	Mass concentration of analyte	8
8.3	Volume concentration of analyte	9
8.4	Uptake rates	9
9	Interferences	9
10	Precision and bias	9
11	Storage and transport	10
12	Test report	10
13	Quality control	10
	Annex A (informative) Description of sorbent types	11
	Annex B (informative) Diffusive sampling rates (cm³/min)	12
	Annex C (informative) Equivalence of gas chromatographic stationary phases	20
	Annex D (informative) Suppliers of charcoal-based organic vapour diffusive samplers	21
	Annex E (informative) Specific information on sampler type A	22
	Annex F (informative) Specific information on sampler type B	23
	Annex G (informative) Specific information on sampler type C	24
	Annex H (informative) Specific information on sampler type D	25
	Annex I (informative) Specific information on sampler type E	26
	Annex J (informative) Retention indices of selected VOCs on BP-1 and BP-10 phases	27
	Bibliography	31

Currently in preview, click buy full vers.

AUSTRALIAN STANDARD

Workplace air quality—Sampling and analysis of volatile organic compounds by solvent desorption/gas chromatography

Part 2:

Diffusive sampling method

1 Scope

This part of ISO 16200 gives general guidance for the sampling and analysis of volatile organic compounds (VOCs) in air.

This part of ISO 16200 is applicable to a wide range of VOCs, including hydrocarbons, halogenated hydrocarbons, esters, glycol ethers, ketones and alcohols. A number of devices and sorbents are recommended for the sampling of these VOCs, each sorbent having a different range of applicability.

NOTE Activated coconut shell charcoal is frequently used. Very polar compounds may require derivatization; very low boiling compounds will only be partially retained by the sorbents and can only be estimated qualitatively. Semi-volatile compounds will be fully retained by the sorbents, but may only be partially recovered.

This part of ISO 16200 is valid for the measurement of airborne vapours of VOCs in a concentration range of approximately 1 mg/m³ to 1000 mg/m³ individual organic for an exposure time of 8 h.

The upper limit of the useful range is set by the sorptive capacity of the sorbent used and, subject to dilution of the analysed solution, by the linear dynamic range of the gas chromatograph column and detector or by the sample splitting capability of the analytical instrumentation used. The lower limit of the useful range depends on the noise level of the detector and on blank levels of analyte and/or interfering artefacts on the sampling devices or in the desorption solvent. Artefacts are typically sub-microgram for activated charcoal, but higher levels of aromatic hydrocarbons have been noted in some batches.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of ISO 16200. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties in agreements based on this part of ISO 16200 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

EN 838:1995, *Workplace atmospheres — Diffusive samplers for the determination of gases and vapours — Requirements and test methods*.

EN 1540, *Workplace atmospheres — Terminology*.

3 Principle

Diffusive samplers consist of a sorbent separated from ambient air by some form of diffusion resistance, commonly a controlled air gap and draught shield. The diffusive sampler (or samplers) is exposed to air for a measured time