

Australian Standard[®]

**Electrical installations—Surface
mines and associated processing
plant**

**Part 2: General protection
requirements**

This Australian standard was prepared by Committee EL/33, Electrical Installations for Outdoor Sites Under Heavy Conditions (Including Open-cast Mines and Quarries). It was approved on behalf of the Council of the Standards Association of Australia on 27 February 1987 and published on 4 May 1987.

The following interests are represented on Committee EL/33:

Association of Consulting Engineers Australia
Australian Electrical and Electronic Manufacturers Association
Australian Institute of Mining and Metallurgy
Confederation of Australian Industry
Department of Industrial Relations, N.S.W.
Department of Mines, Qld
Department of Mines, Tas.
Electricity Supply Association of Australia
Mining Interests

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review, and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 85325.

Australian Standard[®]

**Electrical installations—Surface
mines and associated processing
plant**

**Part 2: General protection
requirements**

First published	1982
Second edition	1987

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 4614 X

PREFACE

This standard was prepared by the Association's Committee on Electrical Installations for Outdoor Sites Under Heavy Conditions (including Open-cast Mines and Quarries) to supersede AS 3007, Part 2—1982.

It is essentially identical with IEC 621-2, as supplemented by IEC 621-2A, which were prepared by the corresponding IEC Technical Committee, i.e. TC 71. The alterations incorporated in this new edition stem primarily from several amendments to IEC 621-2 which have recently been published or which are in the final stages of preparation, viz:

- (a) Amendment No 1 (1984) — see Section 4 and Appendix B herein.
- (b) Amendment No 2 (1986) — see Clause 2 and Table 2 herein.
- (c) A further amendment, in course of publication, based on IEC Document 71(Central Office)34 — see Clause 7, Table 5 and Figs 1 to 4 herein.

Where this standard deviates technically from IEC 621-2 (including the amendments described above) by way of different or additional requirements, this is indicated by a rule in the margin against the clause, or part thereof, affected. A summary of such technical variations is given in the Annex.

The Australian Committee (EL/33) has actively participated in the work of IEC TC 71 which has as its objective the development of uniform and internationally acceptable rules for the safe use of electricity in open-cast mines, quarries, stockpiles and the like. Such applications present particularly onerous conditions for the electrical apparatus and systems, including continual alteration of the location of the apparatus and systems, extension of the operational area, and adverse environmental conditions. Because of the size of the plant and the need for mobility, supply is frequently at high voltage over long distances, by means of trailing cables. This should be compared with other industries where the electrical installations are generally fixed.

The AS 3007 series specifies requirements for the installation and operation of electrical apparatus and systems in the above mentioned locations, with the object of ensuring the safety of persons, livestock and property. AS 3007.1 outlines the scope of the AS 3007 series and provides definitions for some of the terms used. AS 3007.2 (this standard) specifies measures which are required for protection against electric shock in normal service from direct contact with live parts, for protection against electric shock from parts which may become live in the event of a fault (indirect contact), and for protection against the effects of overcurrents resulting from overload or short-circuit conditions. AS 3007.3 prescribes general requirements for equipment and ancillaries associated with the electrical installation. AS 3007.4 sets out the requirements which are specific to particular installations, together with exemptions from the general requirements of AS 3007.2 and 3, which apply for such installations. AS 3007.5 sets out the normal operating procedures which should be carried out to ensure the safety of personnel.

The AS 3007 series recognizes several types of power supply system and specifies the protective measures which are necessary for each system. Requirements for protection of persons from indirect contact (see Section 2 of this standard) are based on the concept of permissible voltage versus time limits, which take into account the pathophysiological effects of electric current passing through the human body, typical industry conditions, and the probability of persons being in contact with the plant. In this and other respects the AS 3007 series differs in approach from the practically evolved requirements of AS 3000, SAA Wiring Rules.

It will therefore be necessary for the regulatory authorities concerned to clearly delineate the respective areas of application for the AS 3007 series and for AS 3000.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows, and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

	<i>Page</i>
SCOPE OF PART	6
REFERENCED DOCUMENTS	6
SECTION 1. PROTECTION AGAINST DIRECT CONTACT	
1 GENERAL REQUIREMENTS	7
2 COMPLETE PROTECTION BY MEANS OF BARRIERS OR ENCLOSURES	7
3 COMPLETE PROTECTION BY INSULATION OF LIVE PARTS	9
4 PARTIAL PROTECTION BY PLACING LIVE PARTS OUT OF REACH	9
5 PARTIAL PROTECTION BY THE PROVISION OF OBSTACLES	9
6 MINIMUM DISTANCES TO BE OBSERVED IN OPERATING AND MAINTENANCE GANGWAYS FOR INDOOR INSTALLATIONS	9
7 MINIMUM CLEARANCES FOR OUTDOOR INSTALLATIONS	9
SECTION 2. PROTECTION AGAINST INDIRECT CONTACT — A.C.	
8 GENERAL	15
9 TN, TT AND IT SYSTEMS DESCRIPTION	16
10 PROTECTION MEASURES FOR TN SYSTEMS	16
11 PROTECTION MEASURES FOR TT SYSTEMS	22
12 PROTECTIVE MEASURES FOR IT SYSTEMS	22
13 REQUIREMENTS FOR EARTH FAULT CURRENT LIMITATION DEVICES ...	23
14 EARTHING ARRANGEMENTS AND PROTECTIVE CONDUCTORS	23
SECTION 3. PROTECTION AGAINST OVERCURRENT	
15 GENERAL RULE	29
16 NATURE OF PROTECTIVE DEVICES	29
17 AUTOMATIC INTERRUPTION-PROTECTION AGAINST OVERCURRENT DUE TO OVERLOAD	29
18 AUTOMATIC INTERRUPTION-PROTECTION AGAINST SHORT CIRCUIT	30
19 COORDINATION OF OVERLOAD AND SHORT-CIRCUIT PROTECTION	31
20 LIMITATION OF OVERCURRENT BY CHARACTERISTICS OF SUPPLY CIRCUIT	31
SECTION 4. SELECTION OF PROTECTIVE DEVICES AND PROTECTION SYSTEMS	
21 BASIC REQUIREMENTS	32
22 SELECTION PROCEDURE	32
23 DISCRIMINATION BETWEEN PROTECTIVE DEVICES	32
APPENDICES	
A SELECTION OF FACTOR k FOR CALCULATING THE MINIMUM CROSS-SECTIONAL AREA OF PROTECTIVE CONDUCTORS	35
B DESCRIPTION OF CERTAIN TYPES OF PROTECTIVE DEVICES AND THEIR USES	37
ANNEX. SUMMARY OF TECHNICAL DEVIATIONS BETWEEN THIS STANDARD AND IEC 621-2	39

TABLES

1	MINIMUM CLEARANCES BETWEEN FIELD INSTALLED BARE CONDUCTORS AND BETWEEN SUCH CONDUCTORS AND EARTHED PARTS	7
2	RELATION BETWEEN DEGREES OF POLLUTION AND CREEPAGE DISTANCES	8
3	MINIMUM PROTECTION AGAINST DIRECT CONTACT BY BARRIERS OR ENCLOSURES (APPLICABLE TO LIVE PARTS ONLY)	10
4	MINIMUM DISTANCES TO BE OBSERVED IN OPERATING AND MAINTENANCE GANGWAYS FOR INDOOR INSTALLATIONS	11
5	MINIMUM CLEARANCES FOR FIELD-INSTALLED BARE LIVE PARTS IN OUTDOOR INSTALLATIONS	12
6	PROSPECTIVE TOUCH VOLTAGE/OPERATING TIME CHARACTERISTICS FOR SYSTEMS UP TO AND INCLUDING 1000 V	15
7	PROSPECTIVE TOUCH VOLTAGE/OPERATING TIME CHARACTERISTICS FOR SYSTEMS ABOVE 1000 V	15
8	MINIMUM SIZE OF EARTHING CONDUCTORS	24
9	SELECTION OF MINIMUM CROSS-SECTIONAL AREA FOR PROTECTIVE CONDUCTORS	27
10	MINIMUM CROSS-SECTIONAL AREA OF AERIAL AND SUSPENDED PROTECTIVE CONDUCTORS	27
11	MINIMUM CROSS-SECTIONAL AREA OF SUPPLEMENTARY EQUIPOTENTIAL BONDING CONDUCTORS	28
12	SUMMARY OF CRITERIA FOR PROTECTION AGAINST INDIRECT CONTACT AND PROTECTIVE DEVICES OR PROTECTIVE MEASURES WHICH MAY BE USED	33
13	VALUES OF FACTOR k FOR CALCULATING THE MINIMUM CROSS-SECTIONAL AREA OF PROTECTIVE CONDUCTORS	35
14	SUGGESTED INITIAL AND FINAL TEMPERATURES FOR PROTECTIVE CONDUCTORS	36

FIGURES

1	CLEARANCES FROM LIVE PARTS AT THE OUTER BOUNDARY FENCE ...	13
2	MINIMUM HEIGHT OF LIVE PARTS ABOVE ACCESSIBLE AREAS IN OUTDOOR INSTALLATIONS	13
3	CLEARANCES FROM LIVE PARTS FOR OUTDOOR INSTALLATIONS WITH VOLTAGES UP TO AND INCLUDING 30 kV	14
4	CLEARANCES FROM LIVE PARTS FOR OUTDOOR INSTALLATIONS WITH VOLTAGES ABOVE 30 kV	14
5	GRAPHICAL REPRESENTATION OF TABLE 6	17
6	GRAPHICAL REPRESENTATION OF TABLE 7	17
7	POWER SYSTEM TN WITH SEPARATE NEUTRAL AND PROTECTIVE CONDUCTORS THROUGHOUT THE SYSTEM	18
8	POWER SYSTEM TN WITH NEUTRAL AND PROTECTIVE FUNCTIONS COMBINED IN A SINGLE CONDUCTOR IN A PART OF THE SYSTEM	18
9	POWER SYSTEM TN WITH NEUTRAL AND PROTECTIVE FUNCTIONS COMBINED IN A SINGLE CONDUCTOR THROUGHOUT THE SYSTEM	19
10	POWER SYSTEM TT	19
11	POWER SYSTEM IT WITH INDEPENDENT EARTH ELECTRODES	20
12	POWER SYSTEM IT WITH COMMON EARTH ELECTRODE	20
13	POWER SYSTEM IT USING EXTERNAL TT OR TN SYSTEM AS A SOURCE	21
14	ILLUSTRATION OF THE ELEMENTS OF A TYPICAL EARTHING ARRANGEMENT	25

	<i>Page</i>
15	DIAGRAM FOR DETERMINING CONDUCTOR LENGTH ON LOAD SIDE FOLLOWING REDUCTION IN CROSS-SECTIONAL AREA 31
16	CHART SHOWING THE PROCEDURE FOR THE SELECTION OF PROTECTION SYSTEMS (INCLUDING APPLICABLE CRITERIA AND EXAMPLES OF PROTECTIVE DEVICES WHICH MAY BE USED) 34

Currently in preview, click buy full vers.

STANDARDS ASSOCIATION OF AUSTRALIA

Australian Standard

for

**ELECTRICAL INSTALLATIONS—SURFACE MINES AND
ASSOCIATED PROCESSING PLANT**

PART 2 — GENERAL PROTECTION REQUIREMENTS

SCOPE OF PART

This standard prescribes general protection requirements for electrical installations within the scope of AS 3007.1. It outlines the measures which are required for protection against electric shock in normal service from direct contact with live parts, for protection against electric shock from parts which may become live in the event of a fault (indirect contact); and for protection against the effects of overcurrent resulting from overload or short-circuit conditions.

REFERENCED DOCUMENTS

The following standards are referred to in this standard:

- | | |
|-----------|--|
| AS 1243 | Voltage Transformers for Measurement and Protection |
| AS 1675 | Current Transformers for Measurement and Protection |
| AS 1824.1 | Insulation Coordination (Phase-to-earth and phase-to-phase, above 1 kV)
Part 1 — Basic Principles, Standard Insulation Levels and Test Procedures |
| AS 1824.2 | Insulation Coordination (Phase-to-earth and phase-to-phase, above 1 kV)
Part 2 — Application Guide |
| AS 1939 | Classification of Degrees of Protection provided by Enclosures for Electrical Equipment |
| AS 2005 | Fuses with Enclosed Fuse-links (up to and including 1000 V a.c. and 1500 V d.c.)
Part 2 — Fuses for Industrial Application |
| AS 3007.1 | Electrical Installations — Surface Mines and Associated Processing Plant
Part 1 — Scope and Definitions |
| AS 3007.4 | Electrical Installations — Surface Mines and Associated Processing Plant
Part 4 — Additional Requirements for Specific Applications |
| IEC 364 | Electrical installations of Buildings
Part 3: Assessment of General Characteristics
Part 4: Protection for Safety
Chapter 41: Protection Against Electric Shock |
| IEC 215 | Guide for the Selection of Insulators in Respect of Polluted Conditions |
| IEC XXX | Protection (Protective) Systems (in preparation). |