

Australian Standard™

**Electric cables—Glass fibre insulated—
For working voltages up to and
including 0.6/1 (1.2) kV**



**STANDARDS
AUSTRALIA**

This Australian Standard was prepared by Committee EL-003, Electric Wires and Cables. It was approved on behalf of the Council of Standards Australia on 16 January 2004 and published on 20 February 2004.

The following are represented on Committee EL-003:

Australasian Railway Association
Australian Electrical and Electronic Manufacturers Association
Australian Industry Group
Canterbury Manufacturers Association New Zealand
Department of Defence (Australia)
Department of Mineral Resources NSW
Electrical Contractors Association of New Zealand
Electrical Regulatory Authorities Council
Electricity Supply Association of Australia
Institution of Engineers Australia
Ministry of Economic Development (New Zealand)
National Electrical and Communications Association

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Web Shop at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Global Standard*, has a full listing of revisions and amendments published each month.

Australian Standards™ and other products and services developed by Standards Australia are published and distributed under contract by SAI Global, which operates the Standards Web Shop.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001.

STANDARDS AUSTRALIA

RECONFIRMATION

OF

AS 3158—2004

Electric cables—Glass fibre insulated—For working voltages up to and including
0.6/1 (1.2) kV

RECONFIRMATION NOTICE

Technical Committee EL-003 has reviewed the content of this publication and in accordance with Standards Australia procedures for reconfirmation, it has been determined that the publication is still valid and does not require change.

Certain documents referenced in the publication may have been amended since the original date of publication. Users are advised to ensure that they are using the latest versions of such documents as appropriate, unless advised otherwise in this Reconfirmation Notice.

Approved for reconfirmation in accordance with Standards Australia procedures for reconfirmation on 10 October 2016.

The following are represented on Technical Committee EL-003:

Australian Cable Makers' Association
Australian Industry Group
Electrical Compliance Testing Association
Electrical Regulatory Authorities Council
National Electrical and Communications Association
Queensland University of Technology

NOTES

Currently in preview, click buy full vers.

Australian Standard™

**Electric cables—Glass fibre insulated—
For working voltages up to and
including 0.6/1 (1.2) kV**

Originated as part of AS C158—1965.
Previous edition AS 3158—1994.
Third edition 2004.

COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd
GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 5749 9

PREFACE

This Standard was prepared by the Joint Standards Australia /Standards New Zealand Committee EL-003, Electric Wires and Cables. After consultation with stakeholders in both countries, Standards Australia and Standards New Zealand decided to develop this Standard as an Australian Standard rather than an Australian/New Zealand Standard. It supersedes AS 3158—1994, *Approval and test specification—Electric cables—Glass fibre insulated for working voltages up to and including 0.6/1 kV*.

The objective of this Standard is to provide manufacturers and suppliers with construction details, dimensions and tests for cables, flexible cables and flexible cords insulated with glass fibre for use in electrical installations at working voltages up to and including 0.6/1.2 kV.

This Standard differs from the 1994 edition in the following significant ways:

- (a) Glass fibre insulated flexible cords have been included.
- (b) The insulation thickness for cables with 4 mm² conductor sizes has been increased to 1.0 mm to align with the insulation thickness of the equivalent flexible cord.
- (c) The tables of dimensions have been deleted.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the appendix to which they apply. A 'normative' appendix is an integral part of a Standard, whereas an 'informative' appendix is only for information and guidance.

Statements expressed in mandatory terms in notes to tables and figures are deemed to be requirements of this Standard.

CONTENTS

	<i>Page</i>
1 SCOPE	4
2 REFERENCED DOCUMENTS	4
3 DEFINITIONS	4
4 VOLTAGE DESIGNATION	6
5 MAXIMUM CONTINUOUS CONDUCTOR TEMPERATURE.....	6
6 CONDUCTORS.....	6
7 INSULATION	6
8 ASSEMBLY OF CORES	7
9 PROTECTIVE BRAID	8
10 IDENTIFICATION	8
11 MARKING OF PACKAGING.....	8
12 CONSTRUCTION	9
13 TESTS.....	9

APPENDICES

A PURCHASING GUIDELINES.....	12
B THE FICTITIOUS CALCULATION METHOD FOR THE DETERMINATION OF THE DIMENSIONS OF PROTECTIVE COVERINGS	13

STANDARDS AUSTRALIA

Australian Standard

Electric cables—Glass fibre insulated—For working voltages up to and including 0.6/1 (1.2) kV**1 SCOPE**

This Standard specifies construction, dimensions and tests for cables, flexible cables and flexible cords insulated with glass fibre for use in electrical installations at working voltages up to and including 0.6/1 (1.2) kV.

NOTE: Purchasing guidelines are contained in Appendix A.

2 REFERENCED DOCUMENTS

The following documents are referred to in this Standard:

AS

2706 Numerical values—Rounding and interpretation of limiting values

AS/NZS

1125 Conductors in insulated electric cables and flexible cords

1660 Test methods for electric cables, cords and conductors

1660.1 Part 1: Conductors and metallic components

1660.2.1 Part 2.1: Insulation, extruded semi-conductive screens and non-metallic sheaths—Methods for general application

1660.3 Part 3: Electrical tests

1660.4 Part 4: Complete cable and flexible cord

1660.5.6 Part 5.6: Fire tests—Test for combustion propagation

ASTM

B355 Standard specification for nickel-coated soft or annealed copper wire

3 DEFINITIONS

For the purposes of this Standard the definitions given in the referenced Standards and those below apply:

3.1 Approximate value

A value which is neither guaranteed nor checked.

3.2 Core (of cable)

The conductor with its insulation but not including any protective covering.

3.3 Direction of lay

The slope of the helically laid-up cores of a multicore cable, when the cable is held vertically.

It is right-hand when the slope is in the direction of the central part of the letter Z, and left-hand when the slope is in the direction of the central part of the letter S.