

Australian Standard®

---

**Authorization requirements for  
plumbing products—Flexible tubes**

---

This Australian Standard was prepared by Committee WS/1, Water Fittings. It was approved on behalf of the Council of Standards Australia on 14 August 1992 and published on 12 October 1992.

---

The following interests are represented on Committee WS/1:

AUSTAP

Australian Valve Manufacturers Association

Brisbane City Council

Confederation of Australian Industry

Department of Local Government, Qld

Department of Public Works, N.S.W.

Engineering and Water Supply Department, S.A.

Federated Master Plumbers of Australia

Hobart City Council

Hunter Water Board, N.S.W.

Institute of Plumbing, Australia

Master Plumbers Association of South Australia

Melbourne Water

Metal Trades Industry Association of Australia

Water Authority of Western Australia

Water Board, Sydney—Illawarra—Blue Mountains

---

*Review of Australian Standards.* To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

The titles of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

---

*This Standard was issued in draft form for comment as DR 91256.*

Australian Standard®

---

**Authorization requirements for  
plumbing products—Flexible tubes**

---

First published as AS 3499—1992.

PREFACE

This Standard was prepared by the Standards Australia Committee on Water Fittings at the request of the Committee for Plumbing Products Authorization (CPPA).

CONTENTS

	Page
1 SCOPE	1
2 REFERENCED DOCUMENTS	3
3 DEFINITIONS	3
4 SIZE DESIGNATION	3
5 MATERIALS	3
6 CONTAMINATION OF WATER	3
7 DESIGN	4
8 PERFORMANCE REQUIREMENTS	4
9 MARKING	4
 APPENDICES	
A HYDRAULIC PRESSURE TEST	5
B HEAT AGEING TEST	6

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

## STANDARDS AUSTRALIA

### Australian Standard

#### Authorization requirements for plumbing products—Flexible tubes

**1 SCOPE** This Standard specifies requirements for hot and cold water supply metallic and non-metallic flexible tubes for above ground application only, in the range of nominal sizes from DN 2 to DN 50 inclusive with a continuous working pressure not exceeding 1.4 MPa and where the normal working temperature does not exceed 95°C. Flexible tubes for cold water application capable of withstanding temperatures up to 60°C are included. The construction of flexible tubes is not included.

**2 REFERENCED DOCUMENTS** The following documents are referred to in this Standard:

AS	
1349	Bourdon tube pressure and vacuum gauges
1769	Welded stainless steel tube for plumbing applications
2345	Dezincification resistance of copper alloys
2831	Thermometers—Solid stem—Long and short—For precision use
2837	Wrought alloy steels—Stainless steel bars and semi-finished products
3500	National Plumbing and Drainage Code
3500.0	Part 0: Glossary of terms
3688	Water supply—Copper and copper alloy body compression and capillary fittings and threaded end connectors
3707	Method for testing pressure cycling resistance of pipes and fittings
3855(Int)	Suitability of plumbing products for contact with potable water

**3 DEFINITIONS** For the purpose of this Standard the definitions given in AS 3500.0 and those below apply.

**3.1 Flexible tube**—a tube intended for use between a pipework system and a fixture, fitting, valve, tap or similar, that is capable of moving or bending in any direction without damage.

**3.2 Length of tube**—the actual length of a flexible tube which shall not be less than the stated nominal length.

**4 SIZE DESIGNATION** The size to which a flexible tube is designated shall be related to the size of the bore. The designated size shall be in the range from DN 2 to DN 50.

#### 5 MATERIALS

**5.1 General** All materials in contact with water shall comply with Clause 6. Acetal plastic shall be co-polymer. Metallic materials shall be corrosion resistant and made of compatible material and resistant to variations in water quality.

NOTE: Manufacturers should consider the likelihood of acetal components being directly connected to copper-alloys and the potential for breakage which may exist. Manufacturers should provide installation instructions to warn against such connections.

**5.2 Dezincification-resistant copper alloy** Dezincification-resistant copper alloys shall comply with AS 2345.

**5.3 Stainless steel** Stainless steel shall comply with the following:

- (a) Wrought components: AS 2837, Series 300, containing not less than 8 percent nickel.
- (b) Tubular components: AS 1769.

**5.4 Corrosion-resistant materials** For the purpose of this Standard, the following metallic materials shall be deemed to be corrosion-resistant:

- (a) Copper alloy as specified in Clause 5.2.
- (b) Stainless steel as specified in Clause 5.3.

**5.5 Elastomers and plastics** Elastomers and plastics components of fittings and flexible tubing shall comply with this Standard.

**6 CONTAMINATION OF WATER** Products and materials in contact with potable water shall comply with AS 3855(Int).